

TOWNSHIP 32 SOUTH
RANGE 3 WEST

FILED

NOV 9 1988

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE

FIRST RE-ESTABLISHMENT

Quarter corner common to Sections 26 and 35, Township 32 South, Range 3 West, W.M.

Fd. projecting 15 ins., the 1 ins. diam. galvanized iron pipe, with 2 1/2 ins. diam. brass cap mkd.:

County Surveyors Office
T32S R3W
Doug. Co.
S26
1/4 —
S35
Jac. Co.
1969

Reference: Douglas County Re-establishment, page 2, date 1969. The original 14x11x5 ins. stone, mkd. "1/4" as recorded by F.Mensch in 1913, is fd. deposited alongside the above described corner monument.

Corner lies in area of recent forest fire & no trees are available, within a reasonable distance, for references. The original bearing trees, were felled (high stumped), prior to the fire. Mound stones around corner & in the top center of found charred stumps set p.k. nail through bearing tree tag:

1. 32 ins. diam. fir stump, brs. N70°E, 11.25 ft. to center.
Record; 10.56 ft.
2. 34 ins. diam. fir stump, brs. S20°W, 3.92 ft. to center.
Record; S18°W, 3.96 ft.

Corner lies on (40%) Northwest slope, 64 ft. South of creek, c. N80°W & an estimated 500 ft., N10°W of small landing alongside road (curve around ridge) c. Southeast & Southwest.

October 24, 1988
R.Frost. Tech.
S.Beecher, Tech.

Edward McGinty
County Surveyor

V=20°
p-360

#228 X

C.S. File No. 63/82-5