

JAN 20 1989

FIRST RE-ESTABLISHMENT

Quarter corner common to Sections 20 and 21, Township 32 South,
2 West, W.M.

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

9/21
#27
Fd. projecting 15 ins., the 2 ins. diam. galvanized iron pipe in mound of stone, with 3 ins. diam. brass cap, mkd. as recorded on Survey No. 3822, dated 1968. The original 18x8x8 ins. stone, mkd. "1/4" by C. Campbell in 1902, is fd. lying alongside the brass cap. Add mks. "T32SR2W CS 1988" to above noted brass cap which now reads:

T32S R2W
1/4
S20|S21
1968
OLS 536
C.S. 1988

from which original bearing trees found:

Fir stump remains fd. at record location of original northeast bearing tree. Nearby is fd. axed out (fir) face scribed "1/4 S2 B".

Sawed Fir stump, 42 ins. diam., scribed "1/4 S2" in partly exposed face, brs. record; S23°W, 27.06 ft. to center of stump.

Bearing tree mkd. on the above noted survey, now a sawed fir stump, 10 ins. diam., containing (partial) scribed "BT" in partly exposed face, brs. S49°E, 7.6 ft. Record; S48°E, 7.3 ft.

Bearing trees apparently mkd. by Douglas County Surveyor (currently not of record in this office) fd. and measured to center of trees at lower blaze: *Rec. # 125*

Douglas Fir, 12 ins. diam., scribed "1/4 S21 CS" & "BT" brs. S34 1/2°E, 5.4 ft.

Douglas Fir, 9 ins. diam., scribed "1/4 S20 CS" & "BT" brs. S56°W, 23.0 ft.

Chinquapin, 13 ins. diam., scribed "1/4 S20 CS" & "BT" brs. N57°W, 17.3 ft.

The center of found spike, thru bearing tree tag, atop a 68 ins. diam. sawed fir stump, brs. N43°E, 34.3 ft.

The peak of Mt. McLaughlin an estimated 40 miles distant, br.s S65°E.

Corner lies near the Northeast edge of standing timber at the corner of southerly and westerly edge of large clear cut.

September 7, 1988
R. Frost, Tech.
S. Beecher, Tech.

Edward McGinty
County Surveyor

V=18°
p-339-340

#1334

C.S. File No. 63/82-7