

TOWNSHIP 32 SOUTH
RANGE 2 WEST

FILED

JAN 20 1989

FIRST RE-ESTABLISHMENT

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

Section corner common to Sections 19, 20, 29 and 30, Township 32 South, Range 2 West, W.M.

Fd. projecting 6 ins. in mound of stone, the 2 ins. diam. galvanized iron pipe, with 3 ins. diam. brass cap mkd:

T32S R2W	
S19	S20

S30	S29
1968	
OLS 536	

as recorded on ^{C 555/87 Ren #42} Survey No. 3822, dated 1968. Add the mks. "CS 1988" to said brass cap, from which, original bearing trees recorded by C.Campbell in 1902, fd. as follows:

Hemlock snag, 22 ins. diam., with complete set of scribing visible, brs. S14½°E, 42.4 ft. to center of tree at base. Record; S14°E, 42.24 ft.

Hemlock, 28 ins. diam., with axed into and partly rehealed single face, brs. N6½°W, 26.90 ft. to center of tree at base. Record; 44.88 ft.

The original Southwest bearing tree, a tipped over hemlock has slid (northeasterly) down hill.

Bearing tree mkd. on Survey No. ^{C 555/87} 3822 fd:

Douglas Fir, 52 ins. diam., containing scribe mks. including "32SR2W" in partially exposed face, brs. N71½°E, 31.4 ft. to center of tree at base. Record; N69°E, 29.5 ft.

Bearing trees mkd. on Survey No. ^{M 81 15 21 113} 8437, dated 1980 fd:

Yew, 11 ins. diam., scribed as recorded, brs. S34°E, 32.1 ft. to center of tree at lower blaze. Record; S31°40'E, 32.0 ft.

Madrone, 6 ins. diam., scribed as recorded, brs. S7°W, 4.8 ft. to center of tree at lower blaze. Record; S6°52'W, 5.5 ft.

Mk a new tree "CS" "BT":

Hemlock, 7 ins. diam., brs. N55°E, 11.8 ft. to center of tree at lower blaze.

Corner lies on Northeast (45%) slope about 40 ft. South of dry branch, c. East.

September 15, 1988
R.Frost, Tech.
S.Beecher, Tech.

Edward McGinty
County Surveyor

V=18°
p-341

#1324

C.S. File No. 63/82-8