

TOWNSHIP 32 SOUTH
RANGE 3 WEST

FILED

JAN 20 1989

FIRST RE-ESTABLISHMENT

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

East Quarter corner to Section 25, only, Township 32 South, Range 3 West, W.M.

Fd. flush with the ground, the original 6x8x16 ins. granite stone, mkd. with cross on top & "1/4" on West side, by F.Mensch in 1912. Replace said stone with and deposit it alongside a 1x36 ins. galvanized iron pipe, set flush, with a 2 1/2 ins. diam. brass cap mkd:

T32W
R3W R2W
1/4 s 25 |
C.S.
1988

Original bearing trees recorded in 1912 fd. as follows:

Sawed fir stump, 60 ins. diam., brs. S77°W, 35.6 ft. to center. Record; 34.32 ft.

Burned, sawed fir stump shell, 42 ins. diam. containing reverse impression of scribe mks, in small segment of exposed (reverse) face, brs. N21°W, 54.9 ft. to center. Record; 55.44 ft.

Mk new trees "CS" "BT" and take measurements to center of trees at lower blaze:

Douglas fir, 13 ins. diam., brs S14 1/4°W, 55.94 ft.

Note: No other available trees in Section 25. All appear to be dead or dying.

Chinquapin, 8 ins. diam., brs. S55 3/4°E, 27.24 ft.

A fd. 2 ins. diam. iron pipe, projecting 10 ins., with 3 ins. diam. brass cap mkd. " 1/4 " brs. S23°E, 1.15 ft.

S25 |
1968
OLS536

T32-3 #51
#23 T32-2

C.S. 55/87

Reference: Survey No. ~~3822~~ dated 1968.

Corner lies near top of West sloping ridge, about 300 ft., S30°W, of end of logging road and an estimated 350 ft. West (downhill) of landing alongside USFS road.

September 29, 1988
R.Frost, Tech.
S.Beecher, Tech.

Edward McGinty
County Surveyor

p-353

#232
#128 T32-2 ✓
T32-3 ✓

C.S. File No. 63/82-9 C