

TOWNSHIP 32 SOUTH

RANGE 3 WEST

FIRST RE-ESTABLISHMENT

Section corner common to Sections 28, 29, 32 and 33, Township 32 South, Range 3 West, W.M.

Fd. projecting 12 ins., the 1 ins. diam. galvanized iron pipe with 2 1/2 ins. diam. brass cap mkd.:

T32S R3W
DOUG
S29 | S28

S32 | S33
JAC.
1969

(get #71)

set by Douglas County Surveyor. Reference; Survey No. 4185, dated 1969.

The original 18x8x6 ins. (serpentine) stone mkd. with "X" on top and 1 and 4 grooves on adjacent sides, is found alongside corner.

Original bearing trees mkd. by F.Mensch in 1913 fd:

The center of partial stump remains of a tipped over (large) fir, brs. N6°E, 48.18 ft. Record; N3°E.

Hemlock, 16 ins. diam. with healed blazes, brs. S80°E, 21.87 ft. to center of tree, at lower blaze. Record; S81°E, 23.10 ft.

Sawed Fir stump, 48 ins. diam., with healed blazes, brs. S76°W, 38.07 ft. to center. Record; 37.62 ft.

Sawed Fir stump, 60 ins. diam. with healed upper blaze, brs. N47°W, 8.65 ft. to center. Record; 8.58 ft.

Bearing trees mkd. by Douglas County in 1969, fd. at record location:

Cedar, 13 ins. diam. with scribe mks. visible in partly exposed face, brs. N60°E, 17.0 ft. to center.

Hemlock, 15 ins. diam. with scribe mks. visible in partly healed blaze, brs. S22°W, 14.0 ft. to center.

Mk a new tree "CS" "BT":

Douglas Fir, 11 ins. diam., brs. N20°W, 20.60 ft. to center of tree at lower blaze.

Corner lies on East slope, about 800 ft. South of location marker on 12 ins. diam. fir, located alongside road, C. N75°E.

#227x

October 6, 1988
R.Frost, Tech.
S.Beecher, Tech.

Edward McGinty
County Surveyor

V=18°
p-356

FIRST RE-ESTABLISHMENT

Quarter corner common to Sections 28 and 33, Township 32 South, Range 3 West, W.M.

Fd. projecting 12 ins., 1 ins. diam. galvanized iron pipe with 2 1/2 ins. diam. brass cap mkd: County Surveyors Office

Doug. Co.
S28
1/2 —
S33
Jack. Co.
1969

(get #125)

with the original (1913) 16x9x8 ins. stone mkd. "1/2" fd. alongside.

Original bearing trees recorded by F.Mensch in 1913 fd;

Douglas Fir, 40 ins. diam., with healed blazes, brs. record; N10°E, 31.7 ft. to center of tree at base.

Douglas Fir, 82 ins. diam., with scribe mks. visible in partly exposed lower face, brs. record; S50°W, 33.0 ft. to center of tree at lower blaze.

Mk a new tree "CS" "BT":

Hemlock, 6 ins. diam. brs. S29°E, 9.7 ft. to center of tree at lower blaze.

Corner lies an estimated 120 ft. East of the East Fork of Applegate Creek and about 350 ft. West of location marker on 36 ins. diam. fir alongside road c. N5°E and Southeast.

See also Survey No. 4185, dated 1970.

September 26, 1988
R.Frost, Tech.
S.Beecher, Tech.

Edward McGinty
County Surveyor

V=18°
p-352

#226x