

FILED

MAR 16 1990

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

Douglas County

I recently found and recorded the following corners in Section 17, Township 31 South, Range 9 West, Willamette Meridian:

I find a 1/2" iron pipe set by Clifford Stephens at the corner of Sections 17, 18, 19, and 20. I also find the 1967 1" BLM brass cap pipe lying on the ground nearby so I lay it against the 1/2" pipe. I find the original 36" fir B.T. North 70° East 34 links is now a 48" stump with face grown over and the original 16" fir B.T. South 32° West 57 links is now 26" with face grown over. I chop an "X" on the stump of the original 24" Cedar B.T. North 60° West 57 links and scribe "S20 BT 378" on a 16" fir South 37°15' East 31.5' to the center.

I set a 5/8" iron rod with yellow plastic cap for the 1/4 Section Corner between Sections 17 and 20 from the original 30" fir B.T. South 5° East 43 links which is now 40" with a B.T. tag. The original 24" fir B.T. North 54° West 62 links has been bulldozed out. A 3/4" iron pipe bears North 82° East 5.3' from the corner. I scribe "1/4 S17 BT 378" on a 6 foot fir North 29° East 12.7' to the center and I chop a low "X" on the original B.T. I also set an iron fence post 0.4' North of the corner.

I find a 3/4" iron pipe at the C.S. 1/16 Corner of Section 17. I find the 44" fir B.T. South 14° East 13.1' is now a windfall. I scribe "1/16 S17 BT 378" on a 48" Cedar stump North 36°30' West 8.0' to face and "1/16 S26 BT" on a 26" White fir South 43°40' East 28.5' to center. I also set an iron fence post 0.4' North of the corner.

I find a 3/4" iron pipe at the Southeast 1/16 Corner of Section 17 and a 48" fir B.T. with face grown over bearing North 9° West 10.4'. I scribe "1/16 S17 BT 378" on a 20" Hemlock South 41°15' West 41.9' to center.

Jack E. LaFlamme
R.O.L.S. 378

Date 3-14-90

REGISTERED
PROFESSIONAL
LAND SURVEYOR

J. E. LaFlamme

OREGON
MAY 21 1989
JACK E. LAFLAMME
378

#171 +
COUNTY
Range # 31
#172 +
#173 +
#174 +
#175 +
#176 +
#177 +
#178 +
#179 +
#180 +