

**MAX H. HULL Land Surveying**

Office 476-2425

602 N.W. 5th. Street Grants Pass, Oregon 97526

SURVEY NARRATIVE to comply with Paragraph 209.250, O. R. S.

DATE: April 10, 1973

FILED *JR*FOR: Josephine County Forestry Department
County Courthouse
Grants Pass, Oregon

NOV 2 1992

AND: William F. Johnson
202 S.E. H Street
Grants Pass, OregonCOUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

PURPOSE: To Survey the perimeter and the North, South Center line of Section 16, Township 33 South, Range 7 West, Willamette Meridian, Josephine County, Oregon, and to mark true line for timber cutting.

PROCEDURE: Starting at the Southeast corner of Section 16 at which point I set a 5/8" Iron Rod from the original Bearing Trees

A Maple 16 ins. diam. chopped out, bears South 65° West 31.02'
 A Fir 7 ft. diam. down and dead, bears North 62° East 13.86'

Thence I traversed North to the Northeast corner of Section 16 at which point I found a Douglas County Brass Cap from which I found new Bearing Trees

A Fir 14 ins. diam. bears North $78\ 1/2^{\circ}$ West 16.2 feet
 A Fir 15 ins. diam. bears North 53° East 17.6 feet
 A B. Oak 7 ins. diam. bears South $8\ 1/2^{\circ}$ East 28.7 feet

Thence I conducted a diligent search for evidence of the East 1/4 corner and found a decayed Fir stump, 26 ins. diam. with healed over growth and old axe marks evident in the remaining bark. I then set a 5/8" Iron Rod North 70° East 20.46 feet and scribed new bearing trees as noted on the plat; thence I returned to the Southeast corner of Section 16 and traversed North $87^{\circ}49'20''$ West 2732.14 feet to the South 1/4, at which point I found a 4 in. by 4 in. post from which I found the original Bearing Trees.

A Fir snag 10 ins. diam. with scribe, bears North 21° West 10.56'
 A rotted Fir stump bears South 64° West 5.94 feet

At the corner point I set a 5/8" Iron Rod and scribed new Bearing Trees as noted on the plat; thence I traversed South $89^{\circ}36'49''$ West 2657.87 feet to the Southwest corner of


MAX H. HULL Land Surveying

602 N. W. 5th. Street Grants Pass, Oregon 97526

Section 16, at which point I found a 2 in. Fir hub from which I found the original bearing trees

- A Fir 30 ins. diam. with scribe bears South 44° East 7.26 feet
- A Pine stump 36 ins. diam. bears North 35° East 34.32 feet
- A Laurel stool bears South 85° West 17.82 feet
- A Laurel stool bears North 30° West 4.62 feet

at the corner point I set a 5/8" Iron Rod and scribed new Bearing Trees as noted on the plat.

Thence I traversed North 1°59'04" East 2658.69 feet and conducted a diligent search for the West 1/4. Being unable to find any evidence of the corner or its' accessories, I continued North 1°59'04" East 2658.69 feet and searched for the Northwest corner of Section 16. I then continued North 1°59'04" East 2658.69 feet to the West 1/4 corner of Section 9, at which point I found a Douglas County Brass Cap from which I found new Bearing Trees

- A Fir 26 ins. diam. bears South 35° West 20.00 feet
- A Fir 39 ins. diam. bears North 20° East 25.10 feet

Thence I set a temporary point on line and at the proportioned distance for the Northwest Section corner; thence South 87°27'30" East 2600.65 feet at which point I searched for the North 1/4 corner. Being unable to find any evidence, I continued South 87°27'30" East 2600.65 feet to the Northeast Section corner; thence I returned to the temporary Northwest corner; thence South 89°42'45" West, at 211.20 feet (3.20 ch. original field noted) I was on top of North and South Ridge described in the original field notes; thence continuing South 89°42'45" West at 2527.07 feet from the temporary Section corner, I found the North 1/4 corner of Section 17, at which point I found a 3 in. by 3 in. by 30 in. Fir post 24 in. in the ground from which I found the original Bearing Trees

- A S. Pine snag 50 ins. diam. bears South 23° West 18.9 feet
- A Fir 14 ins. diam. bears North 11° West 23.1 feet

I thence returned to the temporary Northwest Section corner and conducted another thorough search; thence I set the Northwest Section corner at the proportionate North and South distance and from the call to the top of the ridge of 3.2 chains;

FILED

NOV 2 1992

 COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.



Office 476-2425

MAX H. HULL Land Surveying

602 N.W. 5th. Street Grants Pass, Oregon 97526

thence I set the West 1/4 as shown on the plat; thence I set the North 1/4 as shown on the plat, from which I ran on true line, South 1°22'35" West 5152.38 feet to the South 1/4 corner.

Meridian is based on a solar observation.

FILED *jp*
NOV 2 1992
COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Max H. Hull

OREGON
JULY 11, 1969
MAX H. HULL
901

C.S. File No. 63/115-4

JUN 8 1973