

SURVEY NARRATIVE to comply with O.R.S. 209.250

FILED

DATE: March 3, 1994.  
SURVEYED FOR: City of Glendale  
P.O. Box 361  
Glendale, Oregon 97442  
SURVEYED BY: Gerald V. Nygren, PLS  
522 Barker Drive  
Merlin, Oregon 97532

Date: 5/26/94 By: JP  
This survey consists of:  
Map: M 118-79  
Narrative: C.S. 63/134  
Corner Rpt: \_\_\_\_\_

DOUGLAS COUNTY, OR  
SURVEYOR

LOCATION: Sections 5, 6, 7 and 8, Township 33 South,  
Range 6 West, Willamette Meridian, Douglas  
County, Oregon.

PURPOSE: To survey and mark the following lines:  
The North line, East line and East Half of the  
South line of the South Half of the Southwest  
Quarter of said Section 5; The North and West  
lines of the Southeast Quarter of the Southeast  
Quarter of said Section 6; The West and South  
lines of the Northeast Quarter of the Northeast  
Quarter of said Section 7; The South and East  
lines of the Northwest Quarter of the Northwest  
Quarter of said Section 8.

PROCEDURE: I recovered and held to monuments shown as  
found on survey Map.

The following described corners were used to  
control this survey or were set in this survey:

- (1) At the Quarter corner for Section 6 only I found a  
1 1/2" galvanized iron pipe with 3" brass cap stamped:

Ore. St. Bd. of Forestry  
1/4 S6

1964  
RS 359

Reference found this survey:

A Douglas Fir 17 inches in diameter, bears S02°W, 35.8  
feet distance, healed blaze.

A Douglas Fir 14 inches in diameter, bears N49°E, 12.3  
feet distance, healed blaze.

(continued on page 2)

(continued from page 1)

- (2) At the West Quarter corner of said Section 6, I found a 1 1/2" galvanized iron pipe with 2 1/2" brass cap stamped:

DEPARTMENT OF INTERIOR  
BUREAU OF LAND MANAGEMENT  
1/4

S1 S6

R7W R6W  
T33S  
1963

References found this survey:

A Douglas Fir, 20 inches in diameter, bears N17°E, 8.9 feet distance, healed blaze.

A Incense Cedar, 13" in diameter, bears N10°W, 27.7 feet distance, visible scribe.

- (3) At the Quarter corner common to Sections 5 and 6, I found a 1 1/2" galvanized iron pipe with a 3" brass cap stamped:

Ore. St. Bd. of Forestry  
1/4  
S6 S5  
1964  
RS 359

References found this survey:

A Madrone, 28 inches in diameter, bears N80°W, 11.9 feet distance, visible scribe.

A Chinquapin, 12 inches in diameter, bears S21°E, 10.6 feet distance, visible scribe.

A Fir stump 56 inches in diameter, bears N68°W, 32.2 feet distance.

- (4) At the Center Quarter corner of said Section 5, I found a 5/8" iron rod with yellow plastic cap marked "HULL RS 901".

References found this survey:

A Douglas Fir, 9 inches in diameter, bears S88°E, 14.1 feet distance, visible scribe.

A Douglas Fir, 9 inches in diameter, bears N48°E, 19.8 feet distance, visible scribe.

(continued on page 3)

(continued from page 2)

A Douglas Fir, 13 inches in diameter, bears N62°W, 19.0 feet distance, healed blaze.

A Maple, 12 inches in diameter, bears S61°W, 25.0 feet distance, visible scribe.

- (5) At the Southeast One-sixteenth corner of said Section 6, I set a 5/8" X 30" iron rod with yellow plastic cap marked "NYGREN LS 1035".

New references established this survey:

Douglas Fir, 12 inches in diameter, bears N30°E, 8.3 feet distance, scribed "SE 1/16 S6 BT".

A Madrone, 20 inches in diameter, bears N70°W, 10.0 feet distance, scribed "SE 1/16 S6 BT".

- (6) At the South One-sixteenth corner common to Sections 5 and 6, I set a 5/8" X 30" iron rod with yellow plastic cap marked "NYGREN LS 1035".

New references established this survey:

A Douglas Fir, 5 inches in diameter, bears N38°E, 8.2 feet distance, scribed "X BT".

A Tan Oak, 5 inches in diameter, bears S44°E, 4.8 feet distance, scribed "X BT".

- (7) At the Center South One-sixteenth corner of said Section 5, I set a 5/8" X 30" iron rod with yellow plastic cap marked "NYGREN LS 1035".

New references established this survey:

A Douglas Fir, 8 inches in diameter, bears N20°W, 25.4 feet distance, scribed "CS 1/16 S5 BT".

A Madrone, 7 inches in diameter, bears N70°E, 21.9 feet distance, scribed "CS 1/16 S5 BT".

- (8) At the Quarter corner common to Sections 6 and 7, I found a 1 1/2" iron pipe with a 2 1/2" brass cap stamped:

DEPARTMENT OF INTERIOR  
BUREAU OF LAND MANAGEMENT  
T 33 S R 6 W  
S 6  
1/4  
S 7  
1964

References found this survey:

(continued on page 4)

(continued from page 3)

A Douglas Fir, 12 inches in diameter, bears N85°W, 53.5 feet distance, healed blaze.

A Douglas Fir, 29 inches in diameter, bears S38°E, 58.1 feet distance, healed blaze.

- (9) At the East One-sixteenth corner common to Sections 6 and 7, I found a 1 1/2" iron pipe with a 2 1/2" brass cap stamped:

DEPARTMENT OF INTERIOR  
BUREAU OF LAND MANAGEMENT  
S 6 E 1/16  
S 7  
1964

References found this survey:

A Douglas Fir, 12 inches in diameter, bears N14°W, 21.1 feet distance, healed blaze.

A Douglas Fir, 15 inches in diameter, bears S23°W, 62.0 feet distance, healed blaze.

- (10) At the corner of Sections 5,6,7 and 8, I found 1 1/2" iron pipe with a 2 1/2" brass cap stamped:

COUNTY SURVEYORS OFFICE  
1963            S 6   S 5   T 33 S  
                  -----  
                  S 7   S 8   R 6 W

References found this survey:

A Douglas Fir, 14 inches in diameter, bears S80°E, 77.2 feet distance, healed blaze.

A Madrone, 14 inches in diameter, bears S10°E, 7.9 feet distance, healed blaze.

A Madrone, 14 inches in diameter, bears S20°W, 7.3 feet distance, healed blaze.

- (11) At the West One-sixteenth corner common to Sections 5 and 8, I set a 5/8" X 30" iron rod with yellow plastic cap marked "NYGREN LS 1035".

New references established this survey:

A Douglas Fir, 6 inches in diameter, bears N30°W, 7.1 feet distance, scribed "W 1/16 S5 BT".

(continued on page 5)

(continued from page 4)

A Douglas Fir, 9 inches in diameter, bears S56°W, 10.6 feet distance, scribed "W 1/16 S8 BT".

- (12) At the Quarter corner common to Sections 5 and 8, I set a 5/8" X 30" iron rod with yellow plastic cap marked "NYGREN LS 1035".

New references established this survey:

A Douglas Fir, 8 inches in diameter, bears S76°W, 24.4 feet distance, scribed "1/4 S8 BT".

A Douglas Fir, 8 inches in diameter, bears S67°E, 11.2 feet distance, scribed "1/4 S8 BT".

A Douglas Fir, 7 inches in diameter, bears N62°W, 32.2 feet distance, scribed "1/4 S5 BT".

A Madrone, 12 inches in diameter, bears N70°E, 28.6 feet distance, scribed "1/4 S5 BT".

- (13) At the corner of Sections 4,5,8 and 9 I found a 2 1/2" galvanized iron pipe with brass cap stamped:

DEPARTMENT OF INTERIOR  
BUREAU OF LAND MANAGEMENT  
T 33 S R 6 W

S 5 S 4

S 8 S 9

1963

References found this survey:

A Cedar, 23 inches in diameter, bears S82°20'W, 16.0 feet distance, healed blaze.

A Cedar, 33 inches in diameter, bears S01°35'W, 51.2 feet distance, healed blaze.

A Cedar, 18 inches in diameter, bears S63°52'E, 35.9 feet distance, visible scribe.

A Cedar, 33 inches in diameter, bears N19°56'E, 89.5 feet distance, healed blaze.

- (14) At the Northeast One-sixteenth corner of said Section 7, I found a 2 1/2" galvanized iron pipe with 2 1/2" brass cap marked:

(continued from page 5)

DEPARTMENT OF INTERIOR  
BUREAU OF LAND MANAGEMENT  
NE 1/16  
S 7

1964

References found this survey:

A Douglas Fir, 11 inches in diameter, bears N23'E, 33.7 feet distance, healed blaze.

A Douglas Fir, 10 inches in diameter, bears S1'E, 54.1 feet distance, healed blaze.

- (15) At the North One-sixteenth corner common to Sections 7 and 8, I found a 2 1/2" galvanized iron pipe with a 2 1/2" brass cap stamped:

DEPARTMENT OF INTERIOR  
BUREAU OF LAND MANAGEMENT  
N 1/16

S 7      S 8

1964

References found this survey:

A Douglas Fir, 18 inches in diameter, bears S66'E, 60.7 feet distance, healed blaze.

A Douglas Fir, 18 inches in diameter, bears N9'W, 73.3 feet distance, healed blaze.

- (16) At the Northwest One-sixteenth corner of said Section 8, I set a 5/8" X 30" iron rod with yellow plastic cap marked "NYGREN LS 1035"

New references established this survey:

A Douglas Fir, 5 inches in diameter, bears N66'E, 16.1 feet distance, scribed "X BT".

A Madrone, 13 inches in diameter, bears N15'E, 28.3 feet distance, scribed "NW 1/16 S8 BT".

- (17) At the Quarter corner common to Sections 7 and 8, I found 2 1/2" galvanized iron pipe with a 2 1/2" brass cap stamped:

(continued from page 6)

DEPARTMENT OF INTERIOR  
BUREAU OF LAND MANAGEMENT  
1/4

S 7 S 8

T 33 S R 6 W  
1964

References found this survey:

A Douglas Fir stub, 8 inches in diameter, bears N79°W  
6.60 feet distance, visible scribe.

- (18) At the Quarter corner common to Sections 8 and 9, I  
found a 2 1/2" iron pipe with 2 1/2" brass cap stamped:

COUNTY SURVEYORS OFFICE

T 33 S R 6 W

1/4 S 8 S 9

1967

References found this survey:

A Cedar, 28 inches in diameter, bears S43°E, 23.8 feet  
distance, visible scribe.

A Alder, 12 inches in diameter, bears N34°E, 7.0 feet  
distance, healed blaze.

- (19) At the Quarter corner common to Sections 8 and 17, I  
found 2 1/2" galvanized iron pipe with 2 1/2" brass cap  
stamped:

COUNTY SURVEYORS OFFICE

T 33 S R 6 W

S 8

1/4

S 17

1967

References found this survey:

(continued on page 8)

(continued from page 7)

A Douglas Fir, 55 inches in diameter bears S85°W, 38.3 feet distance, visible scribe.

A Tan Oak, 15 inches in diameter, bears N48°W, 26.0 feet distance, healed blaze.

Bearings based on the North line of the Southwest Quarter of Section 5 per RM 103-3/CS file 63/24(N).


This survey was executed with a Mac 1E EDM and Wild T-16 Theodolite.

FILED

Date: 5/26/94 By: JP  
This survey consists of:  
Map: M 118-79  
Narrative: C.S. 63/134  
Corner Rpt: \_\_\_\_\_

DOUGLAS COUNTY  
SURVEYOR

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR



OREGON  
GERALD V. NYGREN  
AUGUST 22, 1975  
1035

EXPIRES 12-31-94