

FILED

MAPPING CONTROL SURVEY
for
DOUGLAS COUNTY PUBLIC WORKS DEPARTMENT
Sections 21, 22, 27 & 28, T30S, R5W, W.M.
APRIL 1995

Date: 12-7-95 By: JC
This survey consists of:
Map: C.S. 63/164-3
Narrative: _____
Corner Rpt: _____

Survey by: Douglas County Public Works
Courthouse Rm. 304
Roseburg, Oregon 97470

Purpose: To establish horizontal control on existing
section corner and DLC corner for mapping
of Gazley Road.

Personnel: Don Beecroft, Bob Barrett, Roger Beebe
and Mike Koch.

Equipment: Lietz Set 2 Total Station

Precision: FGCC Order 3 Class II

DOUGLAS COUNTY
SURVEYOR

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Donald G. Beecroft Jr.

OREGON
JULY 25, 1991
DONALD G. BEECROFT JR.
2490

EXPIRES: 12-31-95

All 1927 horizontal control station positions held are from the DCSO 1927
record in the Douglas County Surveyors Office geodetic control books. All
1927 horizontal control positions established have been adjusted using those
control stations.

CONTROL HELD

<u>STATION</u> <u>DESIGNATION</u> NORTHING	<u>STATION</u> <u>NAME</u> EASTING	<u>MONUMENT</u> <u>TYPE</u>	<u>MONUMENT</u> <u>MARKINGS</u>	<u>SEC</u>	<u>TWP</u>	<u>RNG</u>
#-112 476885.34	30528A 1253790.98	BC/OVERPASS	"30528A 1978"	28	30S	5W
#-113 476862.01	30528B 1253994.63	BC/OVERPASS	"30528B 1978"	28	30S	5W
P-076 471786.31	PTS22 1255668.69	BC/CONCRETE	"PTS22 1978"	27	30S	5W
477505.24	WCNWDLC51 1254487.74	BC/I.P.	"T30S R5W WITNESS COR NW COR DLC 51 1976"	21	30S	5W

CONTROL ESTABLISHED

<u>STATION</u> <u>DESIGNATION</u> NORTHING	<u>STATION</u> <u>NAME</u> EASTING	<u>MONUMENT</u> <u>TYPE</u>	<u>MONUMENT</u> <u>MARKINGS</u>	<u>SEC</u>	<u>TWP</u>	<u>RNG</u>
477544.38	NWCOR DLC51 1254533.21	1½" I.P.		22	30S	5W
476925.87	NWCOR27 1254515.79	BC/I.P.	"T30S R5W S21 S22 S27 S28 1973"	27	30S	5W

BC=BRASS CAP
I.P.=IRON PIPE

C.S. File No. 63/164-3