





County Surveyor's Record, Douglas County, Oregon

590  
73

Metes and Bounds  
Survey of Tract No. 61, T. 28 S., R. 7 W.

CHAINS				
18.54	Intersect the N. bdy. of the John Coats D.L.C. No. 59, 6 lks. S.89*30'W. from Cor. No.1 thereof, heretofore described.			
40.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for Cor. No. 1 of this Survey, with brass cap marked			
	<table border="1"> <tr><td>API</td></tr> <tr><td>TR61</td></tr> <tr><td>1924</td></tr> </table>	API	TR61	1924
API				
TR61				
1924				
	Thence			
	West, along the N. bdy. of Tract No. 61.			
17.25	Wire fence, bears N. and S.; enter grain field.			
26.30	Board fence, bears N. and S.; leave grain field.			
28.50	Old rail fence, bears N. and S.; enter field.			
36.25	Intersect the W. bdy. of original sec. 30, T.28 S., R. 7 W., Ford survey,			
	At the point of intersection			
	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for cor. No. 2 of this survey, with brass cap marked			
	<table border="1"> <tr><td>AP2</td></tr> <tr><td>TR61</td></tr> <tr><td>1924</td></tr> </table>	AP2	TR61	1924
AP2				
TR61				
1924				
	Thence			
	S.1*30'W., along the W. bdy. of original sec. 30, on the W.bdy. of Tract No. 61.			
0.48	Intersect the S. bdy. of T. 28 S., R. 7½ W., which is at the intersection of the Ford and Hathorn range lines, hereafter described.			
10.84	NW. cor. of Newland's barn, bears East, 25 lks. dist.			
11.75	Road, bears NW. and SE.			
12.90	Road, bears E. and W.			
13.40	Enter field, bears E. and W.			
14.00	Intersect Cor. No. 3 of this survey, identical with the original Ford. cor. of secs. 30 and 31, on the W.bdy. of the Tp., hereafter described, and the place of beginning			

31.68

C.S. File No. 6411