

GOVERNMENT CORNER RESTORATION FORM

FILED

JK

Township 26S Range 6W Sec. 31 County DOUGLAS

State OREGON Date 1/5/90 No. _____

JAN 9 1990

Corner Designation

1/4 S36 | S31

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE

- _____ Condition Report Only
- _____ Not Found
- Renewed
- _____ Unrecorded
- _____ Surveyed In
- _____ Referenced Out

Previous Renewals T26-6 #160 T26-7 #82

MONUMENT DETAIL

Monument(s) Found: (Condition and Source)

A 2 1/2" DIA. BRASS CAP ON A 1/4 IN O.D. IRON PIPE THAT PROTRUDES 4 IN ABOVE GROUND (FROM REN #160)

5/8" I.R. SET AT A POSITION FOR 1/4 CORNER IN REN #160 IS UNDER AC IN ROAD. A STRONG METAL READING WAS TAKEN AT A POINT 30 FT WEST OF W.C.

W. C.
30 WEST TO
T26S

R
1/4 7 S36 | S31 6
W W

L.S. 544
1967

Accessories Found:

BEARINGS AND DISTANCES TAKEN FROM W.C.

16" NOW 19" DIA. W. OAK WITH FULLY HEALED DOUBLE BLAZE, BEARS S16°W, 16.3 FT (AGREES WITH REC) PER REN #160

5/8" I.R. PROPERTY PIN BEARS WEST, 1.19 FT (AGREES WITH REC) (SEE M35-17)

5/8" I.R. PROPERTY PIN BEARS N1 1/2°W, 59.87 FT (REC. N1°08'09"W, 60.01) (SEE M35-17)

NO ORIG. BT'S FOUND

#192 T26-6 X
#118 T26-7 X

RENEWAL

Monument Set (Procedure and Description)

NONE

Monument Detail

N/A

New Accessories

5/8" I.R. WITH YELLOW PLASTIC CAP MARKED "L.S. 1075"
BEARS S 50 3/4° W, 78.90 FT.

5/8" I.R. WITH ALUM CAP (CRRW 10+00.00 PT. ON SOUTH SIDE OF
CLEVELAND LP DR) BEARS N 19 1/2° E, 197.40 FT.

5/8" I.R. WITH ALUM CAP (CRRW 10+46.76 PC ON SOUTH SIDE OF
CLEVELAND LP DR) BEARS N 32 3/4° E, 202.36 FT

Sketch of Monument, Accessories, and General Area

Location & Comments

CORNER LIES 1/2 FT
NORTH OF THE INTERSECTION
OF A NORTH - SOUTH
AND EAST RUNNING FENCE
LINE.

Comp. Declin. 18° E
Agency DLSD
Party Chief RANDALL W. SMITH
Notekeeper Randall W. Smith
Witnesses STEPHEN J. FLAUS

Address

Surveyor's Seal

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Larry E. Monrean

OREGON
JULY 13, 1979
LARRY E. MONREAN
#1830

