

GOVERNMENT CORNER RESTORATION FORM

FILED

Township 30S Range 2W Sec. 21 County DOUGLAS

*SR*

APR 1 1991

State OREGON Date MARCH 18, 1991

No. \_\_\_\_\_

COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE.

Corner Designation

1/4 S21  
S28

- \_\_\_\_\_ Condition Report Only
- \_\_\_\_\_ Not Found
- Renewed
- \_\_\_\_\_ Unrecorded
- \_\_\_\_\_ Surveyed In
- \_\_\_\_\_ Referenced Out

MONUMENT DETAIL

Previous Renewals # 162, 1909 RETRACEMENT

Monument(s) Found: (Condition and Source)

BASALT STONE SET IN 1909 RETRACEMENT AND FOUND IN RENEWAL #162 IS SEARCHED FOR BUT NOT FOUND.  
A 2 1/2 INCH DIAMETER BRASS CAP MARKED AS AT RIGHT ON A 1 1/2 INCH O.D. IRON PIPE IS FIRMLY SET AND PROTRUDS 10 INCHES ABOVE GROUND.

COUNTY SURVEYORS OFFICE

T30S R2W

1/4 S21  
S28

1968

Accessories Found:

FROM 1909 RETRACEMENT ONE ORIGINAL BEARING TREE FOUND. A HEMLOCK, 18 IN. DIAM. NOW A 24 INCH D.B.H. HEMLOCK WITH THE SCRIBING "1/4 B BT" PARTLY VISIBLE ON A PREVIOUSLY OPENED DOUBLE BLAZE BEARS S 60° E, 14 1/2 FEET DISTANT (RECORD S57° E, 14 1/2 FEET DISTANT).

NO EVIDENCE NORTH WEST BEARING TREE FOUND.

FROM RENEWAL #162 ONE ADDITIONAL BEARING TREE FOUND. A 16" HEMLOCK NOW A 19 INCH D.B.H. 5 1/2 FOOT TALL ALUMINIUM CAPPED HEMLOCK STUMP WITH A FULLY HEALED DOUBLE BLAZE BEARS N 25° W, 13 1/2 FEET DISTANT (RECORD N22° W, 13 1/2 FT.).

278 X

