

Township 235 Range 10W Sec. 27 County DOUGLAS

State OREGON Date JULY 23, 1992 No. \_\_\_\_\_

JUL 31 1992

Corner Designation

S28	S27
S33	S34

COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE.

- Condition Report Only
- Not Found
- Renewed
- Unrecorded
- Surveyed In
- Referenced Out

Previous Renewals # 17, # 43

Monument(s) Found: (Condition and Source)

A 3 INCH DIAMETER BRONZE CAP (MARKED AS AT RIGHT) ON A 1 1/2" I.D. GALVANIZED IRON PIPE, FIRMLY SET, AND PROTRUDING 6 INCHES FROM GROUND, FROM RENEWAL # 43.

OREGON STATE BOARD OF FORESTRY

T235 R 10W

S28	S27
-----	-----

S33	S34
-----	-----

1958

RS 359

Accessories Found:

NO EVIDENCE OF ORIGINAL BT'S FOUND, LOGGING AND ROAD WORK IN AREA HAS OBLITERATED REMAINS OF WINDFALLS AND OLD STUMPS (RENEWAL #17). EVIDENCE OF THREE BEARING TREES, NEW IN RENEWAL # 43, IS FOUND.

A 27" FIR NOW A 3 FOOT TALL 48 INCH DIAMETER D. FIR STUMP WITH A FULLY HEALED SINGLE BLAZE BEARS N 26° E, 46 1/2 FEET DISTANT (RECORD N 26° E, 45.9 FT. THIS IS A REASONABLE FACE MEASUREMENT).

A 15" FIR NOW AN UPROOTED 7 FOOT TALL 22 INCH DBH. FIR STUMP WITH A FULLY HEALED SINGLE BLAZE THE ROOT HOLE OF WHICH AGREES WELL WITH THE RECORD BEARING AND DISTANCE N 43° W, 37 1/2 FT.

A 22" FIR NOW A 2 1/2 FOOT TALL 28 INCH DIAMETER D. FIR STUMP WITH THE SCRIBING "S R10W S" VISIBLE IN THE REMAINS OF A PARTIALLY OPENED SINGLE BLAZE, BEARS S 39° E, 24 1/2 FEET DISTANT (RECORD S 42° E, 23 1/4 FT. THE DISTANCE IS A REASONABLE FACE MEASUREMENT).

NO EVIDENCE OF SW BEARING TREE IS FOUND, MEASUREMENT FALLS IN A ROAD.

AN UNRECORDED REFERENCE IS FOUND. A ROTTED 2 FOOT TALL 6 INCH DIAMETER CHINQUAPIN STUMP WITH A WEYERHAEUSER LOCATION TAG BEARS S 28° W 12 1/2 FEET DISTANT (AGREES WITH WEYERHAEUSER TAG).

#116 ✓

CS File No. 64/31-1c

