

FILED

92

Date: 6-16-97 By: SC

This survey consists of:

Map: \_\_\_\_\_

Narrative: \_\_\_\_\_

Corner Rpt: 64/76-2

DOUGLAS COUNTY  
SURVEYOR

**Office U. S. Surveyor General,**

Portland, Oregon. Nov 8, 1883

The following Field Notes of the Survey of the

7<sup>th</sup> Standard Parallel South

executed by

R. S. Dickerson

under his Contract No.

474, dated

May

10,

1883,

having been critically examined, the

necessary corrections and explanations made, the said field notes

and the survey they describe, are hereby approved.

James C. Tolman

Surveyor General.

C.S. File No. 64/76-2

TRANSCRIBED COPY OF ORIGINAL  
FIELD NOTES

58  
147

Extensions of T. 32 S. R. 9 W.  
Willamette Meridian, Oregon.

From the corner to Township 32 S R. 9 W. 8 and 9 W I run West on a Random line along the N. E. of T 32 S R 9 W. The variation of my compass being  $19^{\circ}45'$  I set temporary half mile and mile corners at each 40 and 80 chains. and find the township line to be 5 miles. 70 chains and 61 links long and the falling off to be 10 W. S. of the corner to Township 32 S R. 9 W. There being practically no correction I establish the Random as the true line.

And from the corner to Tps 32 S R. 9 W. I run June 15<sup>th</sup> & 16<sup>th</sup>

East on a true line along N. E. of sec 6.  $N. 19^{\circ}45' E$

7.00 Top of high Mountain S slope of <sup>same</sup> Mountain Sec 6.

87.61 A Laurel 4 in in diam which I mark 14 S on the N. side for the 14 Sec Co and from where a 6 in 60 in in diameter S 10 E 41 W. old. Marked 14 S. 15 S. O.S. File No. 64/762

T31-9  
162100

A 30 in in diam ...

59  
148

Patentees of T. 32 S R. 2 W.

Williamson Brothers, Oregon.

Enter

Marked 14 S - 13 J

Orat on

64.50 A block 40 lbs wide c. h. Step 20 cent

77.51 Set a stone 16 x 10 x 8 in 10 in in the ground

T 31-9 226100

for the cor. to sec 5. 6. 31 & 32. Marked with 5 notches on the C and 1 notch the W edge. and from which

15.00  
40.00  
in

A Laurel 5 in in diam bear at 53° 22 lbs dia

Marked T 31 S R 9 W S 29 - 13 J.

A fir 18 in in diam bear S 25° E 47 lbs dia

Marked T 32 S R 9 W S 5 - 13 J.

A fir 35 in in diam bear S 45° W 17 lbs dia

Marked T 32 S R 9 W S 6 - 13 J.

A Laurel 8 in in diam bear at 263° 25 lbs dia

66.80  
80.00

Marked T 31 S R 9 W S 31 13 J.

Land high mountainous & broken  
covered with brush, most chiefly fir, and  
Soil 3/4 red

Thick underneath. Live oak, fir  
and Laurel.



61

Estimates at 32 S. R. 2 W

60

150

Winnemucca Meridian, Oregon.

A fir 50 in in diam base S 62° E 35 ft. dia. Crown

Marked T 37 S 18° W S 4. 13 T.

A fir 8 in in diam base S 25° W 25 ft. dia.

Marked T 32 S 14° W S 5 - 13 T. 14.50

A fir 20 in in diam base S 52° W 35 ft. dia. 39.60

Marked T 34 S 16° W S 32 - 13 T. 40.00

Land Mountains

Soil 3<sup>d</sup> oak, covered with An

Dense forest of fir, Laurel and P.

Also thick undergrowth of Rhododendron An

Laurel and fir.

June 16<sup>th</sup> 1883.

45.00

80.00

Extensions

T. 32 S

R. 9 E

151<sup>62</sup>

W. 1/2 Sec. 4, Oregon

Over on a true line on N. E. of Sec 4.

$\theta = 19^{\circ} 45' E$

Ascend,

14.50 Top of Spear C. A. Descend.

39.60 A Corn 40 lbs. wide C. A.

T31.9  
364100

40.00 A yew tree 14 in in diam which I marked  
14 in on N. side for the West Co. from which

An Alder 10 in in diam bear S 57 W 50 lbs. dia  
marked 14 S-13. J.

An Alder 14 in in diam bear N 50 W 42 lbs. dia  
marked 14 S-13. J.

Step Ascend

45.00 Gradual "

80.00 A fir 10 in in diam which I marked

T313 R9 N S 54 on N E

T32 S S 3 on S E

84 in dia and S 55 on N W face also 3

notches on the E and W angles of same for

the corner to Secs 3, 4, 33, 7, 34

and from which

A fir 50 in in diam bear N 32 E 42 lbs. dia

marked T31 S N 9 W S 30 13 J

T31.9  
424100

63152

Estacion

47.32 d

R. 9 W

W. 1/2 Sec. 10, T. 32 N., R. 9 W., Oregon.

A Fir 50 in in diameter S 50° E 20' the dist

Marked T 32 S 18 9 W 53 - B.T.

A Fir 18 in in diameter S 30° W 24' the dist

Marked T 32 S 18 9 W 54 - B.T.

A Fir 15 in in diameter S 45° W 11' the dist

Marked T 31 S 18 9 W 53 - B.T.

Grado Mountainous etc etc.

Densely covered with forest of fine fir  
timber, some scattering pine.

Thick undergrowth. chiefly Hays  
and Rhododendron.

Estentian

N. 32 S

R. 9 W

153

164

Willamette Meridian, Oregon.

East on a true line on back leg of sec 5.  
N. 10 45 W

6.00 A creek 2 1/2 m wide c. S.

25.50 Top of Ridge N. 8. trail to Rogue River c. S.  
Gradual descent.

40.00 A Chinquapin 15 in in diam which I mark 4 S.  
on the E. side of the 4 Lac Cr. from which.  
A 7.50 in in diam bears N 30° E 39 the dist.  
Marked 4 S - B. J.

A Chinquapin 20 in in diam bears S 75° W 28 the dist.  
Marked 4 S - B. J.

8.50 A Sugar pine 7 1/2 in in diam which I mark  
T 31 S N 9 W S 35 on A. C.  
T 32 S - S 2 on S E

S 3 on S W and S 34 on A. C. faces. also  
2 notches on the E. and 4 notches on the W  
angles of same. for the corner to sec  
2. 3. 34 & 35. from which

A fir 90 in in diam bears N 60° E 53 the dist.  
Marked T 31 S N 9 W S 35 - B. J.

A Laurel 6 in in diam bears S 50° E 75 the dist.  
Marked S 30 S N 9 W S 2 - B. J.

T 31 -  
S 23 100

6154

*Patenticus*

N.T. 32 S.

R. 9 W.

Willamette Meridian, Oregon.

A Laurel 5 ins in diam base 8' 5" N 45' the dia

Marker T32 S N 45' 2-13 J.

A Laurel 5 ins in diam base 12' 7" N 13' the dia

Marker T32 S N 45' 34-13 J.

Land rolling 24. rate.

Sandy ground with forest chiefly  
fir - scattering pine Laurel &c.  
Thick undergrowth of vine maple  
Laurel, Hazel and Fir.

June 17<sup>th</sup> 1883.

Extensions of T. 32 S. R. 9 West

155

Williams Fork, Oregon

A true line along  
East end of Sec 2. 2<sup>nd</sup> 1<sup>st</sup>  
V. 19° 45' E

7.00 A Creek 60 ft wide at. Stop ascent.

15.00 Rolling lands sloping N.W.

35.00 Top of ridge c. 175. By a descent.

40.00 A 15 in indian which I mark "42" on  
the side of the "42" cor. from which.

T 31-9  
562100

From which

A 24 in indian bore East 13 to dist.

Marked "42" B.T.

A 30 in indian bore West 11 to dist.

Marked "48" - B.T.

Very steep descent.

57.00 Baker Creek 40 ft wide c. st.

57.50 Steep descent - rocky bluffs, c. 175.

55.00 Top of ridge c. 175. Gradual descent down.

80.00 Set a Laurel post 44 ft long in ground  
9 in in the ground for the corner sec

1.2. 33796. marked -

T 31 S 18° N S 35 m at C

T 32 S. S-1 on the S.C.

82 m S to end S 35 m Th. to point also

C.S. File No. 64/76-2

456

Estimations 17.32 d. R. P. 2k

Winnemucca Mountain, Oregon.

5' Notches on the N and S notch on the E  
Angles of the same: dug pits 18x18x12  
in each seen 3 1/2 feet dia and raised a  
mound of earth 2 feet high 4 1/2 feet base  
around feet.

Land Mountainous & broken  
Soil 3rd & 4th rates.

Timber poor and scattering chiefly  
fir & Spruce, <sup>conifers with</sup> thick undergrowth of  
Sage Balm and Sycamore.

11.  
23.  
31.  
40.  
45.  
53.  
60.  
64.  
80.

Extensions of T. 32 S. R. 9 W.

U.S. Forest Service

The C  
18x18x12  
and a  
base.

East on a true line along edge of sec 1  
79° 19' 43" E

Descent, Center Green timber  
19.50 A Creek 100 k wide E by Step Ascent.

25.00 Along Brow of rocky Canyon.

30.50 A Creek 3 k wide E S.

40.00 Set a Stone 14x12x5 in in the ground

at the 1/4 Sec Cor. from which  
A 18 in in diam bar S 45° E 35 k dist

Marked 1/4 S - B. T.

A 15 in in diam bar S 45° E 19 k dist.

Marked 1/4 S - B. T.

45.00 Step Descent.

53.50 West fork 100 k wide E S. Step Ascent.

60.00 Along S slope of Mountain

64.40 In Corner to Township 31 S R 9 W.

80.00 The Corner to Township 32 S R 9 W.

Land Mountainous & broken

Soil rock, 3<sup>d</sup> rate covered with  
brush & most of timber chiefly Fir and  
Buck undergrowth of Hazel, vine maple

Lawrence fir and Balsam

92

**Office U. S. Surveyor General,**

Portland, Oregon. Nov 8, 1883

The following Field Notes of the Survey of the  
17<sup>th</sup> Standard Parallel South

executed by R. S. Dickerson

under his Contract No. 474, dated May  
10, 1883, having been critically examined, the

necessary corrections and explanations made, the said field notes  
and the survey they describe, are hereby approved.

James C. Tolman  
Surveyor General.

FIELD NOTES

Of the survey of the Section

Lines of Gowen's 32 South

8, 9, & 10 West, Willamette Meridian,

Oregon, as surveyed by Richard S. Peterson

U. S. Deputy Surveyor, under his Contract No. 474

dated Nov 10, 1883

Survey commenced, \_\_\_\_\_ 1883

Survey completed, \_\_\_\_\_ 1883

NAMES AND DUTIES OF ASSISTANTS.

\_\_\_\_\_, Compassman.

J. H. Nash, Chainman.

S. Ireland, Chainman.

\_\_\_\_\_, Chainman.

\_\_\_\_\_, Chainman.

C. C. Falls, Axeman.

\_\_\_\_\_, Axeman.

\_\_\_\_\_, Flagman.

Observations of T. J. S. R. 9 W.

58  
147

Willamette Meridian, Oregon.

From the corner to I... 30 S 10 W  
... on a ...  
... of 5 to 5 1/2 W.  
...  
... 5 miles, 7 1/2 miles  
...  
... 10 S 10 W ...  
...  
...  
... June 15<sup>th</sup> & 16<sup>th</sup>

...  
... 11' 15"

... top of high mountain ...

37.61 ...  
T 31-9  
168100 ...  
... 510° ...  
... 15 T

... 30 ...

17  
148

Extensions of T. 32 S R. 9 W.

Willamette Meridian, Oregon.

Marked 45-55

64.30 1/2 in. x 1/2 in. x 1/2 in. Slip 20 units

97.51 1/2 in. x 1/2 in. x 1/2 in. 10 in. in the ground

T31-9 226100 for the C. P. in 5. 6. 17 20 units  
with 5 units on the ground and 1 unit the W  
edge. 100 units 1 unit

1/2 in. x 1/2 in. x 1/2 in. 10 in. in the ground

Marked 55-65

7-19 in. in 1/2 in. x 1/2 in. x 1/2 in. 10 in. in the ground

Marked 65-75

1/2 in. x 1/2 in. x 1/2 in. 10 in. in the ground

Marked 75-85

1/2 in. x 1/2 in. x 1/2 in. 10 in. in the ground

Marked 85-95

1/2 in. x 1/2 in. x 1/2 in. 10 in. in the ground  
covered with 3 1/4 units  
1/2 in. x 1/2 in. x 1/2 in. and

1/2 in. x 1/2 in. x 1/2 in. 10 in. in the ground  
and 1 unit.

Extensions of T. 32 S. R. 4 N.

60  
149

Willamette Meridian, Oregon.

Cross on a true line on N. of Sec 5.  
D. 17° 45' E

Ascent:

15.00 2 1/2 x 2 1/2 x 1/2 C. 18 1/2 W. Secured,

T31-9  
266100

40.00 Set a Corner Post 3/4 x 1/2 x 3/4 iron square 20  
in in the ground at the upper corner. Marked  
W. on E side and from a link.

A distance in a line from 45 to 50 the distance  
marked 45 - 50.

A distance in a line from 55 to 60 the distance  
marked 55 - 60.

66.00 2 1/2 x 2 1/2 x 1/2 C. 18 1/2 W. Secured.

80.00 Set a corner post 3/4 x 1/2 x 3/4 iron square  
20 in in the ground at the corner to Sec 4, 5  
32 and 33. Marked

S 14 1/2 W S 32 and C.

S 32 S - S 41 W C.

T31-9  
326100

S 41 on S 14 and S 32 on S 10 paces on S 4  
Set a link on C and 2 marks on W edges of  
same and from a link.

A distance in a line from 45 to 50 the distance

marked S 13 1/2 W S 15 - S 15.

67

Patent of T. 32 S. R. 7 W.

150

Willamette Meridian, Oregon.

A 1/2 section in claim bear S 52° 6' 35" W. 1/2  
marked 134 & 135 on S 4, 15 S.

1/2 section in claim bear S 25° 4' 25" W. 1/2  
marked 137 & 138 on S 5 - 15 S.

1/2 section in claim bear S 55° 4' 35" W. 1/2  
marked 139 & 140 on S 2, 15 S.

Good view obtained

from 3<sup>rd</sup> stake covered with

brush & cut a line toward P.M.  
was with a distance of 1/2 mile  
from each side.

June 16<sup>th</sup> 1883.

Extensions of T. 32 S R. 9 W

62  
151

Willamette Meridian, Oregon.

One or a line of a body of Sec 4.

7<sup>th</sup> 19<sup>th</sup> 45<sup>th</sup> E

Amount,

14.00 Exp. Jan C. L. General.

39.00 2 1/2 mile 40 ft wide C. L.

T31-9  
3641.00

40.00 of the line 40 ft in diam which I marked  
44 S on side for the 4000 Co. from which  
An 1/2 mile in diam has 3 1/2 in 3 1/2 ft  
marked 44 S.

An 1/2 mile in diam has 3 1/2 in 4 1/2 ft  
marked 44 S, 13, 1.

Step account

45.00 Capital ..

80.00 4 1/2 in in diam which I marked

T313 18 9 1/2 3 3/4 in C. L.

T32 S. 3 3 in C. L.

34 in 1/2 and 3 3/4 in 1/2 same also 3

inches on the C. and to 1/2 in of diam

T31-9  
4241.00

The C. to Secs 3, 4, 5, 7, 34

from diam which

Exp. in diam has 3 3/2 in 4 1/2 ft

Marked T313 18 9 1/2 3 3/4 13, 1.

63152

Extensions

of T. 32 S. R. 7 W.

Willamette Meridian, Oregon.

A 50 in in diam bears S 30° E 20' the bit

marked S 32 S 24° 33' - B. T.

A 40 in in diam bears S 30° W 24' the bit

marked S 32 S 24° 34' - B. T.

A 40 in in diam bears S 45° W 11' the bit

marked S 45 S 11' 30' - B. T.

Gravel mountains 2<sup>nd</sup> rate

Gravel covered with forest of pine & fir  
timber, some scattering birch.

Thick underneath, mostly hazel  
and a few cedars.

Willamette Meridian, Oregon.

East on a true line on North by of Sec 3.  
7.1 1095 E.

0.00 A creek 2 1/2 miles wide S W.

24.50 Top of Ridge N. S. half to quarter mile S.  
Gradual descent.

40.00 A line in a basin which I mark N. S.  
on the N. side of the 1/4 Sec Cor. from which  
A line in a basin bears S 30° to 32° the dist  
marked N 1/4 S - B. T.

A line in a basin bears S 40° to 42° the dist  
marked N 1/4 S - B. T.

8.00 A line in a basin which I mark  
S 1/4 N 1/4 S 35° N. E.  
S 32 S - S 2 N S E

S 3 on S W and S 14 on N W faces, also  
2 marks on the E. and 4 marks on the N.  
angles of same in the corner to Secs  
2, 3, 34 & 35. From which

A line 20 ins in diam bears S 40° to 53° the dist  
marked S 1/4 N 1/4 S 35 - B. T.

A line 6 ins in diam bears S 30° to 15° the dist  
marked S 1/4 N 1/4 S 2 - B. T.

T31-9  
523100

6154

Examinations

of T. 32 S.

R. 7 W.

Willamette Meridian, Oregon.

A Survey 5 in in diam bears S 74 W 43 1/2  
Marked S 32 S 84 W S. 3 - 13 S.

A Survey 5 in in diam bears S 20 W 13 1/2  
Marked S 32 S 84 W S. 34 - 13 S.

Land rolling 2 1/2 miles.

Sandy covered with forest, chiefly  
pine scattering Pine Laurel &c.

Thick underneath of Pine maple  
Laurel, Hazel and Fir.

June 17<sup>th</sup> 1883.

Extentions of T. 32 S. R. 9 West

Willamette Meridian, Oregon.

155

A true line along  
East one half Sec 2. To 1st  
V. 19' 45" E

7.00 A creek 15 ft wide at top ascent.  
13.00 Rolling lands sloping N.W.  
33.00 Top of ridge at S. Base descent.  
40.00 18 in diameter which I marked 44 S  
at side of the 44 Sec corner which  
I marked 44 S

T319  
5621.00

42.24 in diameter base East 13 ft wide at  
marked 44 S. B.S.  
47.20 in diameter base West 14 ft wide at  
marked 44 S. B.S.  
Down to S. descent.

57.00 Below creek 40 ft wide at S.  
57.30 Steep ascent - West by bridge, c 188.  
58.00 Top of ridge at S. gradual descent. See  
80.00 Set a small post upon top 4 in from  
edge in the ground for the corner to sec 3

1.2. 357.55. marked -  
T315 N 7/8 S 35 m at C  
T32 S. S-1 on the S.C.  
S 2 m S. and S 35 m the 4th corner also

456

Excavations of T. 32 S. R. 9 W.  
 Willamette Meridian, Oregon.

5 Notches on the N and S sides on the E  
 angles of the square; dug pits 15 x 18 x 12 in  
 in each sec 3 1/2 feet dia and raised a  
 mound of earth 2 feet high 4 1/2 feet base  
 around post.

Land Mountainous & broken

Soil 3<sup>rd</sup> & 4<sup>th</sup> rate.

Timber poor and scattering chiefly  
 covered with  
 Fir & Spruce, thick underneath, of  
 Laurel Balm and Live oak.

Extensions of T. 32 S. R. 9 W.  
Willamette Meridian, Oregon.

East on abut line along Madras line  
7<sup>th</sup> 1843 'E

Descent to center Green timber  
19.30 At creek 1000 ft wide by State Canal.

23.11 Along Brook creek Canyon.

30.31 At creek 300 ft wide C.S.

40.00 Set a Stone 14 x 12 x 5 - in 10 ins in the ground  
for the Sec Canyon on 1<sup>st</sup> side.

At 15 ins in diam base 8 1/2 to 9<sup>th</sup> the dist  
Marked 2 S. - 15. S.

At 15 ins in diam base 8 1/2 to 11<sup>th</sup> the dist  
Marked 4 S. - 15. S.

43.00 Stop Descent.

53.30 West 2000 ft wide C.S. Stop ascent.

50.00 Along slope of mountain.

54.40 Str Corner to Township 31 S 15 W.

80.00 Str Corner to Township 32 S 15 W.

Land mountainous & broken

Soil dark 3<sup>rd</sup> class covered with  
Dense growth of timber chiefly Fir and  
Buck underneath of Hazel, Vine maple  
Lance, fir and Balsam