

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GENERAL LAND OFFICE

BUREAU OF LAND MANAGEMENT  
FIELD NOTES

OF THE

DEPENDENT RESURVEY OF THE

SOUTH AND EAST BOUNDARIES

AND

SUBDIVISIONAL LINES OF

TOWNSHIP 19 SOUTH, RANGE 7 WEST,

AND THE DEPENDENT RESURVEY OF THE

EAST BOUNDARY OF

TOWNSHIP 19 SOUTH, RANGE 8 WEST

Of the WILLAMETTE Meridian,

In the State of OREGON

EXECUTED BY

NORMAN D. PRICE AND THOMAS A. TILLMAN

Cadastral Engineers

Under special instructions dated June 21, 1945, which provided  
for the surveys included under Group No. 284, bearing the approval of the  
Commissioner of the General Land Office under date of July 2, 1946  
and assignment instructions dated June 9, 1949

Survey commenced June 16, 1949

Survey completed September 23, 1949

FILED

Date: 11-13-97 By: JC

This survey consists of:

Map:

Narrative: CS 64/76-4

Corner Rpt: 6095

DOUGLAS COUNTY  
SURVEYOR

Dependent Resurvey of the S. Bdy., T. 19 S., R. 7 W.

## Chains

T 19 S | R 7 W  
 S 31 | S 32  
 T 20 S R 7 W  
 S 5  
 1949

from which new bearing trees

A fir, 26 ins. diam., bears N.82°45'E., 71 lks. dist., marked  
 T19S R7W S32 BT.

A fir, 20 ins. diam., bears N.13½°W., 91 lks. dist., marked  
 T19S R7W S31 BT.

Deposit the sandstone at the base of the iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, maple, chinquapin, hemlock, cedar, alder, and madrona.

Undergrowth, vine maple, hazel, arrowwood, slickleaf, manzanita,  
 salal, huckleberry, poison oak, and bracken.

N. 89° 19' W., along the S. bdy. of sec. 31.

Ascend 311 ft. over NE. slope, changing to steep E. slope, through  
 heavy timber and dense undergrowth.

5.35 A spur, slopes N.15°E.; desc. 211 ft. over NW. slope.

8.90 The closing corner of secs. 5 and 6, T. 20 S., R. 7 W., bears North,  
 17 lks. dist., monumented with a sandstone, 12 x 10 x 6 ins. above  
 ground, firmly set, marked with a cross on top, C C on N. face, and  
 with 1 groove on W. face; and with an iron rod, 3/4 in. diam.,  
 welded to a 1½ in. angle iron, 24 ins. above ground, firmly set,

from which original bearing trees:

A fir snag, 50 ins. diam., bears N.28°E., 98 lks. dist., plainly  
 blazed and healed. (Record bearing N.30°E.)

A splintered fir stump, 48 ins. diam., bears S.78°E., 21 lks.  
 dist., with partial scribe marks visible on fallen trunk.  
 (Record distance 27 lks.)

and trees marked by the county surveyor

A fir, 7 ins. diam., bears S.83½°E., 13 lks. dist., marked  
 GS T20S R7W S5 CC BT.

A fir, 7 ins. diam., bears S.37½°W., 18 lks. dist., marked.  
 GS T20S R7W S6 CC BT.

11.15 The head of a ravine, course N.40°W.; asc. 6 ft. over NE. slope.

11.90 A small spur, slopes NW.; desc. 67 ft. over NW. slope.

13.90 A ravine, course NE.; asc. 421 ft. over SE. slope, changing to steep  
 E. slope.

22.25 A spur, slopes NE.; asc. 70 ft. along broken N. slope, changing to  
 NE. slope.

25.55 A ridge, bears N.10°W. and S.10°E.; desc. 160 ft. over W. slope.

32.90 A branch, 2 lks. wide, course S.20°W.; asc. 80 ft. over SE. slope.

38.19 The ¼ sec. cor. of sec. 31, determined at the record bearing from  
 the original SE. bearing tree and at the record bearing and distance  
 from the original NW. bearing trees as follows:

Dependent Resurvey of the S. Bdy., T. 19 S.; R. 7 W.

Chains

A fir, 24 ins. diam., bears S.28°E., 18 lks. dist., plainly blazed and healed. (Record distance 28 lks.)

A fir, 50 ins. diam., bears N.30°W., 14 lks. dist., plainly blazed and healed.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

¼ S 31

1949

from which a new bearing tree

A fir, 32 ins. diam., bears N.29½°E., 53 lks. dist., marked ¼ S31 BT.

S. 89° 06' W., beginning new measurement.

Asc. 70 ft. over SE. slope.

2.70 A spur, slopes S.; desc. 50 ft. over broken SW. slope.

11.10 A branch, 2 lks. wide, course S.10°E.; asc. 110 ft. over SE. slope.

15.11 Intersect the E. bdy. of sec. 36, T. 19 S., R. 8 W.

Point for the closing cor. of Tps. 19 and 20 S., R. 7 W.

Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, with brass cap marked

T 19 S	T 19 S
R 7 W	R 7 W
S 36	¾ 31
	S 6
R 8 W	T 20 S

1949

from which

A fir, 60 ins. diam., bears N.11½°E., 35 lks. dist., plainly blazed and healed, an original bearing tree.

A hemlock, 20 ins. diam., bears S.31°E., 62 lks. dist., marked T20S R7W S6 CC BT.

From point of intersection the ¼ sec. cor. of sec. 36 only, on the E. bdy. of T. 19 S., R. 8 W., bears N. 0° 17' E., 4.77 chs. dist., hereinafter described.

From point of intersection the original closing corner of Tps. 19 and 20 S., R. 7 W., bears S. 89° 06' W., 17 lks. dist., determined at the record bearing and distance from the original NE. and SE. bearing trees which are as follows:

A fir, 60 ins. diam., bears N.37°E., 40 lks. dist., plainly blazed and healed.

A cherry, 10 ins. diam., dead and down, bears S.35°E., 29 lks. dist., with old blaze decayed.

Land, mountainous and rolling.

Soil, rocky clay and sandy clay loam.

Timber, fir, hemlock, maple, cedar, alder, yew, chinquapin, cherry, and madrona.

Undergrowth, vine maple, hazel, arrowwood, salal, red huckleberry, manzanita, and bracken.

Dependent Resurvey of the Subdivisional Lines, T. 19 S., R. 7 W.

Chains

West, bet. secs. 30 and 31.

Ascend 94 ft. over NE. slope, changing to N. slope, through heavy timber and dense undergrowth.

3.50 The head of a ravine, course N.70°E.; asc. 70 ft. over E. slope.

5.05 A ridge, bears N. and S.; desc. 164 ft. over W. slope.

8.95 The head of a ravine, course N.30°W.; asc. 60 ft. along N. slope, changing to NE. slope.

13.65 A spur, slopes N.50°W.; desc. 324 ft. over W. slope.

21.70 Clay Creek, 4 lks. wide, course N.; asc. 244 ft. over steep E. slope.

26.35 A spur, slopes N.20°E.; asc. 81 ft. over NE. slope.

30.95 Top of ascent on N. slope; desc. 33 ft. over NW. slope.

35.55 A ravine, course N.30°E.; asc. 267 ft. over E. slope.

40.10 Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate distance; there is no remaining evidence of the original corner:

Set an iron post, 3-ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

1 S 30  
2 S 31  
1949

from which

A fir, 12 ins. diam., bears N.52°W., 28 lks. dist., marked 1/4 S30 BT.

A fir, 12 ins. diam., bears S.79°W., 18 lks. dist., marked 1/4 S31 BT.

Ascend 51 ft. over E. slope.

41.45 A ridge, the divide bet. Clay Creek and Haskins Creek, and a blazed trail, bear N.15°E. and S.15°W.; desc. 198 ft. over NW. slope, changing to N. slope.

50.30 A spur, slopes NW.; desc. 107 ft. over SW. slope.

52.33 Intersect E. bdy. of sec. 25, T. 19 S., R. 8 W.

Point for closing cor. of secs. 30 and 31, at intersection of plainly marked original blazed lines, duly identified; the original corner monument has been destroyed by fire.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T 19 S | T 19 S  
R 8 W | S 30 CC  
S 25 | S 31  
1949

from which

A fir, 10 ins. diam., bears N.21 1/2°E., 48 lks. dist., marked T19S R7W S30 CC BT.

A fir, 12 ins. diam., bears S.26°45'E., 37 lks. dist., marked T19S R7W S31 CC BT.

700236

Dependent Resurvey of the Subdivisional Lines, T. 19 S., R. 7 W.

## Chains

From the point of intersection the  $\frac{1}{4}$  sec. cor. of sec. 25 only, bears N.  $0^{\circ} 29' E.$ , 4.97 chs. dist.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, hemlock, maple, cedar, alder, chinquapin, madrona, and dogwood.

Undergrowth, vine maple, hazel, arrowwood, salal, manzanita, and bracken.

To complete the survey of sec. 31, I proceed to the cor. of secs. 25 and 36, on the E. bdy. of T. 19 S., R. 8 W., and run

S.  $0^{\circ} 04' W.$ , along the E. bdy. of sec. 36.

4.83 Point for the  $\frac{1}{4}$  sec. cor. of sec. 31 only, at midpoint on the W. bdy. of sec. 31.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

700176

$\frac{1}{4}$  S. 31

1949

from which .

A fir, 10 ins. diam., bears N.  $54^{\circ} E.$ , 30 lks. dist., marked  $\frac{1}{4}$  S31 BT.

A fir, 10 ins. diam., bears S.  $12\frac{1}{2}^{\circ} E.$ , 33 lks. dist., marked  $\frac{1}{4}$  S31 BT.

From the cor. of secs. 29, 30, 31, and 32.

North, bet. secs. 29 and 30.

Descend 128 ft. over NE. slope, changing to N. slope.

2.65 A ravine, course N.  $70^{\circ} E.$ ; asc. 13 ft. over SE. slope.

3.50 Top of ascent on E. slope; desc. 111 ft. over NE. slope.

9.05 Dry bed of an intermittent stream, 5 lks. wide, course N.  $5^{\circ} W.$ ; a blazed trail, bears N.  $5^{\circ} W.$  and S.  $25^{\circ} E.$ ; asc. 11 ft. along broken W. slope.

14.00 Top of ascent on W. slope; desc. 76 ft. along broken W. slope near stream.

25.20 Same branch, 5 lks. wide, course N.  $5^{\circ} W.$  from S.  $10^{\circ} W.$ ; asc. 37 ft. over broken W. slope.

32.40 Top of ascent on W. slope; desc. 105 ft. over NW. slope.

37.15 Clay Creek, 6 lks. wide, course E.; asc. 3 ft. over S. slope.

37.45 A blazed trail, bears N.  $5^{\circ} E.$  and S.  $5^{\circ} W.$  Thence across bottom land.

38.50 Edge of bottom, bears NE. and SW.; asc. 57 ft. over SE. slope.

40.81 Point for the  $\frac{1}{4}$  sec. cor. of secs. 29 and 30, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

Dependent Resurvey of the Subdivisional Lines, T. 19 S., R. 7 W.

Chains

- 8.05 The head of a ravine, course NW.; asc. 7 ft. over NW. slope.
- 9.85 A spur, slopes NW.; desc. 82 ft. over W. slope.
- 11.73 The original position of the closing cor. of secs. 19 and 30, determined at the record bearing from the original NE. and SE. bearing trees and the record bearing and distance from the original NW. bearing tree as follows:
  - A dead fir, 60 ins. diam., bears N.39°E., 52 lks. dist.; I open and uncover old burned blaze, but scribe marks were evidently burned before blaze healed. (Record distance 60 lks.)
  - A fir, 40 ins. diam., bears S.38½°E., 37 lks. dist., plainly blazed and healed. (Record distance 40 lks.)
  - An uprooted fir, 66 ins. diam., bears N.52°45'W., 16 lks. dist.; I open and uncover the scribe marks T19S R7W S30 & 19 CC.BT.

- 11.88 Intersect the E. bdy. of sec. 24, T.19 S., R. 8 W.  
Point for the closing cor. of secs. 19 and 30.  
Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked.

T 19 S		T 19 S	
		S 19	
R 8 W		S 30	CC
		S 24	R 7 W
			1949

from which

- A fir, 40 ins. diam., bears S.52°E., 48 lks. dist., an original bearing tree with blaze healed.
- A chinquapin, 8 ins. diam., bears N.17½°E., 44 lks. dist., marked T19S R7W S19 CC.BT.

From point of intersection the ¼ sec. cor. of sec. 24 only, bears N. 0° 23' E., 5.59 chs. dist.

Land, mountainous.

Soil, sandy clay loam.

Timber, fir, maple, hemlock, cedar, chinquapin, alder, madrona, and dogwood.

Undergrowth, vine maple, hazel, arrowwood, salal, manzanita, salmon-berry, and bracken.

To complete the survey of sec. 30, I proceed to the cor. of secs. 24 and 25, on the E. bdy. of T.19 S., R. 8 W., and run

S. 0° 23' W., along the E. bdy. of sec. 25.

- 5.28 Point for the ¼ sec. cor. of sec. 30 only, at midpoint on the W. bdy. of sec. 30.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

¼ S 30
1949

from which

A fir, 6 ins. diam., bears N.53°E., 38 lks. dist., marked ¼ S30 BT.

A maple, 8 ins. diam., bears S.46°E., 110 lks. dist., marked ¼ S30 BT.

700274