

ORIGINAL

01

R-649

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES
OF THE
DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
A PORTION OF THE SUBDIVISION OF SECTION 11
AND CERTAIN CLAIM LINES,
AND
THE SUBDIVISION OF SECTION 11,
TOWNSHIP 33 SOUTH, RANGE 5 WEST,
OF THE
WILLAMETTE MERIDIAN,
IN THE STATE OF GREGON

FILED

Date: 10-3-2000 By: JC

This survey consists of:

Map: _____

Narrative: _____

Corner Rpt: 28 pgs

DOUGLAS COUNTY
SURVEYOR

EXECUTED BY

Terrence O. Nickerson, Cadastral Surveyor

Under Special Instructions dated September 16, 1986, approved
September 17, 1986, and Supplemental Special Instructions dated April 21, 1987,
approved April 22, 1987, and Amendment to Special and
Supplemental Special Instructions dated May 9, 1989, approved May 12, 1989,
which provided for the surveys included under Group No. 1355,
and Assignment Instructions dated December 2, 1986,
May 6, 1987, and June 5, 1989.

Survey commenced December 4, 1986

Survey completed June 6, 1989

C.S. File No. 64/76-5

T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, a portion of the subdivision of section 11 and certain claim lines, and the subdivision of section 11, township 33 south, range 5 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

The subdivisional lines were surveyed in 1894 by Edward F. Sharp, U.S. Deputy Surveyor.

A mineral segregation survey in section 11 was executed in 1897 by A. C. McDonald, U.S. Surveyor.

The line between sections 3 and 10 was dependently resurveyed in 1957 by Hans W. Thielsen, Cadastral Surveyor.

Certain original corners were remonumented without survey in 1965-67 by Joseph S. Gawron, John M. Jelley, and Rollin D. Aanrud, Cadastral Surveyors.

A portion of the subdivisional lines were dependently resurveyed in 1970 by Lynn M. Roseberry, Cadastral Surveyor.

Certain original corners were remonumented without survey in 1973-74 by Lynn M. Roseberry and Larry D. Evans, Cadastral Surveyors.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated September 16, 1986, the Supplemental Special Instructions dated April 21, 1987, and the Amendment to Special and Supplemental Special Instructions dated May 9, 1989, for Group Number 1355, Oregon.

The direction of the lines refer to the true meridian as determined by deflections from azimuths obtained by direct solar observations.

Preliminary to the resurvey, the lines of the original surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Only those lines bounding or crossing public lands were blazed. All lines not forming a closure were measured twice.

04

T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

Detectable Electronically Energized Particles (DEEP-1 TM) were buried as memorials at certain corner monuments. The "DEEP-1" is composed of strontium encased in a color coded plastic container. The wits are 1 inch in diameter, 2½ inches long, weigh 2½ ounces, and are magnetically detectable to an average depth of 8 feet.

The geographic position (NAD 1927) of the center ¼ section corner of section 11, as determined from a tie to an electronic control station established for this survey, is as follows:

Latitude 42° 43' 02.50" N. Longitude 123° 15' 29.35" W.

The mean magnetic declination is 20° E.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

(Restoring the 1894 survey by Edward F. Sharp, the 1957 dependent resurvey by Hans W. Thielsen, the 1965-67 remonumentation by Joseph S. Gawron, John M. Jelley and Rollin D. Aanrud, the 1970 dependent resurvey by Lynn M. Roseberry, and the 1973-74 remonumentation by Lynn M. Roseberry and Larry D. Evans)

Beginning at the cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.

T 33 S R 5 W
S 11 | S 12
S 14 | S 13
1967

from which the remains of the original bearing trees

A cedar snag, 24 ins. diam., bears N. 51° E., 56 lks. dist., with scribe marks 3S 5W 12 visible on partially healed blaze. (Record, N. 48½° E.)

A fir, 38 ins. diam., bears S. 21½° E., 78 lks. dist., with healed blaze. (Record, S. 25° E.)

A cedar, 32 ins. diam., bears S. 16½° W., 72 lks. dist., with healed blaze. (Record, S. 14½° W.)

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir snag, 32 ins. diam., bears N. 14½° W., 119 lks. dist., with scribe marks 33S R5W visible on partially healed blaze. (Record, N. 17° W.)</p> <p>and bearing trees mkd. by Gawron, Jelley and Aanrud</p> <p>A fir, 15 ins. diam., bears N. 57½° E., 56 lks. dist., with healed blaze. (Record, N. 54° E.)</p> <p>A fir, 15 ins. diam., bears N. 60° W., 19½ lks. dist., with healed blaze.</p> <p>The original corner stone is set alongside the iron post.</p> <p>The corner falls at base of rock bluff.</p> <p>N. 0° 12' 00" W., bet. secs. 11 and 12.</p> <p>Descend over rock bluffs, slopes N., through scattered timber and dense undergrowth.</p>
4.00	Foot of rock bluffs, edge bears generally E. and W.; continue descending along NW. slope.
17.70	Spur, slopes N. 20° W.; desc. over NE. slope, changing to E. slope.
40.015	The ¼ sec. cor. of secs. 11 and 12, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.
	<p>T 33 S R 5 W</p> <p>¼</p> <p>S 11 S 12</p> <p>1974</p>
	<p>from which the remains of the original bearing trees</p> <p>A fir snag, 26 ins. diam., bears S. 54° E., 27 lks. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>A cedar snag, 18 ins. diam., bears N. 22° W., 33 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Roseberry and Evans</p> <p>A cedar, 25 ins. diam., bears S. 77° E., 28½ lks. dist., with illegible scribe marks visible on partially healed blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

A cedar, 18 ins. diam., bears N. $57\frac{1}{2}^{\circ}$ W., 143 $\frac{1}{2}$ lks. dist., with illegible scribe marks visible on partially healed blaze.

N. $0^{\circ} 12' 00''$ W., beginning new measurement.

Descend along broken E. slope, through medium timber and dense undergrowth.

21.80 Bottom of descent, slopes E.; asc. along broken E. slope.

38.00 Top of ascent, slopes E.; desc. along E. slope.

40.800 The cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.

T 33 S R 5 W
S 2 | S 1
S 11 | S 12
1966

from which the remains of the original bearing trees

A fir, 35 ins. diam., bears N. 59° E., 7 lks. dist., with healed blaze.

A madrone root crown, bears S. 61° E., 29 lks. dist., no marks visible.

A root hole, bears S. 29° W., 145 lks. dist., alongside of which is lying a pine, 36 ins. diam., no marks visible.

A madrone root crown, bears N. 27° W., 33 lks. dist., no marks visible.

and bearing trees mkd. by Gawron, Jelley and Aanrud

A cedar, 11 ins. diam., bears N. 64° E., 38 lks. dist., with illegible scribe marks visible on partially healed blaze.

A fir, 15 ins. diam., bears S. 35° E., 59 lks. dist., with healed blaze. (Record, 56 lks.)

A fir, 12 ins. diam., bears S. 26° W., 33 lks. dist., with healed blaze.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

A fir, 10 ins. diam., bears N. 64° W., 19 lks.
dist., with healed blaze. (Record, 21 lks.)

Land, mountainous.

Soil, rocky clay.

Timber, fir, pine, cedar, oak and madrone; undergrowth,
ceanothus, manzanita, willow, poison oak, native grasses and
young timber.

From the $\frac{1}{4}$ sec. cor. of secs. 11 and 14, monumented with an iron
post, 2 $\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above the
ground, with brass cap mkd.

T 33 S R 5 W
 $\frac{1}{4}$ $\frac{S 11}{S 14}$
1967

from which the remains of the original bearing trees

A fir, 18 ins. diam., bears S. 55° E., 7 lks.
dist., with healed blaze.

A fir snag, 23 ins. diam., bears N. 55° W., 10 lks.
dist., with scribe marks $\frac{1}{4}$ S visible on partially
healed blaze.

and bearing trees mkd. by Gawron, Jelley and Aanrud

A fir, 26 ins. diam., bears N. 72° E., 30 lks.
dist., with healed blaze.

A fir, 23 ins. diam., bears S. 23° W., 24 $\frac{1}{2}$ lks.
dist., with healed blaze.

N. 88° 51' 30" W., bet. secs. 11 and 14.

Descend over NW. slope, through medium timber and dense
undergrowth.

20.365 Point for the W 1/16 sec. cor. of secs. 11 and 14.

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

W 1/16 $\frac{S 11}{S 14}$
1987

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS					
	<p>from which</p> <p>A fir, 8 ins. diam., bears S. $17\frac{1}{2}^{\circ}$ E., 166$\frac{1}{2}$ lks. dist., mkd. W 1/16 S14 BT.</p> <p>A madrone, 13 ins. diam., bears N. $34\frac{1}{2}^{\circ}$ W., 34 lks. dist., mkd. W 1/16 S11 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of stainless steel post.</p> <p>Descend over NW. slope, changing to W. slope.</p>				
22.70	End of gravel road, 25 lks. wide, bears S.				
40.730	The cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2 $\frac{1}{2}$ ins. diam., firmly set, projecting 12 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.				
	<p>T 33 S R 5 W</p> <table style="margin: auto;"> <tr> <td>S 10</td> <td>S 11</td> </tr> <tr> <td>S 15</td> <td>S 14</td> </tr> </table> <p>1967</p>	S 10	S 11	S 15	S 14
S 10	S 11				
S 15	S 14				
	<p>from which the remaining original bearing trees</p> <p>A fir, 26 ins. diam., bears N. 29° E., 14 lks. dist., with healed blaze.</p> <p>A live oak, 12 ins. diam., bears S. $46\frac{1}{2}^{\circ}$ E., 21 lks. dist., with healed blaze. (Record, S. 50° E.)</p> <p>A cedar, 42 ins. diam., bears S. 64° W., 16 lks. dist., with healed blaze. (Record, S. 68° W.)</p> <p>and a bearing tree mkd. by Gawron, Jelley and Aanrud</p> <p>A fir, 13 ins. diam., bears N. 76° W., 27 lks. dist., with healed blaze.</p>				
	<p>N. $0^{\circ} 09' 00''$ W., bet. secs. 10 and 11.</p> <p>Descend along W. slope, through heavy timber and dense undergrowth.</p>				
5.20	Creek, 5 lks. wide, course W.; asc. over steep S. slope.				

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
10.20	Spur, slopes S. 30° W.; continue ascending along steep W. slope.
20.00	Spur, slopes N. 10° W.; desc. over NE. slope.
33.00	Wolf Creek, 5 lks. wide, course W.; asc. over S. slope.
35.00	Dirt road, 15 lks. wide, bears N. 70° E. and S. 70° W.
40.095	The ½ sec. cor. of secs. 10 and 11, monumented by the original corner tree, a fir, 14 ins. diam., with healed blaze on west side, from which the original bearing trees: <p data-bbox="513 680 1221 743">A fir, 32 ins. diam., bears N. 53° E., 19 lks. dist., with healed blaze.</p> <p data-bbox="513 772 1279 835">A fir, 25 ins. diam., bears S. 44° W., 20 lks. dist., with scribe mark 4 visible on open blaze.</p> <p data-bbox="435 865 1455 928">and a reference monument and bearing tree established and recorded by the Josephine County Surveyor's Office, in 1971</p> <p data-bbox="513 957 1406 1083">An iron post, 1½ ins. diam., firmly set, projecting 4 ins. above the ground as a reference monument, bears North, .045 chs. dist., with brass cap mkd. COUNTY SURVEYOR RM 1971 and an arrow pointing to the corner.</p> <p data-bbox="513 1113 1237 1176">A fir, 28 ins. diam., bears N. 21° W., 24½ lks. dist., with healed double blaze.</p> <hr data-bbox="708 1205 1172 1209"/> <p data-bbox="435 1239 1117 1268">N. 0° 16' 30" W., beginning new measurement.</p> <p data-bbox="435 1302 1442 1331">Ascend over S. slope, through heavy timber and dense undergrowth.</p>
16.10	Ridge, bears N. 65° W. and S. 65° E.; desc. over NE. slope.
17.90	Gravel road, 25 lks. wide, bears N. 70° W. and S. 70° E.; enter scattered timber and dense undergrowth, edge bears same.
20.090	Point for the N 1/16 sec. cor. of secs. 10 and 11. <p data-bbox="435 1591 1455 1654">Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p data-bbox="873 1684 1013 1768" style="text-align: center;">N 1/16 S 10 S 11 1987</p> <p data-bbox="435 1810 597 1831">from which</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

A fir, 11 ins. diam., bears N. $83\frac{1}{2}^{\circ}$ E.,
37 $\frac{1}{2}$ lks. dist., mkd. N 1/16 S11 BT.

A fir, 7 ins. diam., bears S. $22\frac{1}{2}^{\circ}$ W., 11 lks.
dist., mkd. N 1/16 S10 BT.

Deposit a white "DEEP-1" magnetic marker at base of iron post.

Descend over NE. slope.

40.180 The cor. of secs. 2, 3, 10 and 11, monumented with an iron post,
2 $\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above the ground,
with brass cap mkd.

T 33 S R 5 W
S 3 | S 2
S 10 | S 11
1957

from which the remains of the original bearing trees

A fir snag, 20 ins. diam., bears N. $37\frac{1}{2}^{\circ}$ E.,
108 lks. dist., with healed blaze.

A fir stump, 45 ins. diam., bears N. 82° E.,
61 lks. dist., with healed blaze.

A fir stump, 19 ins. diam., bears S. 20° W.,
29 lks. dist., with healed blaze.

A madrone, 27 ins. diam., bears N. 53° W., 43 lks.
dist., with healed blaze.

and the remains of bearing trees mkd. by Thielsen

A root hole, bears S. 57° E., 45 lks. dist., alongside
of which is lying the decayed remains of a fir, 9 ins.
diam., with healed blaze.

A root hole, bears N. 72° W., 42 lks. dist., alongside
of which is lying a cedar, 10 ins. diam., with scribe
marks T33S R5W S3 BT visible on open blaze.

and the remains of bearing trees mkd. by the Douglas County
Surveyor's Office, in 1967

A fir, 13 ins. diam., bears N. $7\frac{1}{2}^{\circ}$ E., 59 lks.
dist., with healed double blaze.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	<p>A sawed cedar stump, 14 ins. diam., bears S. 22½° E., 57 lks. dist., alongside of which is lying a cedar, 14 ins. diam., with healed blaze.</p> <p>A fir, 13 ins. diam., bears S. 42° W., 50½ lks. dist., with healed blaze.</p> <p>and a new bearing tree</p> <p>A fir, 12 ins. diam., bears S. 59° E., 64 lks. dist., mkd. T33S R5W S11 BT.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, pine, cedar, oak and madrone; undergrowth, ceanothus, manzanita, willow, poison oak, native grasses and young timber.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12. N. 88° 32' 00" W., bet. secs. 2 and 11. Ascend over SE. slope, through heavy timber and dense undergrowth.</p> <p>1.60 Spur ridge, slopes N. 30° E.; desc. over steep NW. slope.</p> <p>35.20 Gravel road, 15 lks. wide, bears N. and S., curving W.</p> <p>39.10 Tennessee Gulch, 5 lks. wide, course N. 10° W.; asc. over steep NE. slope.</p> <p>40.810 The ¼ sec. cor. of secs. 2 and 11, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground (with a 5/8 in. iron rod alongside), with brass cap mkd.</p> <p style="text-align: center;">T 33 S R 5 W S 2 ¼ S 11 1974</p> <p>from which the original bearing trees</p> <p>A fir, 42 ins. diam., bears N. 27½° E., 53 lks. dist., with scribe marks CS BT visible on bark.</p> <p>A fir, 40 ins. diam., bears S. 41° W., 44 lks. dist., with healed blaze.</p>
--------	---

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	and a bearing tree mkd. by the Douglas County Surveyor's Office, in 1967
	A fir, 10 ins. diam., bears N. 52° E., 30 lks. dist., with healed blaze.
	N. 89° 19' 00" W., beginning new measurement.
	Ascend over steep E. slope.
3.90	Spur, slopes N. 15° E.; continue ascending along broken N. slope.
19.20	Spur, slopes N. 10° E.; desc. over NW. slope.
20.360	Point for the W 1/16 sec. cor. of secs. 2 and 11.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	$W \frac{1}{16} \frac{S \ 2}{S \ 11}$ 1987
	from which
	A fir, 10 ins. diam., bears S. 24¼° W., 111 lks. dist., mkd. W 1/16 S11 BT.
	A fir, 8 ins. diam., bears N. 69¼° W., 41 lks. dist., mkd. W 1/16 S2 BT.
	and a bearing tree of no known record
	A fir, 19 ins. diam., bears N. 76¼° W., 17½ lks. dist., with scribe marks BT visible on partially opened blaze.
	Descend over NW. slope.
28.50	Creek, 2 lks. wide, course N. 20° E.; asc. over broken NE. slope.
40.720	The cor. of secs. 2, 3, 10 and 11.
	Land, mountainous. Soil, rocky clay. Timber, fir, pine, cedar, oak and madrone; undergrowth, ceanothus, manzanita, willow, poison oak, native grasses and young timber.

Dependant Resurvey of a Portion of the Subdivision of
Section 11, T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

(Restoring the 1897 survey by A. C. McDonald)

From the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.

N. $0^{\circ} 21' 30''$ W., on the N. and S. center line of sec. 11.

Descend over NE. slope, through medium timber and dense undergrowth.

2.00 Creek, 4 lks. wide, course N. 60° W.; asc. over S. slope.

7.50 Spur, slopes N. 75° W.; desc. over N. slope.

24.775 Intersect line 3-4 of Hazel Quartz Mineral Claim, point for a crossing closing corner.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

C
HQ
CCC
S/11
C
1987

from which

A fir, 10 ins. diam., bears S. $30\frac{1}{2}^{\circ}$ E.,
35 $\frac{1}{2}$ lks. dist., mkd. CCC S11 BT.

A cedar, 13 ins. diam., bears S. $53\frac{1}{2}^{\circ}$ W.,
105 $\frac{1}{2}$ lks. dist., mkd. CCC S11 BT.

Deposit a white "DEEP-1" magnetic marker at the base of stainless steel post.

Descend over N. slope.

27.10 Wolf Creek, 3 lks. wide, course N. 65° W.; asc. over SW. slope.

Dependent Resurvey of a Portion of the Subdivision of
Section 11, T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS			
29.710	<p>From this point, Cor. No. 3, Banner Placer, bears West, 0.010 chs. dist., hereinafter described.</p> <p>Ascend over SW. slope.</p>		
39.765	<p>The center 1/4 sec. cor. of sec. 11, identical with Cor. No. 2, Banner Placer, monumented with a mound of stone, 3 ft. diam., 1 ft. high, from which the remains of the original bearing trees:</p> <p>A cedar, 26 ins. diam., bears N. 62° E., 63 lks. dist., with healed blaze. (Record, N. 57° E., 45 1/2 lks.)</p> <p>A pine, 26 ins. diam., bears S. 11° W., 63 lks. dist., with healed blaze. (Record, S. 5° W.)</p> <p>A fir snag, 26 ins. diam., bears S. 81 1/2° W., 44 lks. dist., with healed blaze. (Record, S. 74° W., 67 1/2 lks.)</p> <p>A fir stump, 40 ins. diam., bears N. 64 1/2° W., 39 lks. dist., no marks visible. (Record, N. 70 1/2° W., 37 lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 33 S R 5 W</p> <p>C 1/4 S 11</p> <table border="1" style="margin: auto;"> <tr> <td style="padding: 2px;">COR NO 2</td> </tr> <tr> <td style="padding: 2px;">BP</td> </tr> </table> <p>1987</p> </div> <p>Deposit a white "DEEP-1" magnetic marker at the base of stainless steel post.</p> <p>From this point, a point established as the center 1/4 sec. cor. of sec. 11 and recorded by Burton W. Holt, Registered Land Surveyor No. 418, in 1979, bears N. 56° 02' 00" E., 0.130 chs. dist. This point was established using improper control and is not utilized by this survey; monumented with an iron rod, 5/8 in. diam., firmly set, projecting 4 ins. above the ground, from which bearing trees mkd. by Holt:</p> <p>A fir, 14 ins. diam., bears N. 77 1/2° E., 10 lks. dist., with illegible scribe marks visible on partially healed blaze.</p> <p>A cedar, 6 ins. diam., bears S. 49 1/2° W., 16 lks. dist., with scribe marks C 1/4 S 11 BT visible on partially healed blaze.</p>	COR NO 2	BP
COR NO 2			
BP			

Dependent Resurvey of a Portion of the Subdivision of
Section 11, T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	<p>From this same point, a control point at latitude 42° 43' 07.587" N. and longitude 123° 15' 29.382" W., established in conjunction with this survey, bears N. 0° 30' 30" E., 7.880 chs. dist., monumented with an aluminum cap, 2½ ins. diam., firmly set flush with the ground, in concrete, mkd. GP 1355 EC 1 1987.</p>
	<p>N. 0° 20' 00" W., beginning new measurement.</p>
	<p>Ascend over SW. slope.</p>
6.80	<p>Gravel road, 25 lks. wide, bears N. 70° W. and S. 70° E.</p>
7.40	<p>Ridge, bears N. 65° W. and S. 65° E.; desc. over N. slope.</p>
7.570	<p>Corner No. 1, Ramsey Quartz, identical with Cor. No. 1, Hazel Quartz, as determined at record distance from the remains of the original bearing trees:</p> <ul style="list-style-type: none"> A decayed fir stump, size indeterminate, bears N. 7½° E., 65½ lks. dist., no marks visible. (Record, N. 6½° E.) A sawed fir stump, 24 ins. diam., bears S. 5° E., 29 lks. dist., with bottom of healed blaze visible. (Record, S. 11° 10' E.) A sawed fir stump, 24 ins. diam., bears S. 79° W., 83 lks. dist., no marks visible. (Record, S. 75° W.) A root hole, bears N. 23¼° W., 69½ lks. dist. (Record, N. 25¼° W.) <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>RQ COR NO 1 HQ COR NO 1 1987</p> </div> <p>No suitable trees available within limits.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of iron post.</p>

Dependent Resurvey of a Portion of the Subdivision of
Section 11, T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

From this point, Cor. No. 9, Ramsey Quartz, bears S. $64^{\circ} 58' 00''$ E., 4.320 chs. dist., monumented with a mound of stone, 3 ft. base, 6 ins. high, from which the remains of the original bearing trees:

A madrone clump, bears S. $16\frac{1}{2}^{\circ}$ E., 72 lks. dist.

A sawed pine stump, 30 ins. diam., bears N. 19° W.,
74 lks. dist., no marks visible. (Record, N. 23° W.)

No permanent monument set.

From this same point, Cor. No. 2, Hazel Quartz, bears N. $89^{\circ} 20' 00''$ E., 4.512 chs. dist., monumented with a mound of stone, $2\frac{1}{2}$ ft. base, 6 ins. high, from which the remains of the original bearing trees:

A sawed fir stump, 22 ins. diam., bears S. 79° E., $26\frac{1}{2}$ lks. dist., no marks visible on opened bottom of blaze. (Record, S. 84° E.)

A sawed, decayed fir stump, 38 ins. diam., bears S. $10\frac{1}{2}^{\circ}$ E., 53 lks. dist., with scribe marks 2E BT visible on detached blaze. (Record, S. 23° E.)

At the corner point

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, in a collar of stone, 1 ft. base, to top, with brass cap mkd.

S 11
HQ
COR NO 2
1987

Deposit a white "DEEP-1" magnetic marker at the base of stainless steel post.

No suitable trees available.

N. $0^{\circ} 32' 00''$ E., beginning new measurement.

Descend over steep N. slope.

10.758

Corner No. 3, Ramsey Quartz, determined at record bearing and distance from the remains of an original bearing tree:

Dependent Resurvey of a Portion of the Subdivision of
Section 11, T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	<p>A sawed fir stump, 30 ins. diam., bears S. $70\frac{1}{2}^{\circ}$ W., 39$\frac{1}{2}$ lks. dist., no marks visible on bottom of healed blaze.</p> <p>The NW. bearing tree was found uprooted in a landslide and was not tied in.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 11 / COR NO 3 RQ 1989</p> <p>from which</p> <p>A fir, 6 ins. diam., bears S. $35\frac{1}{2}^{\circ}$ E., 22 lks. dist., mkd. COR NO 3 RQ BT.</p> <p>A fir, 6 ins. diam., bears S. 78° W., 11 lks. dist., mkd. S11 BT.</p> <hr/> <p>N. $0^{\circ} 15' 00''$ W., beginning new measurement.</p> <p>Descend along broken NE. slope.</p> <p>2.05 Gravel road, 25 lks. wide, bears N. 30° W. and S. 30° E.</p> <p>2.102 Point for the center N 1/16 sec. cor. of sec. 11.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 30 ins. in the ground, the top 2 ins. below the ground's surface, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S 11 C 1987</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of iron post.</p> <p>The corner is located in N. side of gravel road, 25 lks. wide, bears N. 30° W. and S. 30° E.</p> <p>From this point, a point established as the center N 1/16 sec. cor. of sec. 11, and recorded by Burton W. Holt, Registered Land Surveyor No. 418, in 1975, bears N. $22^{\circ} 11' 30''$ W., 0.045 chs. dist. This point was established using improper control and is</p>

Dependent Resurvey of a Portion of the Subdivision of
Section 11, T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS									
	<p>not utilized in this survey, monumented with an iron rod, 5/8 in. diam., firmly set flush with the ground, from which bearing trees mkd. by Holt:</p> <p>A fir, 17 ins. diam., bears N. 71° W., 116½ lks. dist, with scribe marks CN 1/16 S11 visible on the bark.</p> <p>A fir, 16 ins. diam., bears N. 1° W., 62½ lks. dist, with fragmentary scribe marks visible on partially healed blaze.</p> <p>Descend over broken NE. slope.</p>								
22.532	<p>The ¼ sec. cor. of secs. 2 and 11.</p> <hr/> <p>From the ¼ sec. cor. of secs. 11 and 12.</p> <p>N. 88° 38' 00" W., on the E. and W. center line of sec. 11.</p> <p>Ascend over NE. slope, through medium timber and dense undergrowth.</p>								
12.00	<p>Spur, slopes N. 35° E.; continue ascending along N. slope.</p>								
14.70	<p>Spur, slopes N. 50° W.; desc. over SW. slope.</p>								
36.00	<p>Gravel road, 25 lks. wide, bears N. 10° W. and S. 10° E.</p>								
40.915	<p>The center ¼ sec. cor. of sec. 11.</p> <hr/> <p>N. 88° 20' 00" W., beginning new measurement.</p> <p>Descend over SW. slope.</p>								
19.775	<p>Point for Cor. No. 1, Banner Placer, identical with Cor. No. 2, Lolo Placer, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td colspan="2">S 11</td> </tr> <tr> <td>C COR NO 2</td> <td>COR NO 1 C</td> </tr> <tr> <td>LOLO</td> <td>BP</td> </tr> <tr> <td colspan="2">1989</td> </tr> </table> </div> <p>from which</p>	S 11		C COR NO 2	COR NO 1 C	LOLO	BP	1989	
S 11									
C COR NO 2	COR NO 1 C								
LOLO	BP								
1989									

Dependent Resurvey of a Portion of the Subdivision of
Section 11, T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	<p>A cedar, 6 ins. diam., bears S. 61° E., 28½ lks. dist., mkd. COR NO 1 BP BT.</p> <p>A fir, 11 ins. diam., bears N. 15½° W., 89½ lks. dist., mkd. S11 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p>
20.290	<p>Point for the center W 1/16 sec. cor. of sec. 11.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> $C \frac{W \ 1/16}{S \ 11} C$ 1987 </p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>From this point, a point established and recorded as the center W 1/16 sec. cor. of sec. 11 by Burton W. Holt, Registered Land Surveyor No. 418, in 1979, bears N. 70° 58' 00" E., 0.055 chs. dist. This point was established using improper control and is not utilized in this survey, monumented with an iron rod, 5/8 in. diam., firmly set, projecting 2 ins. above the ground, from which bearing trees mkd. by Holt:</p> <p>A cedar, 10 ins. diam., bears S. 28½° E., 52 lks. dist., with fragmentary scribe marks visible on partially healed blaze.</p> <p>An apple, 16 ins. diam., bears S. 76° W., 30½ lks. dist., with illegible scribe marks visible on bark.</p> <p>Descend over SW. slope.</p>
39.550	<p>Corner No. 1, Lolo Placer, determined at record bearing and distance from the remains of the original bearing trees:</p> <p>A fir, 32 ins. diam., bears N. 21½° E., 15 lks. dist., with healed blaze.</p> <p>A fir, 42 ins. diam., bears S. 85° E., 22 lks. dist., with healed blaze. (Record and to face, 20½ lks.)</p> <p>A fir, 27 ins. diam., bears S. 35° W., 25 lks. dist., with healed blaze. (Record and to face, 24 lks.)</p>

Dependent Resurvey of a Portion of the Subdivision of
Section 11, T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	<p>A root hole, bears N. 47½° W., 24 lks. dist.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table border="1" style="border-collapse: collapse; margin: auto;"> <tr> <td style="padding: 2px 5px;">C</td> <td style="padding: 2px 5px; text-align: center;">S 11</td> <td style="padding: 2px 5px;">C</td> </tr> <tr> <td style="padding: 2px 5px;"></td> <td style="padding: 2px 5px; text-align: center;">LOLO</td> <td style="padding: 2px 5px;"></td> </tr> <tr> <td style="padding: 2px 5px;"></td> <td style="padding: 2px 5px; text-align: center;">COR NO 1</td> <td style="padding: 2px 5px;"></td> </tr> <tr> <td style="padding: 2px 5px;"></td> <td style="padding: 2px 5px; text-align: center;">1987</td> <td style="padding: 2px 5px;"></td> </tr> </table> </div> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 43' 00" W., beginning new measurement.</p> <p>Over nearly level land.</p> <p>1.030 The ¼ sec. cor. of secs. 10 and 11.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of Portions of Certain Mineral Claims, Section 11, T. 33 S., R. 5 W., Willamette Meridian, Oregon</p> <hr/> <p style="text-align: center;">(Restoring the 1897 survey by A. C. McDonald)</p> <hr/> <p>From Cor. No. 1, Banner Placer, identical with Cor. No. 2, Lolo Placer, hereinbefore described.</p> <p>S. 0° 34' 30" W., on line 2-3, Lolo Placer, identical with line 1-4, Banner Placer.</p> <p>Descend over S. slope, through heavy timber and dense undergrowth.</p> <p>2.10 Wolf Creek, 4 lks. wide, course W.; asc. over N. slope.</p> <p>9.878 Corner No. 3, Lolo Placer, identical with Cor. No. 4, Banner Placer, as determined at record distance from the remains of the original bearing trees:</p> <p style="margin-left: 40px;">A sawed fir stump, 46 ins. diam., bears S. 71½° E., 44 lks. dist., with scribe marks BT visible on open blaze. (Record, S. 70° E.)</p> <p style="margin-left: 40px;">A sawed fir stump, 47 ins. diam., bears S. 29½° W., 54½ lks. dist., with healed blaze. (Record, S. 31° W., 60½ lks., and slope distance.)</p>	C	S 11	C		LOLO			COR NO 1			1987	
C	S 11	C											
	LOLO												
	COR NO 1												
	1987												

Dependent Resurvey of Portions of Certain Mineral Claims,
Section 11, T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	<p>A sawed fir stump, 23 ins. diam., bears N. 41° W., 12 lks. dist., with ax marks visible at bottom of healed blaze. (Record, N. 53° 10' E.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">LOLO BANNER COR 3 COR 4 S 11 1987</p> <p>from which</p> <p>A cedar, 10 ins. diam., bears N. 89° E., 48 lks. dist., mkd. COR 4 BP BT.</p> <p>A cedar, 14 ins. diam., bears N. 41½° W., 46½ lks. dist., mkd. COR 3 LOLO BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <hr/> <p>N. 88° 34' 00" W., on line 3-4, Lolo Placer.</p> <p>Ascend along N. slope, through medium timber and dense undergrowth.</p> <p>0.377 Intersect the N. and S. center line of the SW¼ of sec. 11, point for a crossing closing corner, hereinafter described.</p> <p>1.50 Top of ascent, slopes N.; desc. over NW. slope.</p> <p>17.00 Ravine, drains N.; asc. along N. slope.</p> <p>19.930 Point for Cor. No. 4, Lolo Placer, at proportionate position as determined by the Grant Boundary Method; there is no remaining evidence of the original corner.</p> <p>No permanent monument set.</p> <hr/> <p>N. 1° 26' 00" E., on line 4-1, Lolo Placer.</p> <p>Descend over N. slope, through medium timber and dense undergrowth.</p>

Dependent Resurvey of Portions of Certain Mineral Claims,
Section 11, T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS					
2.90	Wolf Creek, 4 lks. wide, course W.; asc. S. slope.				
5.30	Dirt road, 15 lks. wide, bears N. 70° E. and S. 70° W.				
9.965	Corner No. 1, Lolo Placer, hereinbefore described.				
	<p>From Cor. No. 3, Banner Placer, monumented with a mound of stone, 3 ft. base, 1 ft. high, from which the remains of the original bearing trees:</p> <p>A sawed pine stump,, 26 ins. diam., bears N. 51½° E., 21 lks. dist., with scribe marks 3 B BT visible on open blaze. (Record, N. 40° 20' E.)</p> <p>A sawed pine stump, 30 ins. diam., bears S. 87° E., 113½ lks. dist., no marks visible. (Record, N. 34° E., 120½ lks.)</p> <p>A shattered fir stump, 16 ins. diam., bears S. 65¼° E., 132½ lks. dist., alongside of which is lying a fir, 16 ins. diam., with scribe marks BT visible on open blaze. (Record, S. 72° E.)</p> <p>A fir, 19 ins. diam., bears N. 89½° W., 67½ lks. dist., with healed blaze. (Record, S. 84° W., 73½ lks.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, 2½ ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>BP</td> <td>S 11</td> </tr> <tr> <td>COR NO 3</td> <td></td> </tr> </table> <p>1987</p> </div> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <p>N. 87° 49' 30" W., on line 3-4, Banner Placer.</p> <p>Descend over broken SW. slope, through heavy timber and dense undergrowth.</p>	BP	S 11	COR NO 3	
BP	S 11				
COR NO 3					
4.00	Wolf Creek, 4 lks. wide, course N. 60° W.; asc. broken NE. slope.				

Dependent Resurvey of Portions of Certain Mineral Claims,
Section 11, T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS										
4.305	Intersect line 6-7, Hazel Quartz, point for a crossing closing cor., hereinafter described.									
8.30	Top of ascent, slopes N.; desc. along broken N. slope.									
19.930	Corner No. 4, Banner Placer, identical with Cor. No. 3, Lolo Placer, hereinbefore described.									
	From Corner No. 2, Hazel Quartz, hereinbefore described.									
	S. $0^{\circ} 24' 00''$ E., on line 2-3, Hazel Quartz.									
	Descend over S. slope, through medium timber and dense undergrowth.									
7.50	Gravel road, 25 lks. wide, bears N. 10° W. and S. 10° E.									
22.10	Wolf Creek, 2 lks. wide, course N. 70° W.; asc. broken N. slope.									
22.580	Point for Cor. No. 3, Hazel Quartz, at proportionate position as determined by the Grant Boundary Method; there is no remaining evidence of the original corner.									
	Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, to solid rock, in a collar of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd.									
	<table border="0"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">COR 3</td> <td style="padding-left: 5px;"> </td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">HQ</td> <td style="padding-left: 5px;"> </td> <td>S 11</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td style="padding-left: 5px;"> </td> <td>1987</td> </tr> </table>	COR 3			HQ		S 11			1987
COR 3										
HQ		S 11								
		1987								
	from which									
	A fir, 10 ins. diam., bears N. 79° E., $73\frac{1}{2}$ lks. dist., mkd. S11 BT.									
	A fir, 9 ins. diam., bears N. 49° W., $56\frac{1}{2}$ lks. dist., mkd. COR 3 HQ BT.									
	S. $89^{\circ} 36' 00''$ W., on line 3-4, Hazel Quartz.									
	Ascend along broken N. slope, through medium timber and dense undergrowth.									
4.532	Intersect the N. and S. center line of sec. 11, point for a crossing closing corner, hereinbefore described.									

Dependent Resurvey of Portions of Certain Mineral Claims,
Section 11, T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
4.670	<p>Corner No. 4, Hazel Quartz, as determined at record distance from the remains of the original bearing trees:</p> <p>A root hole, bears N. $5\frac{1}{2}^{\circ}$ E., $35\frac{1}{2}$ lks. dist., alongside of which is lying an uprooted cedar, size indeterminate, no marks visible. (Record, N. $3\frac{1}{2}^{\circ}$ E.)</p> <p>A root hole, bears N. $58\frac{1}{2}^{\circ}$ E., 26 lks. dist., alongside of which is lying a fir, 10 ins. diam., with scribe marks $\frac{1}{4}$E BT visible on partially healed blaze. (Record, N. $56\frac{1}{2}^{\circ}$ E.)</p> <p>A root hole, bears S. $40\frac{1}{4}^{\circ}$ E., $26\frac{1}{2}$ lks. dist., alongside of which is lying a decayed fir, 16 ins. diam., with fragmentary scribe marks visible on open blaze. (Record, S. $47\frac{1}{2}^{\circ}$ E.)</p> <p>A sawed fir stump, 40 ins. diam., bears S. 74° W., 27 lks. dist., to face, no marks visible.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">COR 4 HQ S 11 1987</p> <p>No bearing trees available, the two bearing trees mkd. for the crossing closing corner being the only suitable trees.</p> <p>Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. $89^{\circ} 03' 00''$ W., on line 4-5, Hazel Quartz.</p> <p>Along broken N. slope, through scattered timber and dense undergrowth.</p>
4.195	<p>Corner No. 5, Hazel Quartz, monumented with a mound of stone, 3 ft. base, 1 ft. high.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of Portions of Certain Mineral Claims,
Section 11, T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

S 11 | COR 5
 | HQ
 |
 1987

from which

A fir, 7 ins. diam., bears N. 13° E., $54\frac{1}{2}$ lks.
dist., mkd. COR 5 HQ BT.

A fir, 6 ins. diam., bears S. $52\frac{1}{4}^{\circ}$ W.,
 $20\frac{1}{2}$ lks. dist., mkd. S11 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless
steel post.

N. $0^{\circ} 06' 30''$ W., on line 5-8, Hazel Quartz.

Descend over N. slope, through scattered timber and dense
undergrowth.

5.035 Point for Cor. No. 6, Hazel Quartz, at proportionate distance;
there is no remaining evidence of the original corner. This
point is also a witness corner to a crossing closing corner.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

WC CCC
S 11 | ↑ COR 6
 | HQ
 |
 1987

from which

A fir, 7 ins. diam., bears S. $62\frac{1}{2}^{\circ}$ W., 44 lks.
dist., mkd. S11 BT.

A fir, 12 ins. diam., bears N. $60\frac{1}{2}^{\circ}$ W., $19\frac{1}{2}$ lks. dist.,
mkd. X at breast height and BT at base.

Descend NE. slope, through medium timber and dense undergrowth.

Dependent Resurvey of Portions of Certain Mineral Claims,
Section 11, T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
5.168	<p>Intersect line 3-4 of Banner Placer, and true point for a crossing closing corner; falls on steep cutbank of old mining area where it is impracticable to set a permanent monument.</p> <p>Descend steep NE. slope.</p>
5.40	<p>Wolf Creek, 3 lks. wide, course N. 50° W.; asc. S. slope.</p>
14.985	<p>Point for Cor. No. 7, Hazel Quartz, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>No permanent monument set.</p> <p>Ascend S. slope, through medium timber and dense undergrowth.</p>
22.610	<p>Point for Cor. No. 8, Hazel Quartz, at proportionate position as determined by the Grant Boundary Method; there is no remaining evidence of the original corner.</p> <p>This point falls on steep fill of road, where it is impracticable to set a permanent monument.</p>
	<hr/> <p>N. 89° 53' 30" E., on line 8-1, Hazel Quartz.</p> <p>Ascend along S. slope, through scattered timber and dense undergrowth.</p>
0.60	<p>Gravel road, 25 lks. wide, bears N. 70° W. and S. 70° E.</p>
4.00	<p>Ridge, bears N. 55° W. and S. 65° E.; desc. over nearly level land.</p>
4.240	<p>Corner No. 1, Hazel Quartz, identical with Cor. No. 1, Ramsey Quartz, hereinbefore described.</p>
	<hr/> <p style="text-align: center;">Subdivision of Section 11, T. 33 S., R. 5 W., Willamette Meridian, Oregon</p>
	<hr/> <p>From the W 1/16 sec. cor. of secs. 11 and 14.</p> <p>N. 0° 14' 00" W., on the N. and S. center line of the SW¼ of sec. 11.</p>

Subdivision of Section 11,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	Descend over N. slope, through medium timber and dense undergrowth.
2.30	Begin descending steep N. slope.
5.00	Creek, 5 lks. wide, course W.; asc. over steep S. slope.
12.70	Spur, slopes S. 60° W.; desc. along NW. slope, changing to N. slope.
30.065	Intersect line 3-4, Lolo Flacer, point for a crossing closing corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> LOLO W <hr style="width: 50px; margin: 0 auto;"/> CC C S 11 W 1987 </div>
	from which A fir, 10 ins. diam., bears S. 72½° E., 51½ lks. dist., mkd. CCC S11 BT. A fir, 6 ins. diam., bears S. 35½° W., 26 lks. dist., mkd. CCC S11 BT. Deposit a white "DEEP-1" magnetic marker at base of stainless steel post. Descend over N. slope.
37.90	Wolf Creek, 4 lks. wide, course W.; asc. over S. slope.
39.950	The center W 1/16 sec. cor. of sec. 11.
	N. 0° 10' 30" W., on the N. and S. center line of the NW¼ of sec. 11. Ascend over S. slope, through heavy timber and dense undergrowth.
18.60	Gravel road, 25 lks. wide, bears N. 80° E. and S. 80° W.
19.00	Ridge, bears N. 80° E. and S. 80° W.; desc. over steep N. slope.

Subdivision of Section 11,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
20.10	Gravel road, 20 lks. wide, bears N. 60° E. and S. 60° W.
20.240	Point for the NW 1/16 sec. cor. of sec. 11, at intersection with the E. and W. center line of the NW¼.
	Set an iron post, 28 ins. long, 2½ ins. diam., flush with surface of the road, with brass cap mkd.
	NW 1/16 S 11 1987
	from which
	A fir, 29 ins. diam., bears S. 82° W., 308½ lks. dist., mkd. NW 1/16 S11 BT.
	Deposit a white "DEEP-1" magnetic marker at base of iron post.
	From this point, a point established and recorded as the NW 1/16 sec. cor. of sec. 11 by Burton W. Holt, Registered Land Surveyor No. 413, in 1979, bears N. 48° 58' 00" E., 0.032 chs. dist., this point was established using improper control and is not utilized in this survey, monumented with an iron rod, 5/8 in. diam., firmly set 3 ins. below the surface of the road, from which bearing trees mkd. by Holt:
	A fir, 12 ins. diam., bears S. 8½° E., 51 lks. dist., with healed blaze.
	A madrone snag, 10 ins. diam., bears S. 14° W., 86 lks. dist., with scribe marks NW 1/16 S11 BT visible on partially healed blaze.
	The corner falls on N. edge of gravel road, 20 lks. wide, bears N. 60° E. and S. 60° W.
	Descend over N. slope, changing to W. slope.
40.500	The W 1/16 sec. cor. of secs. 2 and 11.
	From the center N 1/16 sec. cor. of sec. 11.
	N. 88° 51' 00" W., on the E. and W. center line of the NW¼ of sec. 11.
	Ascend along W. slope, through medium timber and dense undergrowth.

Subdivision of Section 11,
T. 33 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
0.20	Gravel road, 20 lks. wide, bears N. 30° W. and S. 30° E.
1.60	Spur, slopes N.; desc. over NW. slope.
3.70	Ravine, drains N.; asc. over E. slope.
13.80	Ridge, bears N. 20° W. and S. 20° E.; continue ascending along broken S. slope.
15.60	Gravel road, 25 lks. wide, in a curve, bears N. 80° W. and S. 70° E.
17.80	Same gravel road, 25 lks. wide, in a curve, bears E. and S. 60° W.
18.80	Same ridge, bears N. 50° E. and S. 50° W.; desc. over NW. slope.
20.20	Gravel road, 20 lks. wide, bears N. 60° E. and S. 60° W.
20.395	The NW 1/16 sec. cor. of sec. 11.
	Descend along broken N. slope.
40.720	The N 1/16 sec. cor. of secs. 10 and 11.
GENERAL DESCRIPTION	
<p>The lands included in this resurvey are located about 10 miles east of the town of Glendale, Oregon. The elevation ranges from about 2,400 feet above sea level to about 3,600 feet above sea level. Access to the area is gained by way of Speaker Road and numerous Bureau of Land Management timber sale access roads.</p>	
<p>The timber in this area consists of Douglas fir, white fir, ponderosa pine, cedar, oak and madrone. The undergrowth consists of young timber, manzanita, live oak, poison oak, Oregon grape, and willow.</p>	
<p>No new mineral deposits were noted along the lines surveyed; however, former ditches and excavations used for mining were noted, along with recent mining activity situated in the northeast quarter and southwest quarter of section 11.</p>	
<p>The magnetic declination as shown on the "GLENDALE, OREG." quadrangle, 15 minute series, published by the United States Geological Survey in 1954, is 20° East.</p>	