

GOVERNMENT CORNER RESTORATION FORM

Date: 2-3-98 By: SC

This survey consists of:

Township 255 Range 3W Sec. 19 County DOUGLA Map: _____

State OR Date 1-26-98 No. _____

Narrative: _____

Corner Rpt: 64/79-11

Corner Designation

$\frac{1}{4} \frac{S19}{S30}$

DOUGLAS COUNTY
SURVEYOR

Condition Report Only

Not Found

Renewed

Unrecorded

Surveyed In

Referenced Out

MONUMENT DETAIL

Previous Renewals 1940 BLM 1966 + 1982 DCSO

Monument(s) Found: (Condition and Source)

2 1/2" DIA BRASS CAP ON
A 1 1/2" O.D. IRON PIPE
WITH APPROX. 6" OF LOOSE
SOL ON TOP 1966

COUNTY SURVEYORS OFFICE
T 255

$\frac{1}{4} \frac{S19}{S30}$

R 3W

1966

Accessories Found:

- 8" NOW 13" DIA 1/2 FT HIGH D. FIR STUMP WITH A
PREVIOUSLY OPENED BLAZE (ILLEGIBLE SCRIBING VISIBLE)
BEARS S51°W, 11.9 FT (AGREES WITH REC.) 1940
- 1940 NE BT NOW GONE
- 16" NOW 22" DIA 1/2 FT HIGH D. FIR STUMP WITH
A HEALED BLAZE BEARS S12°W, 18.8 FT (REC.
S17°W 19.8 FT) 1966
- 6" NOW 10" DIA 2 FT HIGH MAPLE STUMP WITH
SCRIBING "V4S30CS" VISIBLE ON A OPEN BLAZE
BEARS S37°W, 17.8 FT (AGREES WITH REC.) 1982
- 8" FIR NOW 13" DIA HEALED WITH A FULLY HEALED DOUBLE
BLAZE, BEARS S26°W, 46.6 FT (REC. S26°W, 48.0 FT) 1982
- "X" INTO TOP OF 54" DIA METAL CONDUIT BEARS S33°W, 3.7 FT
(REC. S26°W, 3.7 FT) 1982
- 9" NOW 9" DIA 4 FT HIGH MAPLE STAB, WITH SCRIBING
VISIBLE ON A OPEN BLAZE "V4S30CS BT" BEARS S89°E,
26.3 FT (REC S89°E, 26.8 FT) 1982
- 12" NOW 16" DIA R. CEDAR WITH A FULLY HEALED DOUBLE BLAZE
BEARS N89°E, 24.2 FT (REC, N89°E 25.0 FT) 1982

