

FILED

MAP OF SURVEY

LOCATED in the NE 1/4 of Section 7,
T. 22 S., R. 6 W., W.M. in Douglas
County, Oregon.

May 5, 1997

Date: 5/7/97 By: JP

This survey consists of:

Map: C.S. 65/12-8

Narrative: _____

Corner Rpt: _____

DOUGLAS COUNTY
SURVEYOR

JP

JP

SURVEYED FOR: *DICK HESS*
P.O. BOX 491
YONCALLA, OREGON

SURVEYED BY: *DAVID EDWARDS LAND SURVEYING*
P.O. BOX 41
OAKLAND, OREGON 97462
PHONE: (541) 459-0512

REGISTERED
PROFESSIONAL
LAND SURVEYOR

David A. Edwards

OREGON
JULY 24, 1988
DAVID A. EDWARDS
2339

EXPIRES 12/31/97

NARRATIVE

THE PURPOSE OF THIS SURVEY IS TO MONUMENT THE 1/4 CORNER TO SECTIONS 7 AND 8, CONTROL POINTS AND DATA ESTABLISHED BY THIS OFFICE ON M 122-72 AND M 123-51 WERE USED TO ACHIEVE THIS END. ALSO, THE SOUTH AND EAST LINES OF THE SOUTH 1/2 OF THE NE 1/4 OF SECTION 7 WERE SURVEYED AND MARKED. BEARING TREES TO REFERENCE THE 1/4 CORNER WERE SCRIBED ACCORDING TO THE 1973 B.L.M. MANUAL, ARE MEASURED TO CENTER OF TREE AT ROOT CROWN AND ARE SITUATED AS LISTED BELOW.

FIELD CREW: DAVID EDWARDS AND BRANT MILLER.
EQUIPMENT: NIKON DTM AIOLG TOTAL STATION.
COMPUTATIONS AND DRAFTING: DAVID EDWARDS.

LEGEND

- INDICATES 5/8" x 30" STEEL PIN W/RED PLASTIC CAP MKD. D.A. EDWARDS-LS 2339 SET.
- INDICATES 5/8" DIAM. STEEL PIN W/CAP FOUND PER M 122-72 OR M 123-51.

SCALE: 1" = 600'

BASIS OF
BEARINGS: M 122-72 AS SHOWN.

BEARING TREES FOR 1/4 CORNER:

- A 15" DIAM. FIR BEARS N.34°20'E., 56.54 FEET.
- A 15" DIAM. FIR BEARS S.6°59'E., 75.72 FEET.
- A 12" DIAM. FIR BEARS S.79°16'W., 21.61 FEET.
- AN 11" DIAM. FIR BEARS N.47°56'W., 49.60 FEET.



CENTER 1/4 CORNER
PER M 123-51.

