


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner was originally established by Quimby and Ware in 1980 Under M79-55 as follows: Set 2 1/2" iron pipe with brass cap stamped "T27S R1W 1/4 S2/S1 RLS 1654 1980"

Scribed New BT's
36" W. Fir S78°E, 103.6' "1/4 S1 BT"
20" W. Fir S83°W, 156.5' "1/4 S2 BT"

A witness corner was established 7 chains South of the 1/4 Corner in the original 1902 GLO Survey by Homer D. Angell under Contract No. 746. This witness corner was perpetuated by USBLM Cadastral Surveyors Sams and Harris under a 1971 Dependent Resurvey that was suspended in 1980.



Description of corner evidence found:

A 2 1/2" iron pipe by Quimby and Ware in 1980, firmly set, projecting 3" above the ground with a 2 1/2" brass cap stamped:

T27S R1W
1/4
S2 | S1
RLS 1654 1980

From which bearing trees by Quimby & Ware in 1980:

A 37" W. Fir with a snag top bears S.80°45'E., 104.0 ft with scribe marks "1/4 S1 BT" visible on a open blaze (Rec. S.78°E., 103.6 ft.)

A 28" W. Fir bears S.81°45'W., 156.6 ft. with scribe marks "1/4 S2 BT" Visible on a open blaze (Rec. S.83°W., 156.5 ft.)

Description of monument and accessories I established to perpetuate the original location of this corner:

And a new bearing tree:

A 22" W. Fir bears N.58°15"E., 70.7 ft. scribed "1/4 S1 BT" on a double blaze with a brass washer stamped "PLS 1941" nailed into the lower blaze.

I paint BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all BT's.

Magnetic Declination: 20°E.

Witnesses: Les Fanning, Matt Dixon, Aaron Fanning

BTS Engineering & Surveying Inc.
431 SE Main Street
Roseburg, Oregon 97470
(541)-673-0966
Dec. 1997

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Kristian O. DeGroot

OREGON
JULY 17, 1981
KRISTIAN O. DEGROOT
1941

ELP RES 12/31/99

FILED

Date: 2-10-98 By: JK

This survey consists of:

Map: _____

Narrative: _____

Corner Ept: 65/20-4

DOUGLAS COUNTY
SURVEYOR

C.S. File No. 65/20-4

*-107 cv