

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner was originally established by Quimby and Ware in 1980 Under M79-55 as follows: Set 2 1/2" iron pipe with brass cap stamped "T27S R1W C 1/4 S2 RLS 1654 1980"

Scribed New BT's  
36" Hemlock N.14°W., 69.0' "C 1/4 S2 BT"  
30" Hemlock S.30°E., 33.4' "C 1/4 S2 BT"  
Found 3/4" iron rod S.4°40'W., 20 ft. (unrecorded)

T27S R1W  
C 1/4 S2

Description of corner evidence found:

A 2 1/2" iron pipe by Quimby and Ware in 1980, per M79-55, firmly set, projecting 5" above the ground with a 2 1/2" brass cap stamped:

T27S R1W  
C 1/4 S2  
RLS 1654 1980

From which bearing trees by Quimby & Ware in 1980:

- A 25" White fir bears S.33°E., 23.2 ft. with scribe marks visible on a nearly healed double blaxe (Rec. Hemlock S.30°E., 33.4 ft.)
- A 36" hemlock bears N.13°45'W., 68.8 ft. with scribe marks "C 1/4 S2 BT" visible on a partially healed double blaxe. (Rec. N.14°W., 69.0 ft.)
- A 3/4" iron rod bears S.4°40'W., 20.0 ft.

Description of monument and accessories I established to perpetuate the Original location of this corner:

I paint BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all BT's.

Magnetic Declination: 20°E.

Witnesses: Les Fanning, Matt Dixon, Aaron Fanning

BTS Engineering & Surveying  
\$31 SE Main Street  
Roseburg, Oregon 97470  
(541)-673-0966

Dec. 1997

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Kristian O. DeGroot*

OREGON  
JULY 17, 1981  
KRISTIAN O. DEGROOT  
1941

*EXPIRES 12/31/99*

FILED

Date: 2-10-98 By: JC

This survey consists of:

Map: \_\_\_\_\_

Narrative: \_\_\_\_\_

Corner Rpt: C565/20-5

DOUGLAS COUNTY  
SURVEYOR

#2056 cv

C.S. File No. 65/20-5