

BTS ENGINEERING AND SURVEYING, INC.

Date: 3-17-1998 By: JC
 This survey consists of:
 Map: _____
 Narrative: _____
 Corner Rpt: 65/20-6

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

**DOUGLAS COUNTY
SURVEYOR**

History of original corner establishment: This corner was originally established by Joseph A. Ganong and John G. Collins, U.S. Cadastral Engineers, in 1927 as follows:

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. In the ground, for cor. of Secs. 26, 27, 34 and 35, with brass cap marked:

T25S	R1E
S27	S26
S34	S35

1927

T25S	R1E
S27	S26
S34	S35

from which

A pine, 48 ins. diam., bears N.61°E., 54 lks. dist., marked "T 25 S R 1 E S 26 B T".

A fir, 16 ins. diam., bears S.44°E., 6 lks. dist., marked "T 25 S R 1 E S 35 B T".

A fir, 10 ins. diam., bears S.6°W., 34 lks. dist., marked "T 25 S R 1 E S 34 B T".

A fir, 30 ins. diam., bears N. 73°W., 36 lks. dist. marked "T 25 S R 1 E S 27 B T".

The corner was restored by Richard C. Grant in 1957 per C.S. file No. 42/328 as follows:

Set 3/4" steel rod below surface of road, from which:

Marked 40" fir T25S, R1E, S34 2807 bears S.83°10'W., 200.4 ft.

Marked 8" fir T25S, R1E, S27 bears N.87°30'W., 234.5 ft.


Description of corner evidence found: A 2" (O.D.) iron pipe buried 12" below the rock road surface of USFS Road 4713-500 with a 2 1/2" brass cap stamped:

U.S. GENERAL LAND OFFICE
 T25S R1E
 S27 | S26
 S34 | S35
 1927

No evidence of Grant's 1957 iron rod or bearing trees can be found.

Description of monument and accessories I established to perpetuate the original location: I established a new reference monument, new bearing objects and a new bearing tree as follows:

A 2 1/2" x 30" aluminum monument set 26" in the ground with a 3 1/4" aluminum cap stamped:

US DEPT. OF AGRICULTURE FOREST SERVICE
 T25S R1E
 S27 RM

 1997
 PLS 1941

bears N.29°W., 43.3 ft.

I chiseled "X BO" in 3" tall letters in a vertical rock face that bears S.13°E., 13.35 ft. to the center of the "X".

A 5/8" X 30" iron rod with plastic cap "BTS ENG-SURV" bears S.57°W., 45.7 ft.

A 9" D.fir bears N.57°E., 35.1 ft. scribed "T25S R1E S26 BT" with a brass washer stamped "PLS 1941" nailed in lower blaze.

I paint a 6" red band and BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to bearing trees.

Magnetic declination: 20°E.

Witnesses: Les Fanning, Matt Dixon, Aaron Fanning

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Kristian O. Decroot

OREGON
JULY 17, 1981
KRISTIAN O. DECROOT
1941

Eyes 12/21/99