

FILED

BTS ENGINEERING AND SURVEYING, INC.

Date: 3-17-1998 By: J

This survey consists of: _____

Map: _____

Narrative: _____


Corner Rpt: 65/20-13

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

**DOUGLAS COUNTY
SURVEYOR**

History of original corner establishment: This corner was originally established in 1931 by Otto L. Draper, U.S.G.L.O. Transitman, as follows:
Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, for the 1/4 sec cor., with brass cap mkd.

1/4
S8 | S9
1931



from which

A fir, 40 ins. diam., bears S.21°E., 81 lks. dist., mkd. 1/4 S 9 B T

A fir, 20 ins. diam., bears N.76°W., 49 lks. dist., mkd. 1/4 S 8 B T

Description of corner evidence found: A 1" (O.D.) iron pipe, firmly set, projecting 8' above the ground with a 2 1/2" brass cap stamped:

U.S. GENERAL LAND OFFICE

1/4
S8 | S9
1931

from which bearing trees by Draper in 1931:

A 42" fir bears S.38°E., 53.5 ft. with a healed blaze. (Rec. S.21°E.)

A 30" fir bears N.76°W., 32.3 ft. with a healed blaze.

Description of monument and accessories I established to perpetuate the original location: I build a stone mound, 48" diam. base to top of monument and paint a 6" red band and BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to bearing trees.

Magnetic declination: 20°E.

Witnesses: Les Fanning, Matt Dixon, Aaron Fanning

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Kristian O. De Groot

OREGON
JULY 17, 1981
KRISTIAN O. DE GROOT
1941

Expire 12/31/99

#11 VC