

BTS ENGINEERING AND SURVEYING, INC.

FILED

Date: 3-17-1978 By: JC

This survey consists of: _____

Map: _____

Narrative: _____

Corner Rpt: 65/20-15

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

**DOUGLAS COUNTY
SURVEYOR**

History of original corner establishment: This corner was originally established in 1930 by Otto L. Draper, U.S.G.L.O. Transitman as follows:

Set an iron post, 3 ft. long, 1 in diam., 28 ins. in the ground, for the 1/4 sec. cor., with a brass cap mkt.

1/4
S10 | S11
1930

T26S R3E

1/4
S10 | S11

from which,

A fir, 11 ins. diam., bears S.32°E., 28 lks. dist., mkd. 1/4 S 11 B T

A fir, 9 ins. diam., bears N.57°W., 28 lks. dist., mkd. 1/4 S 10 B T

Description of corner evidence found: A 1" (O.D.) iron pipe, firmly set, projecting 10" above the ground with a 2 1/2" brass cap stamped:

U.S. GENERAL LAND OFFICE

1/4
S10 | S11
1930

from which a bearing tree by Draper in 1930:

A 24" fir bears S.32°E., 18.5 ft. with a healed blaze.

Description of monument and accessories I established to perpetuate the original location: I build a stone mound, 48" diam. base to top of the monument and mark a new bearing tree:

A 20" D.fir bears N.72°W., 23.3 ft. scribed "1/4 S10 BT" with a brass washer stamped "PLS 1941" nailed into the lower blaze.

I paint a 6" red band and BT faces red and corner tree faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all bearing trees.

Magnetic declination: 20°E.

Witnesses: Les Fanning, Matt Dixon, Aaron Fanning

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Kristian O. DeGroot

OREGON
JULY 17, 1981
KRISTIAN O. DEGROOT
1841

Effend 12/31/90

#13 - c

C.S. File No. 65/20-15