


BTS ENGINEERING AND SURVEYING, INC.

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: This corner was established in 1980 by Quimby and Ware under Survey M 79-45 for the U.S. Forest Service (Contract 53-04H1-9-7490N) as follows:

Set 2 1/2" iron pipe with brass cap marked:

T27S R2W
W 1/16
C——C
S34
RLS 1654
1980



from which bears scribed new B.T.'s:

8" Hemlock S.14W., 111.8' "CW 1/16 S34 B.T."

8" Hemlock S.76°W., 93.8' "CW 1/16 S34 B.T."

This corners perpetuated by G.V. Nygren in 1988 who scribed new bearing trees as recorded in CS File No. 63/69-38:

a 12" Hemlock bears S.82 1/4°W., 135.5ft. scribed "CW 1/16 S34 BT".

a 8" Hemlock bears S.4°E., 143.8 ft. scribed "CW 1/16 S34 BT".

a 1/2" brass washer marked "LS 1035" was set in BT faces.

Description of corner evidence found:

A 2 1/2" (O.D.) iron pipe, firmly set, projecting 3" above the ground with a 2 1/2" brass cap stamped:

T27S R2W
W 1/16
C——C
S34
RLS 1654
1980

from which bearing trees by Nygren in 1988:

a 14" Hemlock bears S.81°30'W., 136.7 ft. with scribe marks "CW 1/16 S34 BT" visible. (Rec. S.82°15'W. 135.5 ft.)

a 10" Fir bears S.3°30'E., 145.7 ft. with scribe marks "CW 1/16 S34 BT visible. (Rec. Hemlock S.4°E., 143.8 ft.)

Description of monument and accessories I established to perpetuate the original location:

I paint a 6" red band and BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all bearing trees:

Magnetic declination: 20°E.

Witnesses: Les Fanning, Matt Dixon, Aaron Fanning

FILED

Date: 6/29/1998 By: JC

This survey consists of:

Map: _____

Narrative: _____

Corner Rpt: 65/20-26

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Kristian O. Degroot

OREGON
JULY 17, 1961
KRISTIAN O. DEGROOT
1941

Exp 12/31/99

**DOUGLAS COUNTY
SURVEYOR**