

BTS ENGINEERING AND SURVEYING, INC.

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: This corner was established in 1980 by Quimby and Ware under Survey M 79-49 for the U.S. Forest Service (Contract 53-04H1-9-7490N) as follows:

Set 2 1/2" iron pipe with brass cap marked :
T27S R2W
C
S 1/16 | S32
C
RLS 1654
1980

T27S R2W
C
S 1/16 S32
C

from which bears scribed new B.T.'s:
36" Cedar N.26°W., 53.1' "CS 1/16 S32 BT"
14" Hemlock N.50°E., 63.2' "CS 1/16 S32 BT"

Description of corner evidence found:

A 2 1/2" (O.D.) iron pipe, firmly set, flush with the ground with a 2 1/2" brass cap stamped:

T27S R2W
C
S 1/16 | S32
C
RLS 1654
1980

from which bearing trees by Quimby and Ware in 1980:
a 38" Cedar bears N.26°W., 52.5 ft. with scribed marks "CS 1/16 S32 BT" visible on a double blaze. (Rec. 53.1 ft.)
a 19" Hemlock bears N.50°E., 63.2 ft. with scribed marks "CS 1/16 S32 BT" visible on a double blaze.

Description of monument and accessories I established to perpetuate the original location:

I paint a 6" red band and BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all bearing trees:

Magnetic declination: 20°E.

Witnesses: Les Fanning, Matt Dixon, Aaron Fanning

FILED

Date: 6/29/1998 By: JC

This survey consists of:

Map: _____

Narrative: _____

Corner Rpt: 65/20-27

DOUGLAS COUNTY
SURVEYOR

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Kristian O. DeGroot
OREGON
JULY 17, 1991
KRISTIAN O. DEGROOT
1941

Exp 12/31/99