


BTS ENGINEERING AND SURVEYING, INC.

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: This corner was originally established in 1968 by Thomas E. Shrum under Survey M 37-17. Shrum's Corner was not accepted and the corner was reestablished in 1980 by Quimby and Ware under Survey M 79-37 for the U.S. Forest Service (Contract 53-04H1-9-7490N) as follows:

Set 2 1/2" iron pipe with brass cap marked:
T28S R2W
E 1/16
C——C
S6
RLS 1005
1980



from which bears scribed new B.T.'s:
15" Madrone S.3°E., 15.2' "CE 1/16 S6 BT"
10" D. fir N.44°E., 11.8' "CE 1/16 S6 BT"
7" D. fir S.74°E., 17.3' "CE 1/16 S6 BT"

found aluminum cap on 1" iron pipe N.69°13'36"E., 9.96' from brass cap:
10" fir bears N.8°E., 3.6'
7" fir stump bears S.48°E., 11.4'

Description of corner evidence found:

A 2 1/2" (O.D.) iron pipe, firmly set flush with the top of a 36" diameter mound of stone with a 2 1/2" brass cap stamped:

T28S R2W
E 1/16
C——C
S6
RLS 1005
1980

from which bearing trees by Quimby and Ware in 1980:
a 12" Madrone bears S.3°E., 13.7 ft. scribe marks "CE 1/16 S6 BT" visible.
(Rec. 15.2 ft.)
a 13" D. fir bears N.44°E. 11.8 ft. with a healed double blaze
a 11" D. fir bears S.79°E., 17.3 ft. with a healed double blaze (Rec. S.74°E.)
and a monument by Shrum in 1968:
a 1" (O.D.) iron pipe, firmly set, projecting 16" above the ground with a 2 1/2" aluminum cap stamped "T28S R2W CE 1/16 SEC 6 RE 4287 1968" bears N.71°30'E., 9.96 ft. (Rec. N.69°13'36"E.)
and bearing trees by Shrum in 1968 :
a 14" D. fir bears N.8°E., 3.6 ft. with a healed blaze facing Shrum's monument.
a 7" D. fir stump bears S.45°E., 11.4 ft. with a healed blaze facing Shrum's monument. (Rec. S.48E.)

Description of monument and accessories I established to perpetuate the original location:

I paint a 6" red band and BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all bearing trees:

Magnetic declination: 20°E.

Witnesses: Les Fanning, Matt Dixon, Aaron Fanning

FILED

Date: 6-29-1998 By: DC

This survey consists of:

Map: _____

Narrative: _____

Corner Rpt: 65/20-30

**DOUGLAS COUNTY
SURVEYOR**

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Kristian O. Diergroot

OREGON
JULY 17, 1981
KRISTIAN O. DIERGROOT
1981

Exp 12/31/99