

# BTS ENGINEERING AND SURVEYING, INC.

## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

**History of original corner establishment:** This corner was originally established in 1910 by Wm. N. Gibb, Deputy Surveyor under USGLO Contract No. 783 as follows:

Set granite stone, 12x12x14 ins., 10 ins. in the ground for 1/4 sec. cor., marked 1/4 on N face, from which

A laurel, 18 ins. diam., bears N.40°W., 32 lks. dist., marked 1/4 S 6 B T.

A fir, 10 ins. diam., bears S.60°E., 22 lks. dist., marked 1/4 S 7 B T.

This corner was restored by Thomas E. Shrum in 1962 under Survey M 25-7 from original bearing trees as follows:

Found: Mad. 15" diameter N37 1/2°W, 21.8'

Fir 9" diameter S54°E, 14'

Set: 2 1/2" Aluminum Cap

Cedar 11" diameter N56°E, 33.5'

Fir 15" diameter S51°E, 28.2'

This corner was perpetuated in 1980 by Quimby and Ware who scribed a new bearing tree as follows:

20" Cedar S.6°E 98.0' "1/4 S7 BT"

T28S R2W
1/4 S6
4 S7

**Description of corner evidence found:** A 1" iron pipe (O.D.) firmly set, projecting 10" above the ground with a 2 1/2" aluminum cap stamped:

T28S R2W

1/4 S6

S7

RE 4287

1961

from which a bearing tree by Shrum in 1962:

a 21" Cedar bears N.56°30'E., 33.5 ft. with a healed blaze. (Rec. N56°E)

and a bearing tree by Quimby and Ware in 1980:

a 24" Cedar bears S.6°E., 95.3 ft. with scribe marks "1/4 S7 BT" visible.

(Rec. 98.0 ft.)

**Description of monument and accessories I established to perpetuate the original location:**

I paint a 6" red band and BT faces red and nail USFS "BEARING TREE" and "LAND SURVEY MONUMENT" signs to all bearing trees:

Magnetic declination: 20°E.

Witnesses: Les Fanning, Matt Dixon, Aaron Fanning

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Kristian O. DeGroot*

OREGON  
JULY 17, 1981  
KRISTIAN O. DEGROOT  
1041

EXP 12/31/199

FILED

Date: 6-29-1998 By: J C

This survey consists of:

Map: \_\_\_\_\_

Narrative: \_\_\_\_\_

Corner Rpt: 65/20-32

DOUGLAS COUNTY  
SURVEYOR