

FILED

FIELD NOTES

OF THE

REMONUMENTATION OF CERTAIN ORIGINAL CORNER POINTS,

TOWNSHIP 21 SOUTH, RANGE 6 WEST,

Date: 12-16-99 By: JC

This survey consists of:

Map: _____

Narrative: 21 PAGES

Corner Rpt: 22 PGS

DOUGLAS COUNTY
SURVEYOR

Of the WILLAMETTE Meridian

In the State of OREGON

EXECUTED BY

William K. Gleason, Cadastral Surveyor

James E. Jelley, Cadastral Surveyor

Under special instructions dated May 3, 1957
April 12, 1967, which provided for the surveys
included under Group Number 350, approved May 6, 1957
March 31, 1967
and assignment instructions dated April 12, 1967

Survey commenced April 19, 19 67

Survey completed May 9, 19 67

INDEX DIAGRAM

Township 21 SOUTH, Range 0 WEST

6	<u>17</u>	8	<u>13</u>	4	<u>10</u>	8	<u>6</u>	2	<u>4</u>	1	<u>1</u>
	<u>16</u>	<u>16</u>	<u>12</u>	<u>12</u>	<u>9</u>	<u>9</u>	<u>6</u>	<u>6</u>	<u>3</u>	<u>3</u>	
7	<u>15</u>	8		9	<u>6</u>	10	<u>5</u>	11	<u>2</u>	12	
	<u>15</u>	<u>14</u>	<u>12</u>	<u>11</u>	<u>11</u>	<u>7</u>		<u>5</u>	<u>2</u>		
18	<u>14</u>	17	<u>10</u>	14		18		14		17	
	<u>13</u>		<u>10</u>								
19		20		21		22		23		24	
30		20		28		27		26		25	
31		32		33		34		35		36	

T. 21 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

During August, 1966, the Oxbow Ridge fire swept across a portion of township 21 south, range 8 west, destroying the undergrowth and killing much of the standing timber. To help meet the administrative needs in the burned area an aerial electronic cadastral resurvey project was conducted jointly by the Oregon State Office Branch of Cadastral Engineering and the Research Branch of the Portland Service Center in the spring of 1967. This project also served to test the limitations and feasibility of adopting this type of survey to the terrain found in western Oregon.

In the course of placing panels at corners for sighting from the air many corners were remonumented or rehabilitated. The record of the action taken at the corners for the portion of the project in this township is included in this set of notes. New and live bearing trees were marked at the corners where possible. In cases where no live trees were available, trees previously used as accessories were remarked on a new blaze, and in situations where the timber had been logged it was necessary to use stumps for corner accessories. Steel fence posts were set alongside the corner monuments to aid in the protection and perpetuation of the corner.

The following field notes describe the remonumentation of certain original corner points in township 21 south, range 8 west, of the Willamette Meridian, Oregon, as provided for in the General Special Instructions, Group No. 350, Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, with New Accessories when Needed"

The mean magnetic declination is 21° E.

Last Boundary, T. 21 S., R. 8 W.,
Willamette Meridian, Oregon

(Rehabilitating a corner established by
Laban H. Wheeler, in 1883, and remonumented
by Marvin J. Lytle, Thomas A. Tillman,
Joseph S. Gawron, and Hans W. Thielsen, in 1952-54)

The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, on the E. bdy. of the
Tp., monumented with an iron post, 1 in. diam., firmly
set, projecting 4 ins. above ground, with brass cap mkd.

$\frac{1}{4}$
S 1 | S 6
1954

from which the remaining original bearing tree

A sawed fir stump, 40 ins. diam., bears
S. 55° W., 41 lks. dist., no marks visible
on decayed blaze.

and bearing trees mkd. in 1954

A fir snag, 32 ins. diam., bears N. 77° E.,
38 lks. dist., with fragmentary scribe marks
visible on open and decayed blaze.

A fir, 25 ins. diam., bears S. 26 $\frac{1}{2}$ ° W.,
47 lks. dist., with scribe marks $\frac{1}{4}$ visible
on open blaze.

and a new bearing tree

Remonumentation of Certain Original Corner Points,
T. 21 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A fir, 35 ins. diam., bears N. 7° E.,
80½ lks. dist., mkd. ¼ S6 BT.

Set a 6 ft. steel fence post alongside the
iron post.

Subdivisions, T. 21 S., R. 8 W.,
Willamette Meridian, Oregon

(Rehabilitating a corner established by
William P. Wright in 1883, and remonumented by
Marvin J. Lytle, Thomas A. Tillman, Joseph S. Gawron,
and Hans W. Thielsen, in 1952-54)

The cor. of secs. 11, 12, 13, and 14, monumented with an
iron post, 2 ins. diam., firmly set, projecting 8 ins.
above ground, with brass cap mkd.

T 21 S R 8 W			
S 11		S 12	
S 14		S 13	
1954			

from which the remaining original bearing trees

A maple, 20 ins. diam., bears N. 48° E.,
30 lks. dist., with healed blaze.

A maple, 16 ins. diam., bears S. 3½° W.,
52 lks. dist., with healed blaze.

A sawed fir stump, 80 ins. diam., bears
N. 75° W., 33 lks. dist., with healed blaze

and bearing trees mkd. in 1954

A root hole, bears N. 22½° E., 81 lks. dist.,
with a down hemlock alongside, 12 ins. diam.,
with scribe marks T21S R8W S12 BT visible
on open blaze.

A hemlock, 25 ins. diam., bears S. 37¼° E.,
112 lks. dist., with scribe marks T21S R8W
S13 BT visible on open blaze.

A fir, 21 ins. diam., bears S. 14° W.,
87 lks. dist., with healed blaze.

A cedar, 50 ins. diam., bears N. 29° W.,
95 lks. dist., with scribe marks T21S R8W
S1 BT visible on open blaze.

Set a 6 ft. steel fence post alongside the iron
post.

(Rehabilitating a corner reestablished by
Marvin J. Lytle, Thomas A. Tillman,
Joseph S. Gawron, and Hans W. Thielsen, in 1952-54)

The ¼ sec. cor. of secs. 11 and 12, monumented with an
iron post, 1 in. diam., firmly set, projecting 8 ins.
above ground, with brass cap mkd.

S 11		S 12	
1954			

Remonumentation of Certain Original Corner Points,
T. 21 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

from which bearing trees mkd. in 1954:

A fir, 12 ins. diam., bears S. $81\frac{1}{2}^{\circ}$ E.,
37 lks. dist., with healed blaze.

A fir, 12 ins. diam., bears N. 34° W.,
46 lks. dist., with scribe marks $\frac{1}{4}$ S11
BT visible on open blaze.

Set a 6 ft. steel fence post alongside the
iron post.

(Rehabilitating a corner established by
William P. Wright, in 1853, and remonumented
by Marvin J. Lytle, Thomas A. Tillman,
Joseph S. Gawron, and Hans W. Thielsen, in 1952-54)

The cor. of secs. 1, 2, 11, and 12, monumented with an
iron post, 2 ins. diam., firmly set, projecting 6 ins.
above ground, with brass cap mkd.

T 21 S R 8 W
S 2 S 1
S 11 S 12
1954

from which the remaining original bearing tree

A fir and cedar grown together, 55 ins. diam.,
bears S. 71° W., 95 lks. dist., with
fragmentary scri marks visible on partially
healed blaze on the cedar. (Record, fir)

and bearing trees mkd. in 1954

A fir, 27 ins. diam., bears N. 44° E.,
64 lks. dist., with healed blaze.

A hemlock, 22 ins. diam., bears S. $8\frac{1}{4}^{\circ}$ E.,
36 lks. dist., with scribe marks T21S R8W
S12 BT visible on open blaze.

A hemlock, 12 ins. diam., bears S. $47\frac{1}{2}^{\circ}$ W.,
16 lks. dist., with scribe marks T21S R8W
S11 BT visible on open blaze.

A fir, 12 ins. diam., bears N. 7° W.,
8 lks. dist., with healed blaze.

Set a 6 ft. steel fence post alongside the iron
post.

(Rehabilitating corners reestablished by
Marvin J. Lytle, Thomas A. Tillman,
Joseph S. Gawron, and Hans W. Thielsen, in 1952-54)

The $\frac{1}{4}$ sec. cor. of secs. 1 and 12, monumented with an
iron post, 1 in. diam., firmly set, projecting 6 ins.
above ground, with brass cap mkd.

$\frac{1}{4}$ S 1
$\frac{1}{4}$ S 12
1954

from which bearing trees mkd. in 1954

Remonumentation of Certain Original Corner Points,
T. 21 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A cedar, 36 ins. diam., bears N. 49° W.,
25 lks. dist., no marks remaining on
decayed blaze. (Record, N. 47° W., 30 lks.)

A fir stump, 75 ins. diam., bears S. 14° E.,
29 lks. dist., with scribe marks $\frac{1}{4}$ S12 BT
visible on open blaze. (Record, 24 lks.)

and a new bearing tree

An alder, 8 ins. diam., bears N. 55° W.,
87 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

Set a 6 ft. steel fence post alongside the
iron post.

The $\frac{1}{4}$ sec. cor. of secs. 1 and 2, monumented with an
iron post, 1 in. diam., firmly set, projecting 6 ins.
above ground, with brass cap mkd.

$\frac{1}{4}$
S 2 | S 1
1954

from which bearing trees mkd. in 1954

A fir, 9 ins. diam., bears S. 8° E.,
14 lks. dist., with healed blaze.

A fir, 25 ins. diam., bears N. 81° W.,
20 lks. dist., with healed blaze.

Set a 6 ft. steel fence post alongside the
iron post.

(Rehabilitating a corner established by
William P. Wright in 1883, and remonumented by
Marvin J. Lytle, Thomas A. Tillman, Joseph S. Gawron,
and Hans W. Thielsen, in 1952-54)

The cor. of secs. 10, 11, 14, and 15, monumented with an
iron post, 2 ins. diam., firmly set, projecting 4 ins.
above ground, with brass cap mkd.

T 21 S R 8 W
S 10 | S 11
S 15 | S 14
1952

from which the remaining original bearing tree

A hemlock, 25 ins. diam., bears S. 50° W.,
10 lks. dist., no marks remaining on
burned blaze.

and bearing trees mkd. in 1952

A root hole, bears N. 56 $\frac{1}{2}$ ° E., 76 lks.
dist., with a down cedar alongside, 20
ins. diam., with scribe marks T21S R8W
S11 BT visible on open blaze.

A hemlock snag, 21 ins. diam., bears
S. 54 $\frac{1}{2}$ ° E., 49 lks. dist., with scribe
marks T21S R8W S14 BT visible on open blaze.

A fir stump, 48 ins. diam., bears S. 35° W.,

GPO

Remonumentation of Certain Original Corner Points,
T. 21 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

128 lks. dist., with scribe marks T21S
R&W S15 BT visible on open blaze.

A fir stump, 60 ins. diam., bears N. 23° W.,
73 lks. dist., no marks remaining on burned
out blaze.

and a new bearing tree

A fir stump, 25 ins. diam., bears N. 23° E.,
41 lks. dist., mkd. T21S R8W S11 BT.

Set a 6 ft. steel fence post alongside the
iron post.

(Rehabilitating a corner reestablished by
Marvin J. Lytle, Thomas A. Tillman,
Josepa S. Gawron, and Hans W. Thielsen, in 1952-54)

The $\frac{1}{4}$ sec. cor. of secs. 11 and 14, monumented with an
iron post, 1 in. diam., firmly set, projecting 4 ins.
above ground, with brass cap mkd.

$\frac{1}{4}$ S 11
S 14
1954

from which bearing trees mka. in 1954

A hemlock, 25 ins. diam., bears N. 74° E.,
37 lks. dist., with fragmentary scribe
marks visible on partially healed blaze.

A hemlock, 16 ins. diam., bears S. 34° E.,
47 lks. dist., with scribe marks $\frac{1}{4}$ S14 BT
visible on open blaze.

Set a 6 ft. steel fence post alongside the
iron post.

(Rehabilitating corners established by
William P. Wright in 1883, and remonumented
by Marvin J. Lytle, Thomas A. Tillman,
Joseph S. Gawron, and Hans W. Thielsen, in 1952-54)

The $\frac{1}{4}$ sec. cor. of secs. 10 and 11, monumented with an
iron post, 1 in. diam., firmly set, projecting 4 ins.
above ground, with brass cap mkd.

$\frac{1}{4}$
S 10 | S 11
1954

from which the remaining original bearing tree

A fir, 55 ins. diam., bears S. 68° W.,
9 lks. dist., no marks remaining on bark
blaze.

and bearing trees mkd. in 1954

A cedar, 32 ins. diam., bears S. 54° 45' E.,
45 lks. dist., with scribe marks $\frac{1}{4}$ S11
BT visible on open blaze.

Remonumentation of Certain Original Corner Points,
T. 21 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A cedar, 35 ins. diam., bears N. 76 $\frac{1}{2}$ ° W.,
74 lks. dist., with scribe marks $\frac{1}{4}$ " S10
BT visible on open blaze.

Set a 6 ft. steel fence post alongside the
iron post.

The cor. of secs. 2, 3, 10, and 11, monumented with an
iron post, 2 ins. diam., firmly set, projecting 4 ins.
above ground, with brass cap mkd.

T 21 S R 8 W
S 3 | S 2
S 10 | S 11
1954

from which the remaining original bearing tree

A burned fir, 18 ins. diam., bears N. 58° E.,
24 lks. dist., with healed blaze.

A burned fir, 15 ins. diam., bears S. 70° E.,
15 lks. dist., with healed blaze.

A burned fir, 31 ins. diam., bears N. 12° W.,
45 lks. dist., with healed blaze.

and a bearing tree mkd. in 1954

A burned fir, 12 ins. diam., bears S. 23° W.,
41 lks. dist., with healed blaze.

Set a 6 ft. steel fence post alongside the
iron post.

The $\frac{1}{4}$ sec. cor. of secs. 2 and 11, monumented with an
iron post, 1 in. diam., firmly set, projecting 4 ins.
above ground, with brass cap mkd.

$\frac{1}{4}$ S 2
S 11
1954

from which the remaining original bearing tree

A burned fir, 30 ins. diam., bears N. 60° E.,
4 lks. dist., no marks remaining on burned
blaze.

and bearing trees mkd. in 1954

A burned hemlock, 15 ins. diam., bears
S. 77 $\frac{1}{2}$ ° E., 6 lks. dist., no marks remaining
on burned blaze.

A burned fir, 30 ins. diam., bears N. 48 $\frac{1}{2}$ ° W.,
45 lks. dist., with healed blaze.

Set a 6 ft. steel fence post alongside the
iron post.

(Rehabilitating a corner reestablished by
Marvin J. Lytle, Thomas A. Tillman,
Joseph S. Gawron, and Hans W. Thielsen, in 1952-54)

The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, monumented with an

Remonumentation of Certain Original Corner Points,
T. 21 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

$\frac{1}{2}$
 S 3 | S 2
 1954

from which bearing trees mkd. in 1954

A burned fir, 20 ins. diam., bears
S. $82\frac{1}{2}^{\circ}$ E., 44 lks. dist., with healed
blaze.

A burned and dead fir, 18 ins. diam.,
bears N. 60° W., 31 lks. dist., no marks
remaining on burned blaze. (Record,
N. $68\frac{1}{2}^{\circ}$ W., 29 lks.)

and a new bearing tree

A burned fir, 22 ins. diam., bears
N. 58° W., 34 lks. dist., mkd. $\frac{1}{2}$ S3 BT.

Set a 6 ft. steel fence post alongside the
iron post.

(Rehabilitating a corner established by
William P. Wright, in 1863, remonumented by
Norman D. Price, in 1945, and subsequently
rehabilitated by Marvin J. Lytle, Thomas J. Tillman,
Joseph S. Gawron, and Hans W. Thielsen, in 1952-54)

The cor. of secs. 9, 10, 15, and 16, monumented with an
iron post, 2 ins. diam., firmly set, projecting 6 ins.
above ground, with brass cap mkd.

T 21 S R 8 W
 S 9 | S 10
 S 16 | S 15
 1945

from which the remaining original bearing tree

A burned and sawed fir stump, 65 ins. diam.,
bears N. 45° W., 20 lks. dist., no marks
remaining on burned blaze.

and bearing trees mkd. in 1945

A sawed fir stump, 50 ins. diam., bears
S. 40° E., 30 lks. dist., no marks remaining
on burned blaze.

A burned and sawed fir stump, 45 ins. diam.,
bears S. 2° W., 60 lks. dist., with scribe
marks W 16 S B visible on partially healed
blaze.

A burned and sawed fir stump, 65 ins. diam.,
bears N. 4° W., 243 lks. dist., no marks
remaining on burned blaze.

and reference monuments set in 1954

An iron post, 2 ins. diam., firmly set,
projecting 2 ins. above the ground, bears
N. $22\frac{1}{2}^{\circ}$ E., 20 lks. distant, with brass cap

Re monumentation of Certain Original Corner Points,
T. 21 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

mkd. T21S R8W S10 RM and an arrow pointing to the corner.

An iron post, 2 ins. diam., firmly set, projecting 2 ins. above the ground, bears S. $22\frac{1}{2}^{\circ}$ W., 20 lks. distant, with brass cap mkd. T21S R8W S16 RM and an arrow pointing to the corner.

Set a steel fence post alongside the corner post.

(Rehabilitating a corner reestablished by Marvin J. Lytle, Thomas A. Tillman, Joseph S. Gawron, and Hans W. Thielsen, in 1952-54)

The $\frac{1}{4}$ sec. cor. of secs. 10 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 10 \\ S 15 \\ 1954 \end{array}$$

from which bearing trees mkd. in 1954

A cedar, 18 ins. diam., bears N. $6\frac{1}{2}^{\circ}$ W., 110 lks. dist., with scribe marks $\frac{1}{4}$ S10 BT visible on open blaze.

A cedar, 14 ins. diam., bears S. $73\frac{1}{2}^{\circ}$ W., 76 lks. dist., with scribe marks $\frac{1}{4}$ S15 BT visible on open blaze.

Set a 6 ft. steel fence post alongside the iron post.

(Rehabilitating a corner established by William P. Wright, in 1883, re monumented by Norman D. Price, in 1945, and subsequently rehabilitated by Norman J. McDonald, in 1963)

The $\frac{1}{4}$ sec. cor. of secs. 9 and 10, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 9 | S 10 \\ 1963 \end{array}$$

from which the original bearing trees

A root hole, bears N. 54° E., 23 lks. dist., with a down fir stump alongside, 25 ins. diam., with scribe marks $\frac{1}{4}$ S visible on open blaze.

A fir snag, 17 ins. diam., bears N. 85° W., 45 lks. dist., with scribe marks $\frac{1}{4}$ S BT visible on open blaze.

and bearing trees mkd. in 1945

A fir, 31 ins. diam., bears S. 20° E., 59 lks. dist., with healed blaze.

A fir, 40 ins. diam., bears N. 89° W.,

Remonumentation of Certain Original Corner Points,
T. 21 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

67 lks. dist., with healed blaze.

and a bearing tree mkd. in 1963

A hemlock, 23 ins. diam., bears N. $75\frac{1}{2}^{\circ}$ E.,
122 lks. dist., with scribe marks $\frac{1}{4}$ S10 BT
visible on open blaze. (Record, N. $72\frac{3}{4}^{\circ}$ E.)

Set a 6 ft. steel fence post alongside the
iron post.

(Rehabilitating a corner established by
William P. Wright, in 1883, and
remonumented by Norman D. Price, in 1945)

The cor. of secs. 3, 4, 9, and 10, monumented with an
iron post, 2 ins. diam., firmly set, projecting 18 ins.
above ground, with brass cap mkd.

T 21 S R 8 W
S 4 | S 3
S 9 | S 10
1945

from which the remains of the original bearing trees

A sawed fir stump, 38 ins. diam., bears
N. 34° E., 22 lks. dist., with healed
blaze.

A fir snag, 16 ins. diam., bears S. $63\frac{1}{2}^{\circ}$ E.,
34 lks. dist., no marks visible on burned
blaze.

A fir stump, 12 ins. diam., bears S. $68\frac{1}{2}^{\circ}$..,
39 lks. dist., with fragmentary scribe
marks visible on burned blaze. (Record,
S. 70° W.)

A sawed fir stump, 30 ins. diam., bears
N. $82\frac{1}{2}^{\circ}$ W., 16 lks. dist., with healed
blaze. (Record, N. 80° ..)

and a bearing tree mkd. in 1945

A burned fir, 27 ins. diam., bears S. 59° E.
40 lks. dist., with fragmentary scribe marks
visible on open blaze.

Set a 6 ft. steel fence post alongside the
iron post.

(Rehabilitating a corner reestablished by
Marvin J. Lytle, Thomas A. Tillman
Joseph S. Gawron, and Hans W. Thielsen in 1952-54)

The $\frac{1}{4}$ sec. cor. of secs. 3 and 10, monumented with an
iron post, 1 in. diam., firmly set, projecting 6 ins.
above ground, with brass cap mkd.

$\frac{1}{4}$ S 3
S 10
1954

from which bearing trees mkd. in 1954

Remonumentation of Certain Original Corner Points,
T. 21 S., R. 8 W., Willamette Meridian, Oregon

CHAINS	
	<p>A burned fir, 30 ins. diam., bears N. 7° 45' E., 41 lks. dist., with healed blaze.</p> <p>A burned fir, 12 ins. diam., bears S. 22½° W., 30 lks. dist., with healed blaze.</p> <p>Set a 6 ft. steel fence post alongside the iron post.</p>
	<p>(Rehabilitating corners established by Norman D. Price, in 1945)</p> <hr/> <p>The ¼ sec. cor. of secs. 3 and 4, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} \frac{1}{4} \\ \text{S } 4 \frac{1}{4} \text{ S } 3 \\ 1945 \end{array}$ </p> <p>from which bearing trees mkd. in 1945</p> <p>A burned and dead fir, 42 ins. diam., bears S. 64½° E., 48 lks. dist., with healed blaze.</p> <p>A burned and dead fir, 23 ins. diam., bears N. 47½° W., 36 lks. dist., with healed blaze.</p> <p>Set a 6 ft. steel fence post alongside the iron post.</p> <hr/> <p>The cor. of secs. 16, 17, 20, and 21, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} \text{T } 21 \text{ S } \text{R } 8 \text{ W} \\ \text{S } 17 \text{ S } 16 \\ \text{S } 20 \text{ S } 21 \\ 1945 \end{array}$ </p> <p>from which new bearing trees</p> <p>A fir, 4 ins. diam., bears N. 54° E., 58 lks. dist., mkd. T21S R8W S16 BT.</p> <p>A fir, 4 ins. diam., bears S. 34½° W., 67 lks. dist., mkd. T21S R8W S20 BT.</p> <p>A fir, 4 ins. diam., bears N. 55½° W., 132 lks. dist., mkd. T21S R8W S17 BT.</p> <hr/> <p>The ¼ sec. cor. of secs. 16 and 17, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} \frac{1}{4} \\ \text{S } 17 \text{ S } 16 \\ 1945 \end{array}$ </p> <p>from which the remaining bearing tree mkd. in 1945</p> <p>A fir stump, 34 ins. diam., bears S. 37½° E.,</p>

Remonumentation of Certain Original Corner Points,
T. 21 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

68 lks. dist., no marks remaining on
burned blaze. Rescribed $\frac{1}{4}$ S16 BT on
new blaze.

and a new bearing tree

A sawed fir stump, 36 ins. diam., bears
N. 34° W., 95 lks. dist., mkd. $\frac{1}{4}$ S17 BT.

The cor. of secs. 8, 9, 16, and 17, monumented with an
iron post, 2 ins. diam., firmly set, projecting 2 ins.
above ground, with brass cap mkd.

T 21 S R 8 W
S 8 | S 9
S 17 | S 16
1945

from which bearing trees mkd. in 1945

A fir stump, 70 ins. diam., bears N. $84\frac{1}{2}^{\circ}$ E.,
37 lks. dist., no marks remaining on burned
out blaze. Rescribed T21S R8W S9 BT on
new blaze.

A fir stump, 64 ins. diam., bears S. $6\frac{1}{4}^{\circ}$ E.,
131 lks. dist., with healed blaze.

A fir stump, 54 ins. diam., bears S. $31\frac{3}{4}^{\circ}$ W.,
50 lks. dist., with healed blaze.

A fir stump, 62 ins. diam., bears N. $83\frac{1}{4}^{\circ}$ W.,
159 lks. dist., with healed blaze.

and new bearing trees

A fir, 8 ins. diam., bears S. $46\frac{1}{2}^{\circ}$ E.,
142 lks. dist., mkd. T21S R8W S16 BT.

A fir, 4 ins. diam., bears S. $60\frac{3}{4}^{\circ}$ W.,
25 lks. dist., mkd. T21S R8W S17 BT.

A fir, 10 ins. diam., bears N. $70\frac{3}{4}^{\circ}$ W.,
118 lks. dist., mkd. T21S R8W S8 BT.

The $\frac{1}{4}$ sec. cor. of secs. 9 and 16, monumented with an
iron post, 1 in. diam., firmly set, projecting 10 ins.
above ground, with brass cap mkd.

$\frac{1}{4}$ S 9
S 16
1945

from which new bearing trees

A burned fir stump, 35 ins. diam., bears
N. 2° E., 79 lks. dist., mkd. $\frac{1}{4}$ S9 BT.

A burned fir, 23 ins. diam., bears S. 45° W.,
 $4\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S16 BT.

Set a 6 ft. steel fence post alongside the
iron post.

Remonumentation of Certain Original Corner Points,
T. 21 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

(Rehabilitating a corner established by
William P. Wright, in 1883, and remonumented
by Norman D. Price, in 1945)

The cor. of secs. 4, 5, 8, and 9, determined at record
bearing and distance from the remaining original bearing
trees:

A burned fir stump, size indeterminate, bears
S. 28° W., 12 lks. dist., no marks
remaining.

A burned fir stump, size indeterminate, bears
N. 57° W., 15 lks. dist., no marks
remaining.

and a bearing tree mkd. in 1945

A fir, 32 ins. diam., bears S. 46½° W.,
96 lks. dist., with scribe marks T21S R8W
S8 BT visible on open blaze.

At the corner point

Set a fiberglass post, 28 ins. long, 2½ ins. diam., 20
ins. in the ground, and in a mound of stone, 4 ft. base,
to top, with brass cap mkd.

T 21 S R 8 W
S 5 S 4
S 8 S 9
1967

from which new bearing trees and a bearing object

A dead maple, 12 ins. diam., bears
N. 84° E., 115 lks. dist., mkd. T21S R8W
S4 BT.

A sandstone outcrop, bears S. 28° E.,
160 lks. dist., mkd. X B O, with concrete
nail driven at center of X.

Set a 6 ft. steel fence post, alongside the
fiberglass post.

The ¼ sec. cor. of secs. 4 and 9, monumented with an
iron post, 1 in. diam., firmly set, projecting 10 ins.
above ground, with brass cap mkd.

¼ S 4
S 9
1945

from which the original bearing trees

A root hole, bears North, 28 lks. dist.,
with a down cedar alongside, 45 ins. diam.,
with healed blaze.

A fir, 45 ins. diam., bears S. 10° W.,
19 lks. dist., with healed blaze.

and a bearing tree mkd. in 1945

A fir, 39 ins. diam., bears N. 41° W.,
76 lks. dist., with healed blaze.

Remonumentation of Certain Original Corner Points,
T. 21 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

Set a 6 ft. steel fence post alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with melted brass cap, no marks legible, from which the original bearing trees:

A fir, 60 ins. diam., bears N. 22° E., 29 lks. dist., no marks remaining on burned out blaze. Rescribed $\frac{1}{4}$ S4 BT on new blaze. (Record, 26 lks.)

A fir stump, size indeterminate, bears S. 31° W., 29 lks. dist., no marks remaining on burned blaze. (Record, S. 24° W.)

and a bearing tree mkd. in 1945

A maple, 18 ins. diam., bears S. 44° W., 66 lks. dist., no marks remaining on burned blaze. (Record, S. 42° W.)

At the corner point

Set a fiberglass post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$
S 5 | S 4
1967

from which a new bearing tree

A maple, 5 ins. diam., bears S. 49° W., 69 lks. dist., mkd. $\frac{1}{4}$ S5 BT.

Deposit the 1 in. iron post at base, and set a 6 ft. steel fence post alongside the iron post.

(Rehabilitating corners reestablished by Norman D. Price, in 1945)

The cor. of secs. 17, 18, 19, and 20, monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 21 S R 8 W
S 18 | S 17
S 19 | S 20
1945

from which the remaining bearing trees mkd. in 1945

A burned fir, 62 ins. diam., bears S. 36° E., 168 lks. dist., with healed blaze.

A fir, 30 ins. diam., bears N. 45° W., 174 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

and new bearing trees

A fir; 17 ins. diam., bears N. 83° E.,

Remonumentation of Certain Original Corner Points,
T. 21 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

83 lks. dist., mkd. T21S R8W S17 BT.

A maple, 20 ins. diam., bears S. 12° E.,
23 lks. dist., mkd. T21S R8W S20 BT.

A cedar, 15 ins. diam., bears S. 67° W.,
85 lks. dist., mkd. T21S R8W S19 BT.

Set a 6 ft. steel fence post alongside the
iron post.

The $\frac{1}{4}$ sec. cor. of secs. 17 and 18, monumented with an
iron post, 1 in. diam., firmly set, projecting 6 ins.
above ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 18 \text{ | } \text{S } 17 \\ 1945 \end{array}$$

from which bearing trees mkd. in 1945

A burned fir stump, 60 ins. diam., bears
N. 4° E., 58 lks. dist., no marks remaining
on burned blaze.

A burned fir stump, 52 ins. diam., bears
S. 42 $\frac{1}{2}$ ° W., 76 lks. dist., no marks remaining
on burned blaze.

and new bearing trees

A fir, 5 ins. diam., bears N. 63 $\frac{1}{2}$ ° E.,
6 lks. dist., mkd. $\frac{1}{4}$ S17 BT.

A fir, 5 ins. diam., bears S. 50° W.,
34 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

Set a 6 ft. steel fence post alongside the iron
post.

(Rehabilitating a corner reestablished by
Norman D. Price, in 1945, and subsequently
rehabilitated by Floyd A. Brooks, in 1960)

The cor. of secs. 7, 8, 17, and 18, monumented with an
iron post, 2 $\frac{1}{2}$ ins. diam., firmly set, projecting 4 ins.
above ground, with brass cap mkd.

$$\begin{array}{c} \text{T } 21 \text{ S } \text{R } 8 \text{ W} \\ \text{S } 7 \text{ | } \text{S } 8 \\ \text{S } 18 \text{ | } \text{S } 17 \\ 1960 \end{array}$$

from which bearing trees mkd. in 1945

A burned and sawed fir stump, 23 ins. diam.,
bears N. 31° E., 35 lks. dist., with healed
blaze.

A burned and sawed fir stump, 24 ins. diam.,
bears S. 54 $\frac{1}{2}$ ° E., 48 lks. dist., with healed
blaze.

A burned and sawed fir stump, 27 ins. diam.,
bears S. 57 $\frac{1}{2}$ ° W., 131 lks. dist., with healed
blaze.

Remonumentation of Certain Original Corner Points,
T. 21 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

A burned and sawed fir stump, 35 ins. diam., bears N. 17° W., 134 lks. dist., with healed blaze.

and a bearing tree mkd. in 1960

A fir, 4" ins. diam., bears S. 54½° E., 229 lks. dist., with scribe marks T21S R8W S17 BT visible on open blaze.

Set a 6 ft. steel fence post alongside the iron post.

(Rehabilitating corners reestablished by
Norman D. Price, in 1945)

The ¼ sec. cor. of secs. 8 and 17, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 8 \\ S 17 \\ 1945 \end{array}$$

from which bearing trees mkd. in 1945

A fir, 42 ins. diam., bears N. 4½° E., 65 lks. dist., no marks remaining on burned blaze. Rescribed ¼ S8 BT on new blaze.

A root hole, bears S. 18° W., 22 lks. dist., with a down fir alongside, 22 ins. diam., no marks remaining on burned blaze.

and a new bearing tree

A fir, 7 ins. diam., bears South, 31 lks. dist., mkd. ¼ S17 BT.

The ¼ sec. cor. of secs. 7 and 18, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 7 \\ S 18 \\ 1945 \end{array}$$

from which bearing trees mkd. in 1945

A burned and sawed fir stump, 80 ins. diam., bears N. 74° E., 42 lks. dist., no marks visible. Rescribed ¼ S7 BT on new blaze.

A burned and sawed fir stump, 70 ins. diam., bears S. 3½° E., 36 lks. dist., no marks visible. Rescribed ¼ S18 BT on new blaze.

Set a 6 ft. steel fence post alongside the iron post.

The ¼ sec. cor. of secs. 7 and 8, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

Remonumentation of Certain Original Corner Points,
T. 21 S., R. 8 W., Willamette Meridian, Oregon.

CHAINS

$\frac{1}{4}$
 S 7 | S 8
 1945

from which bearing trees mkd. in 1945

A burned fir stump, 30 ins. diam., bears N. 85° E., 42 lks. dist., with burned blaze.

A burned and sawed fir stump, 16 ins. diam., bears S. 71½° W., 76 lks. dist., with scribe marks S7 BT visible on open and burned blaze.

and new bearing trees

A fir, 40 ins. diam., bears N. 41½° E., 174 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

A fir, 35 ins. diam., bears N. 84° W., 208 lks. dist., mkd. $\frac{1}{4}$ S7 BT.

Set a 6 ft. steel fence post alongside the iron post.

The cor. of secs. 5, 6, 7, and 8, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

T 21 S R 8 W
 S 6 | S 5
 S 7 | S 8
 1945

from which bearing trees mkd. in 1945

A fir snag, 70 ins. diam., bears N. 55½° E., 34 lks. dist., no marks remaining on burned blaze. Rescribed T21S R8W S5 BT on new blaze.

A burned fir stump, 50 ins. diam., bears S. 70¼° E., 97 lks. dist., no marks remaining on burned blaze.

A burned fir stump, 50 ins. diam., bears S. 16¼° W., 117 lks. dist., with scribe marks T21S R8W S7 visible on open and burned blaze.

A fir snag, 60 ins. diam., bears N. 4¼° W., 114 lks. dist., no marks remaining on burned blaze.

and a new bearing tree

A fir, 4 ins. diam., bears N. 54° W., 67 lks. dist., mkd. T21S R8W S6 BT.

Set a 6 ft. steel fence post alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 5 and 8, monumented with an iron post, 1 in. diam., firmly set, projecting 3 ins. above ground, with brass cap mkd.

GPO

Remonumentation of Certain Original Corner Points,
T. 21 S., R. 8 W., Willamette Meridian, Oregon

CHAINS

$$\frac{1}{4} \frac{S 5}{S 8}$$

1945

from which new bearing trees

A fir, 5 ins. diam., bears N. $20\frac{1}{4}^{\circ}$ W.,
98 lks. dist., mkd. $\frac{1}{4}$ S5 BT.

An alder, 10 ins. diam., bears S. 60° E.,
60 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

Set a 6 ft. steel fence post alongside the
iron post.

The $\frac{1}{4}$ sec. cor. of secs. 5 and 6, monumented with an
iron post, 1 in. diam., firmly set, projecting 4 ins.
above ground, with brass cap mkd.

$$S 6 \frac{1}{4} S 5$$

1945

from which the remaining bearing tree mkd. in 1945

A sawed fir stump, 30 ins. diam., bears
S. 70° E., 52 lks. dist., no marks remaining
on burned blaze.

and a new bearing tree

A burned fir snag, 12 ins. diam., bears
S. 89° E., 58 lks. dist., mkd. $\frac{1}{4}$ S5 BT.

A fir, 4 ins. diam., bears S. $83\frac{1}{2}^{\circ}$ W.,
25 lks. dist., mkd. $\frac{1}{4}$ S6 BT.

Set a 6 ft. steel fence post alongside the
iron post.

CERTIFICATE OF SURVEY

XX(We), William W. Glenn and James E. Jelley, Cadastral Surveyors, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 12th day of April, 1967, XX(We) have remonumented certain original corner points, township 21 south, range 8 west,

of the Willamette Meridian, in the State of Oregon, which are represented in the foregoing field notes as having been executed by (us) and under (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 15, 1968 (Date)

William W. Glenn (Cadastral Surveyor)

February 15, 1968 (Date)

James E. Jelley (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Washington, D C.

The foregoing field notes of the remonumentation of certain original corner points, township 21 south, range 8 west, Willamette Meridian, Oregon,

executed by William W. Glenn and James E. Jelley, Cadastral Surveyors, having been critically examined and found correct, are hereby approved.

MAR 3 1977 (Date)

J. J. Jordan Acting (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys is a true copy of the original field notes

(Date)

(Chief, Division of Cadastral Survey) GPO 149 626

10. 65/27 1 U