

**REWITNESSED CORNER FOR
STATE OF OREGON - DEPARTMENT OF FORESTRY**

Southeast Section corner Section 10 only, Township 23 South, Range 10 West, W.M.,
Douglas County, Oregon.

ORIGINAL by Levi Walker, 1906

No original evidence found

REESTABLISHMENT by Arnold G. Gibson, 1972

Oregon State Board of Forestry 1 1/2" x 36" galvanized iron pipe with 3" bronze cap
(missing) from which a:

- 20" Fir N16°W 183.4 ft.; now 21" x 3' high rotted stump in place, axe work visible on bark.
- 16" Fir N50°W 149.1 ft.; now 10" x 3' high rotted stump in place, axe work visible on bark.
- 4" x 4" x 72" white painted cedar post North 2.0 ft.; reset in 1976.

RESTORED by Arnold G. Gibson, 1976

Oregon State Board of Forestry 1 1/2" x 36" galvanized iron pipe with 3" bronze cap,
1976 (in place)

Reset 4" x 4" x 72" white painted cedar post N20°W 1.6 ft. with yellow metal location poster; now rotted and fallen over.

REWITNESSED from the above pipe and cap

- 8" Fir N71°W 27.1 ft. to aluminum nail in BT face scribed T23SR10WS10BT.
- Carsonite Witness Post N17°W 3.9 ft. to base.
- Carsonite Witness Post N89°W 2.6 ft. to base.

Bearing tree tag on 8" Fir BT N71°W 27.1 ft.

Magnetic variation set at 20° east.

Dated September 26, 2000

Rewitnessed by Jim Van Vleet under my direction.
Tim VanVleet

FILED

Date: 10-30-2000 By: JC
This survey consists of:
Map: _____
Narrative: _____
Corner Hpt: 65/33-2

**DOUGLAS COUNTY
SURVEYOR**



James M. McIntosh



Expiration date of certificate 12-31-00

Present and witnessed by Ralph C. Hall

C.S. File No. 65/33-2