

**REWITNESSED CORNER FOR  
STATE OF OREGON – DEPARTMENT OF FORESTRY**

Section corner common to Sections 11 and 14, Township 23 South, Range 10 West,  
W.M., Douglas County, Oregon.

**ORIGINAL by William H. Byars 1879**

No evidence of corner found.

**Survey by Levi C. Walker, 1906**

No evidence of corner found.

**REESTABLISHMENT by Arnold G. Gibson, 1972**

Oregon State Board of Forestry 1 ½" x 36" galvanized iron pipe with 3" bronze cap  
(in place) from which a:

- 9" Fir N77°E 23.5 ft.; missing, in road.
- 10" Fir S28 ½°E 44.0 ft.; missing, in road.
- 4" x 4" x 72" white painted cedar post N80°E 2.8 ft.; in place.

**REWITNESSED by Arnold G. Gibson, 1976**

- 14" Fir S01°W 111.9 ft.; now 21" in place, face closed.
- 15" Fir stump S31°E 108.5 ft.; now 12" x 2' high rotted stump in place, no marks visible.

**REWITNESSED from the above pipe and cap:**

- 11" Fir N57°E 8.6' to aluminum nail in BT face scribed T23SR10WS11BT.
- Carsonite witness post N84°E 3.7' to base.
- Carsonite witness post S28°E 3.6' to base.
- 10" Fir S10°E 26.7' to aluminum nail in BT face scribed T23SR10WS14BT.

Bearing tree tag on 11" Fir BT N57°E 8.6 ft., 10" Fir BT S10°E 26.7 ft. and white painted cedar post N80°E 2.8'.

Magnetic variation set at 20° east.

Dated October 7, 2000

Rewitnessed by Tim VanVleet under my direction.  
Tim VanVleet



*James M. McIntosh*  
**OREGON**  
JULY 18, 1984  
**JAMES M. MCINTOSH**  
2103

Expiration date of certificate 12-31-00

Present and witnessed by Ralph C. Hall

C.S. File No. 65/33-4

**FILED**

Date: 10/30/2000 By: JC  
This survey consists of:  
Map: \_\_\_\_\_  
Narrative: \_\_\_\_\_  
Corner Rpt: 65/33-4

**DOUGLAS COUNTY  
SURVEYOR**