

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: THIS CORNER WAS ORIGINALLY ESTABLISHED IN SURVEY BY WILLIAM J. RUPPERT FOR THE U.S.D.A. FOREST SERVICE DATED NOVEMBER, 1977 AS TILLER LAND SURVEY #24 UNDER CONTRACT #006522N. RECORDED IN DOUGLAS COUNTY SURVEYOR'S OFFICE AS M65-50.  
SET 2" X 30" GALVANIZED STEEL PIPE 25" IN THE GROUND WITH A STONE MOUND AROUND IT, WITH A 2 1/2" DIA. BRASS CAP PERMANENTLY ATTACHED TO THE TOP, STAMPED:

"T31S R1W"  
S 1/16  
S8 | S9  
PLS 866  
"1977"

FROM WHICH A:

12" D. FIR BEARS S 43° 20'E, 16.8 FT. SCRIBED "S 1/16 S9 BT".  
15" D. FIR BEARS N23° 03'W, 45.7 FT. SCRIBED "S 1/16 S8BT".

Description of corner evidence found: FOUND A 2" GALVANIZED IRON PIPE SET FLUSH IN A 36" DIA. STONE MOUND WITH A 2 1/2" DIA. BRASS CAP FIRMLY AFFIXED TO THE TOP, STAMPED AS PER RECORD.

FROM WHICH BEARING TREES BY RUPPERT:

WAS 12" NOW 19" D. FIR BEARS S 43° 20' E(REC.), 16.8 FT. (REC.) WITH A HEALED FACE.  
WAS 15" NOW 15" 5 FT HIGH D. FIR STOB BEARS N 23° 03' W (REC.), 45.7 FT (REC) WITH SCRIBING "S 1/16 S8 BT" VISIBLE ON AN UNHEALED FACE.

Description of monument and accessories I established to perpetuate the original location of this corner:

NEW BEARING TREE:

12" D. FIR BEARS N 17° W, 36.7 FT. WHICH I SCRIBED "S 1/16 S8 BT" ON A DOUBLE FACE. I PLACED A BRASS WASHER STAMPED "PLS 1941" IN THE LOWER FACE.

ALL BEARING TREES WERE PAINTED WITH A RED 6" BAND AND FACES. F. S. SIGN 54-9 ATTACHED TO THE BACK OF EACH TREE. BEARING TREE TAGS WERE UPDATED OR REPLACED.

EQUIPMENT: WARREN - KNIGHT STAFF COMPASS

MAGNETIC DECLINATION 17° 30' E. (DETERMINED FROM RECORD OF POSTED LINE TO NORTH)

WITNESSES: L. FANNING, M. DIXON, M.CALVERT

FILED

Date: 2-21-2001 By: JC

This survey consists of:

Map: \_\_\_\_\_

Narrative: \_\_\_\_\_

Corner Rpt: 65/36-6

DOUGLAS COUNTY  
SURVEYOR

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

*Lester L. Fanning*

OREGON  
JULY 17, 1994  
LESTER L. FANNING  
2684

EXPIRES  
12-31-01

C.S. File No. 65/36-6