

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: THIS CORNER WAS ORIGINALLY ESTABLISHED IN SURVEY BY WILLIAM J. RUPPERT FOR THE U.S.D.A. FOREST SERVICE DATED NOVEMBER, 1977 AS TILLER LAND SURVEY #24 UNDER CONTRACT #006522N. RECORDED IN DOUGLAS COUNTY SURVEYOR'S OFFICE AS M65-50.
SET 2" X 30" GALVANIZED STEEL PIPE 25" IN THE GROUND WITH A STONE MOUND AROUND IT, WITH A 2 1/2" DIA. BRASS CAP PERMANENTLY ATTACHED TO THE TOP, STAMPED:

"T31S R1W"
E 1/16
C — C
S8
PLS 866
"1977"

FROM WHICH A:

14" D. FIR BEARS S 63°W, 22.3 FT. SCRIBED "CE 1/16 S8 BT".
24" D. FIR BEARS S 71° 20' E. 66.7 FT. SCRIBED "CE 1/16 S8BT".

Description of corner evidence found: : FOUND A 2" GALVANIZED IRON PIPE SET FLUSH IN A 72" DIA. STONE MOUND WITH A 2 1/2" DIA. BRASS CAP FIRMLY AFFIXED TO THE TOP, STAMPED AS PER RECORD.

FROM WHICH BEARING TREES BY RUPPERT:

WAS 14" NOW 18" D. FIR BEARS S 63° W (REC.), 22.3 FT. (REC.) WITH A HEALED FACE.
WAS 24" NOW 27" D. FIR BEARS S 71° 20' E (REC.), 67.5 FT (REC. 66.7 FT) WITH A HEALED FACE.

Description of monument and accessories I established to perpetuate the original location of this corner:
ALL BEARING TREES WERE PAINTED WITH A RED 6" BAND AND FACES. F. S. SIGN 54-9 ATTACHED TO THE BACK OF EACH TREE. BEARING TREE TAGS WERE UPDATED OR REPLACED.

MAGNETIC DECLINATION 20° E.

WITNESSES: L. FANNING, M. DIXON, M.CALVERT

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Lester L. Fanning

OREGON
JULY 17, 1994
LESTER L. FANNING
2684

EXPIRES
12-31-01

FILED

Date: 2-21-2001 By: JC

This survey consists of:

Map: _____

Narrative: _____

Corner Rpt: 65/36-7

DOUGLAS COUNTY
SURVEYOR