

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: THIS CORNER WAS ORIGINALLY ESTABLISHED IN SURVEY BY WILLIAM J. RUPPERT FOR THE U.S.D.A. FOREST SERVICE DATED NOVEMBER, 1977 AS TILLER LAND SURVEY #24 UNDER CONTRACT #006522N. RECORDED IN DOUGLAS COUNTY SURVEYOR'S OFFICE AS M65-50.

SET 2" X 30" GALVANIZED STEEL PIPE 25" IN THE GROUND WITH BRASS CAP STAMPED:

"T31S R1W"

S5

E 1/16 —

S8

PLS 866

"1977"

CONSTRUCTED CAIRN TO TOP OF CAP.

FROM WHICH A:

16" D. FIR BEARS N 35° 21' E, 42.5 FT. SCRIBED "E 1/16 S5 BT".

16" D. FIR BEARS S 11° 21' E, 117.7 FT. SCRIBED "E 1/16 S8BT".

Description of corner evidence found: FOUND A 2" GALVANIZED IRON PIPE SET FLUSH IN A 36" DIA. STONE MOUND WITH A 2 1/2" DIA. BRASS CAP FIRMLY AFFIXED TO THE TOP, STAMPED AS PER RECORD.

FROM WHICH BEARING TREES BY RUPPERT:

WAS 16" NOW 16" +/- 20 FT. TALL D. FIR SNAG BEARS N 35° 21' E (REC.), 41.7 (REC. 42.5 FT.) WITH SCRIBING "E 1/16 S5 BT" VISIBLE IN OPEN FACE. THIS TREE WAS PROBABLY DEAD WHEN ORIGINALLY SCRIBED.

WAS 16" NOW 26" D. FIR BEARS S 11° 21' W (REC S 11° 21' E), 115.7 FT. (REC. 117.7 FT.) WITH HEALED FACE.

Description of monument and accessories I established to perpetuate the original location of this corner:

NEW BEARING TREE:

29" D. FIR BEARS N 51° E, 35.8 FT. WHICH I SCRIBED "E 1/16 S5 BT" ON A DOUBLE FACE. I PLACED A BRASS WASHER STAMPED "PLS 1941" IN THE LOWER FACE.

ALL BEARING TREES WERE PAINTED WITH A RED 6" BAND AND FACES. F. S. SIGN 54-9 ATTACHED TO THE BACK OF EACH TREE. BEARING TREE TAGS WERE UPDATED OR REPLACED.

MAGNETIC DECLINATION 20° E.

WITNESSES: L. FANNING, M. DIXON, M.CALVERT

FILED

Date: 2-21-2001 By: JC

This survey consists of:

Map: _____

Narrative: _____

Corner Rpt: 65/36-8

DOUGLAS COUNTY
SURVEYOR

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Lester L. Fanning

OREGON
JULY 17, 1994
LESTER L. FANNING
2664

EXPIRES
12-31-01