

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: THIS CORNER WAS ORIGINALLY ESTABLISHED BY DENNIS HATHORN, DEPUTY SURVEYOR UNDER HIS CONTRACT # 73 DATED JUNE 8, 1857. SET POST FOR CORNER FROM WHICH:


- 10" OAK BEARS N 85° W. 47 LKS
- 10" OAK BEARS S 12° W. 67 LKS
- 15" OAK BEARS N 77° E. 39 LKS
- 15" OAK BEARS S 25° E. 64 LKS

AND RESTORED BY JOHN M. POWELL, SEPT , 1966 AND RECORDED IN THE DOUGLAS COUNTY SURVEYOR'S OFFICE AS C.S. 54/28.

FOUND ORIGINAL BEARING TREES:

- WAS 10" NOW OAK STOB BEARS N 85° W, 31.0 FT. SHOWS GOOD SCAR.
- WAS 10" NOW 15" OAK BEARS S 12° W, 44.2 FT. SHOWS GOOD SCAR.
- WAS 15" NOW OAK STOB BEARS S 25° E, 42.2 FT. SCRIBE "2W" VISABLE.
- WAS 15" NOW 26" OAK BEARS N 77° E, 25.1 FT. SHOWS GOOD SCAR.

SET BRASS CAP MARKED: "COUNTY SURVEYORS OFFICE"



FILED

Date: 2-21-2001 By: JC

This survey consists of:

Map: _____

Narrative: _____

Corner Rpt: 65/36-9

DOUGLAS COUNTY SURVEYOR

FROM WHICH NEW BEARING TREES:

- 17" W. OAK BEARS N 30° W, 39.3 FT. MARKED "T30S R2W S 35 CS BT".
- 15" W. OAK BEARS S 22° E, 45.4 FT. MARKED "T31S R2W S1 CS BT".

SURVEY BY GLENN S. BAUGHMAN FOR U.S.D.A. FOREST SERVICE DATED FEB., 1978 AS TILLER LAND SURVEY #23, UNDER CONTRACT #006687N. RECORDED IN DOUGLAS COUNTY SURVEYOR'S OFFICE AS M 65-56.

FOUND COUNTY SURVEYOR'S 1" IRON PIPE EXPOSED 20 " ABOVE THE GROUND WITH 2 1/2 " DIA. BRASS CAP STAMPED AS PER RECORD.

FROM WHICH ORIGINAL BEARING TREES:

- WAS 10" OAK, NOW 7 FT HIGH STOB, BEARS N 85° W, 31.0 FT. WITH HEALED FACE.
- WAS 10 " NOW 18" OAK BEARS S 12° W, 44.2 FT. WITH HEALED FACE.
- WAS 15" NOW 28" OAK BEARS N 77° E, 25.1 FT. WITH HEALED FACE.

AND BEARING TREES BY POWELL:

- WAS 17" NOW 18" OAK BEARS N 30° W, 39.3 FT. WITH HEALED FACE.
- WAS 15" NOW 16" OAK BEARS S 22° E, 45.4 FT. WITH SCRIBING VISIBLE.

Description of corner evidence found: FOUND 1" GALVANIZED IRON PIPE EXPOSED 20" ABOVE GROUND WITH A 2 1/2 " DIA. BRASS CAP FIRMLY AFFIXED TO THE TOP STAMPED AS PER RECORD.

FROM WHICH ORIGINAL BEARING TREES:

- WAS 10" NOW FALLEN AND ROTTED OAK, ROOT CROWN BEARS N 81° W (REC N 85° W), 31.0 FT. (REC. 47 LKS).
- WAS 10" NOW 21" OAK BEARS S 10° 30' W (REC S 12° W.), 44.2 FT. (REC 67 LKS) WITH HEALED FACE.
- WAS 15" NOW 30" OAK BEARS N 81° E (REC. N 77° E), 25.1 FT. (REC. 39 LKS) WITH HEALED FACE.
- WAS 15" NOW ROTTED OAK ROOT CROWN BEARS S 25° E (REC.), 42.2 FT. (REC. 64 LKS).

AND BEARING TREES BY POWELL:

- WAS 17" NOW 20 " OAK SNAG BEARS N 27° 30' W, (REC. N 30° W), 39.3FT. (REC.) WITH GOOD SCAR.
- WAS 15" NOW 21" OAK BEARS S 24° E (REC S 22 ° E), 45.4 FT. (REC.) WITH HEALED FACE. THIS TREE IS A SECOND TRUNK FROM THE SAME ROOT CROWN AS THE ORIGINAL MISSING IN THIS SECTION.

Description of monument and accessories I established to perpetuate the original location of this corner:

I SCRIBED ANEW BEARING TREE:

- 16" D. FIR BEARS N 29° W, 33.3 FT. WHICH I SCRIBED "T30S R2W S35 BT" ON A DOUBLE FACE. I PLACED A BRASS WASHER STAMPED "PLS 1941" IN THE LOWER FACE.

ALL BEARING TREES WERE PAINTED WITH A RED 6" BAND AND FACES. F. S. SIGN 54-9 ATTACHED TO THE BACK OF EACH TREE. BEARING TREE TAGS WERE UPDATED OR REPLACED.

EQUIPMENT: WARREN - KNIGHT STAFF COMPASS

MAGNETIC DECLINATION 17° 30' E. (DETERMINED FROM RECORD OF POSTED LINE TO NORTH

WITNESSES: L. FANNING, M. DIXON, M.CALVERT

REGISTERED PROFESSIONAL LAND SURVEYOR

Lester L. Fanning

OREGON JULY 17, 1994 LESTER L. FANNING 2684

C.S. File No. 65/36-9

EXPIRES 12-31-01