OREGON CORNER RESTORATION FORM

Corner No. 28

Section 27 Township 32S Range 7W

County Douglas Date March, 2002

Mining Claim
Corner Designation



X Condition Report Only
___ Not Found
___ Renewed
___ Unrecorded
___ Surveyed In
___ Referenced Out

Previous Renewals/Surveys, etc.
Briggs, U.S.G.L.O., 1901 Survey Plat.
RLS Van Swearingen, Map No. M21-61, 1961 Survey.

Monument(s) & Accessories Found: (Condition and Source)
Found Drill Steel, from which a:
28" Madrone, original BT, old face, bears S18¾°E, 72⁸ feet (Record 76⁰ feet).
28" Madrone, original BT, old face, bears N71°E, 42⁰ feet (Record 44 feet).

Monument Detail

Sketch

FILED
Date: 3/27/2002 By: JC
This survey consists of:
Map: M137-35
Narrative:
Corner Rpt: 65/42-38

DOUGLAS COUNTY
SURVEYOR

Monument Set (Procedures and Description)

New Accessories
6 Foot Steel Fence Post bears West, 0⁵ feet.

Location & Comments

Surveyor's Seal

Compass Declination 20°E
Firm/Agency Shaner Engineering
Address P.O. Box 1430
Roseburg, OR 97470
Party Chief B. Shaner
Notes " "
Witness Ron Schneider

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Bruce A Shaner

OREGON
OCT. 4, 1957
BRUCE A. SHANER
430

Renews June 30, 2002

C.S. File No 65/42-38