

FILED

Date: 12-16-2002 By: X

This survey consists of:

Map: _____

Name: _____

Corner: 65/44-31 A&B

OREGON CORNER RESTORATION FORM

Section 22 Township 21S Range 8W

County Douglas Date 12/10/02

DOUGLAS COUNTY
SURVEYOR

Corner Designation

Section Corner
Sections 22, 23, 26, 27

- Condition Report Only
- Not Found
- Renewed
- Unrecorded
- Surveyed In
- Referenced Out

Previous Renewals/Surveys, etc. _____

See T21S, R8W Card 500300 and unofficial until
approved BLM re-monumentation notes


Monument(s) & Accessories Found: (Condition and Source)

3" BLM BC marked as shown

28" D. Fir bears N 27° E 125.4 ft - healed face (Lytle)
35" D. Fir bears S 29 1/2° W 84.5 ft - healed face (Lytle)

12" Hem. bears N 54 1/2° W 20.9 ft - open face (1999)
2" D. Fir (1999) down out of position

Monument Detail



Sketch

Monument Set (Procedures and Description)

None

New Accessories

10" D. Fir bears N 16° W 26.3 ft blazed, scribed "T21S R8W S22 BT"

Location & Comments

Compass Declination _____

Firm/Agency _____

ward Northwest Inc.

Address P O Box 125

Florence OR 97439

Party Chief Ron Rice

Notes 02-74

Witness Ben Pastor

Surveyor's Seal

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Ronald L Rice

OREGON
JULY 9, 2002
RONALD L. RICE
#54633 LS

EXPIRES: 12/31/02

FILED

OPTIONAL FORM 99 (7-90)

FAX TRANSMITTAL

of pages 1

8

Date: 12/14/2002 By: JC

This survey consists of:

To: ROB WARD
 Dept / Agency: _____
 From: AARON GRAHAM
 Phone #: 541-751-4248
 Fax #: _____
 Fax #: 541-997-3546
 NSN 7540-01-317-7300 5099-101

nal Lines, T. 21 S., R. 9 W.,
amette Meridian, Oregon

Map: _____
Name: _____

Corner: 65/44-31A/B

**UNOFFICIAL
UNTIL APPROVED**

1/4 S 26
S 35
1952

DOUGLAS COUNTY
SURVEYOR

from which the remains of bearing trees mkd. by Lytle

A cedar snag, 17 ins. diam., bears S. 32 1/2° E., 3.9 ft. dist.,
with no marks visible.

A fir, 47 ins. diam., bears N. 73° W., 40.3 ft. dist., with
a healed blaze.

and a new bearing tree

A cedar, 42 ins. diam., bears S. 10° E., 51.1 ft. dist., mkd.
1\4 S35 BT.

The cor. of secs. 22, 23, 26 and 27, determined at record bearing
and distance to the NE. bearing tree, and record distance to the
SW. bearing tree:

from which bearing trees mkd. by Lytle

A fir, 65 ins. diam., bears N. 27° E., 125.4 ft. dist., with
a healed blaze.

A fir, 35 ins. diam., bears S. 29 1/2° W., 84.5 ft. dist., with
a healed blaze. (Record. S. 27 1/2° W.)

and new bearing trees

A fir, 7 ins. diam., bears S. 75 1/2° E., 8.0 ft. dist., mkd. X
BT.

A hemlock, 11 ins. diam., bears N. 54 1/2° W., 20.9 ft. dist.,
mkd. T21S R8W S22 BT.

At the corner point

Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 21 S R 8 W
S 22 S 23
S 27 S 26
1999

**UNOFFICIAL
UNTIL APPROVED**

The corner falls on a steep E. slope.

The 1\4 sec. cor. of secs. 14 and 23, monumented with an iron
post, 1 in. diam., firmly set, projecting 2 ins. above the ground,
with brass cap mkd.