

FILED DEC 30 2004

Form 9180-6
(April 1974)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL 289

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,

TOWNSHIP 26 SOUTH, RANGE 10 WEST,

AND

A PORTION OF THE SOUTH BOUNDARY AND SUBDIVISIONAL LINES,

AND

REMONUMENTATION OF AN ORIGINAL CORNER POINT,

TOWNSHIP 26 SOUTH, RANGE 9 WEST,

Filed in a C.S. File because only 1 corner
is in Douglas Co. - The sec cor to Secs.
33 & 34 (south) only.

JC-DCSO - 12-30-2004

Of the WILLAMETTE Merid. in
In the State of OREGON

EXECUTED BY

Owen C. Chatters II, Cadastral Surveyor

Jack W. Bowder, Cadastral Surveyor

Under special instructions dated May 3 1957 approved May 6, 1957

special instructions dated July 28, 1972, approved July 31, 1972, and
supplemental special instructions dated March 18, 1975, approved March 18, 1975

which provided for the surveys included under U.S. Survey Group

Number s 350 and 791 and assignment instructions dated September 5 1972.

March 29, 1973, and March 28, 1975

Survey commenced September 8 1972

Survey completed August 5 1977

C.S. File No

65/52-19A

12/30/2004 Douglas County Clerk

Dependent Resurvey of a Portion of the East Boundary,
T. 26 S., R. 10 W., Willamette Meridian, Oregon

CHAINS
40.26

The $\frac{1}{4}$ sec. cor. of sec. 12 only, monumented with the original sandstone, 12 x 8 x 4 ins., firmly set 8 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, from which the remains of the original bearing trees:

A cedar stump, 40 ins. diam., bears S. 29° E., 28 lks. dist., with illegible scribe marks visible on burned blaze.

A cedar stump, 30 ins. diam., bears N. 81° W., 116 lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 26 S
R 10 W
 $\frac{1}{4}$ S 12
1973

from which new bearing trees

A fir, 8 ins. diam., bears S. 43 $\frac{1}{2}$ ° W., 14 lks. dist., mkd. $\frac{1}{4}$ S12 BT.

A fir, 8 ins. diam., bears N. 27° W., 46 lks. dist., mkd. $\frac{1}{4}$ S12 BT.

Deposit corner stone alongside iron post.

Land, mountainous.

Soil, rocky clay.

Timber, cedar, fir, hemlock, alder, maple, yew, madrone, chinquapin, and myrtle; undergrowth, fern, vine maple, salal, poison oak, Oregon grape, rhododendron, arrowwood, hazel, and huckleberry.

Dependent Resurvey of a Portion of the South Boundary,
T. 26 S., R. 9 W., Willamette Meridian, Oregon

(Restoring the survey by John W. Meldrum,
U. S. Deputy Surveyor, in 1896,
and the amended survey by Robert C. Bonser,
U. S. Compassman, in 1901)

From the cor. of secs. 33 and 34 only, on the S. bdy. of the Tp., monumented with an iron pipe, 12 ins. long, $\frac{3}{4}$ in. diam., firmly set, projecting 4 ins. above ground, from which the remains of the original bearing trees:

A sawed fir stump, 70 ins. diam., bears N. 42° E., 21 lks. dist., with scribe marks BT visible on bark. (Record, 24 lks.)

A sawed fir stump, 72 ins. diam., bears S. 12° E., 50 lks. dist., with scribe marks T27S R9W S3 BT visible on bark. (Record, S. 57 $\frac{1}{2}$ ° E., 52 lks.)

A sawed fir stump, 65 ins. diam., bears S. 22° W., 29 lks. dist., with scribe marks T27S R9W S4 BT visible on bark. (Record, S. 8° W., 27 lks.)

At the corner point

C.S. File No 65/52-198

Dependent Resurvey of a Portion of the South Boundary,
T. 26 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 9 W S 33 S 34 S 4 T 27 S 1973</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears N. 30° E., 33½ lks. dist., mkd. T26S R9W S34 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 60° W., 26 lks. dist., mkd. T26S R9W S33 BT.</p> <p>N. 89° 57' W., on the S. bdy. of sec. 33, marking and blazing the true line.</p> <p>Descend 25 ft. over W. slope, through moderate timber and undergrowth.</p>
1.00	Burnt Mountain Access Road, asphalt surfaced, 25 lks. wide, bears N. 5° W. and S. 5° E.
4.95	Spring branch, 1 lk. wide, course N. 80° W.; desc. 25 ft. along branch.
7.90	Leave spring branch, course SE.; desc. 200 ft. over general W. slope.
19.50	Waterfall, 5 lks. wide, 35 ft. high, drains N. 85° W.; desc. 100 ft. over NW. slope.
25.00	Spur, slopes N. 30° W.; desc. 400 ft. over general W. slope.
32.30	Ravine, drains NW.; desc. 200 ft. over NW. slope.
35.37	<p>From this point, a locally established cor. bears South, 0.14 chs. dist., monumented with an iron pin, ½ in. diam., firmly set, projecting 6 ins. above ground, from which a locally mkd. bearing tree:</p> <p style="padding-left: 40px;">A hemlock, 11 ins. diam., bears S. 60° W., 32 lks. dist., with scribe marks X BT visible on open blaze.</p> <p>Descend 75 ft. over NW. slope.</p>
39.84	<p>Point for the ¼ sec. cor. of sec. 33 only, at proportionate distance there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 26 S R 9 W ¼ S 33 1973</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears N. 82½° E., 43 lks. dist., mkd. ¼ S33 BT.</p>