

FIRST RE-ESTABLISHMENT
GCDB 300340

Quarter corner common to Sections 20 and 21, Township 32 South, Range 1 West, W.M.

Fd. original stone 18x8x8 ins. with 1/4 scribed on the westerly face lying on its easterly face. At base of said stone set an iron pipe 1 ins. in diam., 36 ins. long 34 ins. in the ground with bronze disc. mkd:

JACKSON COUNTY
T32S R1W
20|21
1984

from which:

Evidence of original bearing tree; stump hole, brs. N32°W, 2.64 ft. (There is indication, in this general area, that there was a heavy forest fire near the turn of the century).

New references:

Douglas Fir, 7 ins. diam., brs. N44°06'E, 27.93 ft. (8.51 m) scribed "CS" "BT".

Douglas Fir, 15 ins. diam., brs. S32°40'E, 49.50 ft. (15.08 m) scribed "CS" "BT".

The original stone was placed along side of pipe with rock mound built along side of monument.

This corner falls on slight easterly slope in a clear cut about 10 years old and about 45 ft. West of a new North and South line.

May 24, 1984
E.McGinty
B.Malotte

Edward McGinty
County Surveyor

FILED
Date: 9-13-05 By: JC
This survey consists of:
Map: _____
Name of _____
Corner Ref: 65/54-37
DOUGLAS COUNTY
SURVEYOR

C.S. File No 65/54-37