

MAP OF SURVEY

LOCATED in Section 26, T.30S., R.8W., WM
in Douglas County, Oregon.

February 21, 2005

SURVEYED FOR: *SENECA JONES TIMBER CO.
P.O. BOX 2129
ROSEBURG, OREGON*

SURVEYED BY: *DAVID EDWARDS LAND SURVEYING
P.O. BOX 361
OAKLAND, OREGON 97462
PHONE: (541) 459-0512*

FILED
Date: 2-24-2005 By: NW
This survey consists of:
Map: CS 65/55-1
Narrative: _____
Corner Rpt: _____
**DOUGLAS COUNTY
SURVEYOR**

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**
David A. Edwards
OREGON
JULY 26, 1988
DAVID A. EDWARDS
2339
RENEWS 12/31/05

C.S. File No 65/55-1

LEGEND

- ⊙ INDICATES DOUGLAS COUNTY SURVEYOR BRASS CAP FOUND.
- INDICATES 5/8" DIAM. IRON ROD W/ALUM. CAP FOUND PER M 92-52.
- INDICATES LINE POSTED, BLAZED AND FLAGGED THIS SURVEY.
- () DENOTES RECORD DATA PER M 92-52. SCALE: 1" = 1000'
- BASIS OF BEARINGS: M 92-52 AS SHOWN.

NARRATIVE

THE PURPOSE OF THIS SURVEY IS TO MARK THOSE LINES SHOWN AS BOLD HEREON. RANDOM TRAVERSES WERE RUN NEAR THE SUBJECT BOUNDARIES TYING IN THE CONTROLLING CORNERS. THE TRUE LINE WAS THEN COMPUTED AND OFFSETS MADE THERETO. THE TRUE LINE WAS MARKED BY BLAZING TREES ON EACH SIDE OF LINE, BY SETTING 6 FOOT STEEL POSTS ALONG THE LINE AT INTERVALS OF 200 FEET OR LESS AND BY HANGING LIBERAL AMOUNTS OF RED FLAGGING ALONG SAID TRUE LINE. NEW BEARING TREES ARE SCRIBED ACCORDING TO THE 1973 MANUAL AND MEASURED TO CENTER OF TREE AT ROOT CROWN.

FIELD CREW: BRANT MILLER AND ERIC SPRINKLE.
EQUIPMENT: NIKON TOTAL STATION.
COMPS. AND DRAFTING: DAVID EDWARDS.

C.S. File No 65/55-1

