

MAP OF SURVEY

LOCATED in Section 12, T.24S., R.4W., W.M. Douglas Co., Ore.

May 24, 2006

SURVEYED FOR:

SENECA JONES TIMBER CO.
P.O. BOX 2129
ROSEBURG, OREGON 97470

SURVEYED BY:

DAVID EDWARDS LAND SURVEYING
P.O. BOX 361
OAKLAND, OREGON 97462
PHONE: (541) 459-0512

FILED

Date: 5-30-2006 By: JC

This survey consists of:

Map: C.S. 65/57-9

Narrative: _____

Corner Rpt: _____

DOUGLAS COUNTY
SURVEYOR

REGISTERED
PROFESSIONAL
LAND SURVEYOR

David A. Edwards

OREGON
JULY 26, 1988
DAVID A. EDWARDS

2339
RENEWED 12/31/07

LEGEND

⊙ INDICATES B.L.M. OR COUNTY SURVEYOR BRASS CAP FOUND.

() DENOTES RECORD DATA PER B.L.M. RESURVEY.

————— INDICATES LINE BLAZED AND POSTED THIS SURVEY.

SCALE: 1" = 1000'

BASIS OF BEARINGS: B.L.M. RESURVEY AS SHOWN.

NARRATIVE

THE PURPOSE OF THIS SURVEY IS TO MARK THOSE BOUNDARIES SHOWN AS BOLD LINES HEREON. RANDOM TRAVERSES WERE RUN, CONTROLLING MONUMENTS TIED TOGETHER AND OFFSETS MADE. THE BOUNDARIES WERE THEN MARKED BY BLAZING TREES ON EACH SIDE OF LINE, BY SETTING 6 FOOT STEEL POSTS ALONG THE LINES AT INTERVALS OF 200 FEET OR LESS AND BY HANGING LIBERAL AMOUNTS OF RED FLAGGING ALONG THE TRUE LINE.

FIELD CREW: BRANT MILLER AND ERIC SPRINKLE.

EQUIPMENT: NIKON TOTAL STATION.

COMPS. AND DRAFTING: DAVID EDWARDS.

SECTION CORNER
B.T.'S PER M 133-54

(N.0°06'E. 3329.04')
N.0°01'56"E. 3329.23'



1/4 CORNER
15" FIR S.31°E., 35.3'
17" HEMLOCK N.49 1/2°W., 11.2'
BOTH WITH HEALED BLAZE.

BASE BEARING (3320.46')
N.0°06'00"E. 3319.24'

SECTION CORNER
23" FIR N.78°E., 77.9'
41" CEDAR S.68°E., 39.6'
13" FIR S.74°W., 20.5'
35" FIR N.7°W., 68.6'
ALL WITH HEALED BLAZE.

1/4 CORNER
42" FIR N.78°E., 30.4'
19" CEDAR N.56°E., 17.5'
25" FIR SNAG S.9°E., 39.7'
ALL WITH HEALED BLAZE

N.89°46'21"E. 2632.94'