

MAP OF SURVEY

LOCATED in the SE 1/4 of Section 8,
T. 22 S., R. 6 W., W.M. in
Douglas County, Oregon.

July 10, 2006

SURVEYED FOR: *DAVE MENSHIK*
MARY GARRETT
DRAIN, OREGON

SURVEYED BY: *DAVID EDWARDS LAND SURVEYING*
P.O. BOX 361
OAKLAND, OREGON 97462
PHONE: (541) 459-0512

FILED
Date: <u>7-25-2006</u> By: <u>JC</u>
This survey consists of:
Map: <u>C.S. 65/57-13</u>
Narrative: _____
Corner Rpt: _____
DOUGLAS COUNTY SURVEYOR

REGISTERED
PROFESSIONAL
LAND SURVEYOR

David A. Edwards

OREGON
JULY 26, 1908
DAVID A. EDWARDS
2339
RENEWS 12731707

LEGEND

- INDICATES 5/8" DIAM. STEEL PIN W/CAP FOUND AT THE SE 1/16 COR. SEC. 8 PER M 135-36.
- INDICATES 5/8" X 30" STEEL REBAR W/RED PLASTIC CAP MKD. "D.A. EDWARDS-LS 2339" SET AT THE SOUTH 1/16 CORNER COMMON TO SECTIONS 8 AND 9.

SCALE: 1" = 300'

X—X—X FENCE LINE

BASIS OF BEARINGS: EXISTING CONTROL PER MY SURVEY M 135-36.

NARRATIVE

THE PURPOSE OF THIS SURVEY IS TO IDENTIFY AND MARK THE SOUTH LINE OF THE NE 1/4 OF THE SE 1/4 OF SECTION 8 AND TO SET THE SOUTH 1/16 CORNER COMMON TO SECTIONS 8 AND 9. I UTILIZE EXISTING CONTROL POINTS AND DATA RELATIVE TO THE SUBDIVISION OF SECTION 8 PER MY SURVEY M 135-36 TO ACCOMPLISH THIS TASK AS SHOWN HEREON.

AT THE SET SOUTH 1/16 CORNER:

- A 7" DIAM. FIR SCRIBED "S 1/16 S9 BT" BEARS S.62°E., 31.3 FEET.
- A 10" DIAM. FIR SCRIBED "S 1/16 S8 BT" BEARS S.44°W., 2.6 FEET.

FIELD CREW: BRANT MILLER AND ERIC SPRINKLE.

EQUIPMENT: NIKON TOTAL STATION.

COMPS. AND DRAFTING: DAVID EDWARDS.

