


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

GLO survey by William Bushey, Deputy Surveyor, under Contract #620, dated June 17, 1893 (DCSO records Vol. 18 Page(s) 7695):
A Sugar Pine 34" dia., on line marked with 2 notches on E. and W. sides.

DIAGRAM



Gerald V. Nygren, L.S. #1035 - For: U.S. Forest Service - March 15, 1988
C.S. File 63/69-24:

Found 46" Pine (angle point) line tree with USFS sign 52-2 attached.

New BTs-

A 13" D.Fir bears N.78°W., 26.4 ft. scribed "T31S R3W S36 LINE TREE BT" with brass washer nailed to lower end of blaze.

A 7" D.Fir bears S.24°E., 14.0 ft. scribed "S1 LINE TREE BT" with brass washer nailed to lower end of blaze.

Bearing tree signs and monument signs were placed on all bearing trees and a 6" red band and face blazes were painted on all bearing trees.

Description of corner evidence found:

A 48" P.Pine with USFS Sign 54-9 nailed to the east side and a faded red paint band around the trunk.

From which bearing trees by Nygren in 1988:

A 13" D.fir sawed stump pushed 30 feet out of position by road construction bears S.60°W., 13.5 feet with scribing "BT" visible on an open face. (Rec. N.78°W., 26.4 feet)

A root hole bears S.24°E., 14.0 feet with a uprooted and rotted 7" D.fir laying alongside with scribe marks "SI LINE TREE BT" visible on an open face.

Description of monument and accessories established to perpetuate the original location of this corner:

I scribe new bearing trees:

A 15" D.fir bears N.40°E., 30.8 feet, scribed "AP S36 BT".

A 8" D.fir bears S.44°E., 23.7 feet, scribed "AP S1 BT".

All new bearing trees have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearings are taken to the center of the tree at the root crown and distances are measured to an aluminum nail in the root crown at the side and center of the tree. All bearing trees have a 6" red band painted around the tree and the blazed face painted red and Bearing Tree and USFS Land Survey Monument sign nailed to the tree.

Corner renewal date: June 29, 2007

Party Chief: Lester Fanning, PLS 2664

Witnesses: Scott McCurdy, Sam Clayton

Warren Knight Staff Compass -- declination 16 1/2°E

By: BTS Engineering & Surveying, Inc.
431 SE Main
Roseburg, OR 97470



RENEWAL 12/31/07

FILED

Date: 11-7-2007 By: JC

This survey consists of:

Map: _____

Name/Date: _____

Corner Rpt: 65/60-43

DOUGLAS COUNTY
SURVEYOR

Douglas County Surveyor's Office

Douglas County, Oregon

I hereby certify that the written instrument was filed in this office for record on the 7 day of NOVEMBER, 2007.

Rorney Ware (County Official) by [Signature] (Deputy)

C.S. File No 65/60-43