

**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**History of original corner establishment:**

William J. Ruppert, PLS 866, per under Survey M 84-6  
with CS 58/143-25 Narrative dated May, 1980:  
Set: 2"x30" aluminum pipe with 2 1/2" magnetized aluminum cap marked  
as shown:

T32S R2W  
NW 1/16 S30  
RLS 866  
1980

**DIAGRAM**

T32S R2W  
NW 1/16 S30

GCDB 120260

New BT: 21" W. fir S.28°34'E., 16.3 ft. "NW 1/16 S30 BT"  
8" W. fir S.57°15'W., 38.7 ft. "NW 1/16 S30 BT"  
Attached 3/4" brass washer marked "LS 866" to lower blaze of each new BT.

**Description of corner evidence found:**

A 2 1/2" aluminum post, firmly set, projecting 10" above the ground and flush with the top of a 10" high x 36" diam. Mound of stone with a 2 1/2" aluminum cap stamped:

T32S R2W  
NW 1/16 S30  
RLS 866  
1980

From which bearing trees by Ruppert in 1980:

A 24" W. fir snag bears S.29°E., 16.3 ft. with a healed double blaze. (Rec. S.28°34'E.)  
A 14" W. fir bears S.57°W., 38.7 ft. with a healed double blaze. (Rec. S.57°15'W.)

**Description of monument and accessories established to perpetuate the original location of this corner:**

I scribed a new bearing tree:

A 6" hemlock bears S.7°E., 7.2 feet, scribed "NW 1/16 S30 BT".

All new bearing trees have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearings are taken to the center of the tree at the root crown and distances are measured to an aluminum nail in the root crown at the side and center of the tree. All bearing trees have a 6" red band painted around the tree and the blazed face painted red and Bearing Tree and USFS Land Survey Monument sign nailed to the tree.

Corner renewal date: July 27, 2007  
Party Chief: Lester Fanning, PLS 2664  
Witnesses: Tony Bellando, Sam Clayton  
Warren Knight Staff Compass – declination 19°E

By: BTS Engineering & Surveying, Inc.  
431 SE Main  
Roseburg, OR 97470



RENEWAL 12/31/07

FILED

Date: 11-7-2007 By: JK

This survey consists of:

Map: \_\_\_\_\_

Narrative: \_\_\_\_\_

Corner Rpt: 65/60-48

DOUGLAS COUNTY  
SURVEYOR

Douglas County Surveyor's Office Douglas County, Oregon  
I hereby certify that the written instrument was filed in this office for record  
on the 7 day of NOVEMBER, 2007.

Romey Ware by [Signature]  
(County Official) (Deputy)

C.S. File No 65/60-48