

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract No.746, dated May 5, 1902, - (DCSO records Vol. 11 Page 4825)

**DIAGRAM
T27S R1W
1/4
S21 S22
400340**

Set a basalt stone, 20x10x8 ins., 15" in stone mound, marked 1/4 on West face, from which:

- A Fir, 24 ins. in diam. bears S.72°E., 19 lks. scribed "1/4 S 22 BT".
- A Hemlock, 30 ins. in diam. bears N.50°W., 17 lks. scribed "1/4 S21 BT".

U.S. Forest Service – Jim S. Peterson, dated November, 1978 (per M 70-41, and D.C.S.O., Renewal # 145)
No trace of original corner or BT's.

Set Brass tablet in rock outcropping: "T27S R1W 1/4 S21 S22 1978 PLS 1084"

- New BTs: 16" Fir N.74 3/4 °E., 65.2 ft. scribed "1/4 S22 BT".
- 12" Hemlock N.54 1/2 °W., 6.1 ft. scribed "1/4 S21 BT".

FILED
Date: 7-23-2008 By: JC
This survey consists of:
Map: _____
Narrative: _____
Corner Rpt: 65/63-23

Description of corner evidence found:

A 3" diam. brass tablet set in rock outcropping stamped:

T27S R1W
1/4
S21 S22
1978 PLS 1084

**DOUGLAS COUNTY
SURVEYOR**

from which bearing trees by Peterson in 1978:

- A 25" D. Fir bears N.74 3/4 °E., 65.2 ft. with healed double blaze. (Rec. N.74 3/4 °E., 65.2 ft.)
- A 22" uprooted Hemlock blown down to the Southeast over the rock outcropping creating huge root wad with boulders and soil hanging over corner monument, which is still accessible. (Rec. N.54 1/2 °W., 6.1 ft.)

Description of monument and accessories established to perpetuate the original location of this corner:

I scribe new bearing tree:

A 17" Hemlock bears S.57°W., 20.8 feet, scribed "1/4 S21 BT" on double face.

All new bearing trees have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearings are taken to the center of the tree at the root crown and distances are measured to an aluminum nail in the root crown at the side and center of the tree. All bearing trees have a 6" red band painted around the tree and the blazed face painted red and Bearing Tree and USFS Land Survey Monument sign nailed to the tree.

Corner renewal date: July 7, 2008
Party Chief: Lester Fanning, PLS 2664
Witnesses: Adam DeGroot, Scott McCurdy, and Rick Sanford
Warren Knight Staff Compass – declination 18°E
By: **BTS Engineering & Surveying, Inc.**
431 SE Main
Roseburg, OR 97470



Douglas County Surveyor's Office Douglas County, Oregon
I hereby certify that the written instrument was filed in this office for record on the 23rd day of July, 2008.

Romey Ware by [Signature]
(County Official) (Deputy)

C.S. File No 65/63-23