

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

GLO survey by Homer D. Angell, Deputy Surveyor, under Contract No.746, dated May 5, 1902, - (DCSO records Vol. 11 Page 4825)

DIAGRAM
T27S R1W
1/4
S21 | S22
400340

Set a basalt stone, 20x10x8 ins., 15" in stone mound, marked 1/4 on West face, from which:

A Fir, 24 ins. in diam. bears S.72°E., 19 lks. scribed "1/4 S 22 BT".

A Hemlock, 30 ins. in diam. bears N.50°W., 17 lks. scribed "1/4 S21 BT".

U.S. Forest Service – Jim S. Peterson, dated November, 1978 (per M 70-41, and D.C.S.O., Renewal # 145)
No trace of original corner or BT's.

Set Brass tablet in rock outcropping: "T27S R1W 1/4 S21 S22 1978 PLS 1084"
New BTs: 16" Fir N.74 3/4 °E., 65.2 ft. scribed "1/4 S22 BT".
12" Hemlock N.54 1/2 °W., 6.1 ft. scribed "1/4 S21 BT".

FILED

Date: 11-24-2008 By: X
This survey consists of:
Map: Replaces CS 65/63-23
Narrative: _____
Corner Rpt: 65/63-37

Description of corner evidence found:

A 3" diam. brass tablet set in rock outcropping stamped:

T27S R1W
1/4
S21 | S22
1978 PLS 1084

DOUGLAS COUNTY
SURVEYOR

from which bearing trees by Peterson in 1978:

A 25" D. Fir bears N.74 3/4 °E., 65.2 ft. with healed double blaze. (Rec. N.74 3/4 °E., 65.2 ft.)

A 22" uprooted Hemlock blown down to the Southeast over the rock outcropping creating huge root wad with boulders and soil hanging over corner monument, which is still accessible. (Rec. N.54 1/2 °W., 6.1 ft.)

Description of monument and accessories established to perpetuate the original location of this corner:

I scribe new bearing tree:

A 17" W.Fir bears S.57°W., 20.8 feet, scribed "1/4 S21 BT" on double face.

All new bearing trees have double blazed faces with a brass washer stamped "PLS 1941" nailed into the lower blaze. Bearings are taken to the center of the tree at the root crown and distances are measured to an aluminum nail in the root crown at the side and center of the tree. All bearing trees have a 6" red band painted around the tree and the blazed face painted red and Bearing Tree and USFS Land Survey Monument sign nailed to the tree.

Corner renewal date: July 7, 2008

Party Chief: Lester Fanning, PLS 2664

Witnesses: Adam DeGroot, Scott McCurdy, and Rick Sanford

Warren Knight Staff Compass -- declination 18°E

By: BTS Engineering & Surveying, Inc.
431 SE Main
Roseburg, OR 97470

Douglas County Surveyor's Office

Douglas County, Oregon

I hereby certify that the written instrument was filed in this office for record on the 24th day of November, 2008.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Kristian O. DeGroot

OREGON
JULY 17, 1981
KRISTIAN O. DeGROOT
1941

RENEWAL 12/31/09

Romey Ware
(County Official)

by *Roy A. [Signature]*
(Deputy)

C.S. File No 65/63-37