

Index

**CORNER RECORD (SEARCH)**

File No. R-7 PROJ. NO. \_\_\_\_\_ CORNER 1/4  
 TOWNS. 27S RANGE 1W R.D. Glide COUNTY Douglas GCDB# 240300  
 MERID. WM FOREST UMPQUA STATE OR

<p><b>CORNER DIAGRAM</b></p>	<p><b>DESCRIBE CORNER MONUMENT FOUND</b>                  Found 1" Iron Pipe with 2-1/2" County Surveyors Office Brass Cap                  Projecting 15" above ground, cap marked "T27S R1W S20 1/4 S29 1969"                  "County Surveyors Office"</p> <p><b>DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND</b></p> <table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>DIA</th> <th>TYPE</th> <th>BEARS</th> <th>DIST</th> <th>FACE/MARKINGS</th> </tr> </thead> <tbody> <tr> <td>3/4"</td> <td>Rebar</td> <td>South</td> <td>0.2 FT.</td> <td>No Cap</td> </tr> <tr> <td>19"</td> <td>Fir</td> <td>N 36° 15' W</td> <td>39.8 FT.</td> <td>Healed Single Blaze</td> </tr> <tr> <td>INDT</td> <td>Stump</td> <td>S 39° 15' W</td> <td>24.4 FT.</td> <td>Decayed rotting stump</td> </tr> <tr> <td>9"</td> <td>Fir Snag</td> <td>S 18° 30' E</td> <td>48.5 FT.</td> <td>Scribing visible on Part. Healed Single Blaze</td> </tr> </tbody> </table>	DIA	TYPE	BEARS	DIST	FACE/MARKINGS	3/4"	Rebar	South	0.2 FT.	No Cap	19"	Fir	N 36° 15' W	39.8 FT.	Healed Single Blaze	INDT	Stump	S 39° 15' W	24.4 FT.	Decayed rotting stump	9"	Fir Snag	S 18° 30' E	48.5 FT.	Scribing visible on Part. Healed Single Blaze
DIA	TYPE	BEARS	DIST	FACE/MARKINGS																						
3/4"	Rebar	South	0.2 FT.	No Cap																						
19"	Fir	N 36° 15' W	39.8 FT.	Healed Single Blaze																						
INDT	Stump	S 39° 15' W	24.4 FT.	Decayed rotting stump																						
9"	Fir Snag	S 18° 30' E	48.5 FT.	Scribing visible on Part. Healed Single Blaze																						
<p><b>PHOTO IDENTIFICATION DATA</b></p> <p>Photo No. <u>None</u></p> <p>Filed At. <u>None</u></p> <p>Obj. Ident. <u>None</u></p> <p>Ident. By <u>None</u></p> <p style="text-align: center;">Signature _____</p>	<p><b>DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER</b></p> <p>Corner is on a flat, in a old clear cut unit approx 700' south of Road 2792                  Follow posted line south from 2792 crossing of N-S Centerline of S20</p>																									
<p><b>PLANE COORDINATE POSTION DATA</b></p> <p>State <u>OR</u> Zone <u>UTM-10M</u></p> <p>North <u>4782824</u></p> <p>East <u>512619</u></p> <p>Estab. By <u>GCDB</u></p> <p style="text-align: center;">Signature _____</p>	<p><b>DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER</b></p> <p>Corner is on a flat, in a old clear cut unit approx 700' south of Road 2792                  Follow posted line south from 2792 crossing of N-S Centerline of S20</p>																									

Signature	Title	Division	Hedquarters	Date	7100-52 (3/68)
	LIST	LANDS	SPRINGFIELD	1/17/2011	

**CORNER RECORD (PERPETUATION)**

<p><b>MONUMENT : DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT</b></p>	<div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">                 REGISTERED                  PROFESSIONAL                  LAND SURVEYOR             </div> <p style="font-size: 1.2em; margin: 0;"><i>John Ransom</i></p> <div style="border: 1px solid black; padding: 2px; margin-top: 5px; font-size: 0.8em;">                 OREGON  <small>REV 21, 1992</small>                  JOHN C. RANSOM                  2561             </div>						
<p><b>ACCESSORIES : DESCRIBE NEW BT's WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE</b></p> <p>Painted BT's red with 6" wide band at head height, painted face blaze, new nails on tags. Added New Tree:</p> <table style="width:100%; border: none;"> <tr> <td style="width:15%;">16"</td> <td style="width:15%;">Fir</td> <td style="width:15%;">Bears</td> <td style="width:15%;">S 51° 45' W</td> <td style="width:15%;">18.2 FT.</td> <td style="width:20%;">Scribed "1/4S29" "BT" on Double Blaze 17.6' to washer</td> </tr> </table> <p>All new trees include a 3/4" brass washer nailed between B and T on lower blaze, Washer stamped "LS2561"</p>		16"	Fir	Bears	S 51° 45' W	18.2 FT.	Scribed "1/4S29" "BT" on Double Blaze 17.6' to washer
16"	Fir	Bears	S 51° 45' W	18.2 FT.	Scribed "1/4S29" "BT" on Double Blaze 17.6' to washer		
<p><b>DONE BY:</b> <u>Jonathan Drew</u> TITLE <u>LSIT</u> DATE <u>1/17/2011</u> PLS NO./AGENCY/STATE <u>LSIT-Maine</u></p> <p>Certified Cor. Record Prepared ? _____ Filed At: _____ DATE _____</p>							
<p style="text-align: center;"><b>REMARKS</b></p>							

Index File No R-7 T. 27S R. 1W M. WM Proj No. \_\_\_\_\_ 0 Cor. 1/4

John Ransom  
 Boundary Lead  
 Siuslaw, Willamette, Umpqua, and Rogue River-Siskiyou National Forests  
 3106 Pierce Parkway  
 Springfield, OR 97477  
 Ph 541-225-6446  
 Email: jransom@fs.fed.us

FILED

Date: 4-6-2014 By: JC  
 This survey consists of:  
 Map: \_\_\_\_\_  
 Narrative: \_\_\_\_\_  
 Corner File: CS 65/72-16

DOUGLAS COUNTY  
 SURVEYOR

C.S. File No 65/72-16