

FILED
 Date: 11/30/2011 By: JC
 This survey consists of:
 Map: _____
 Narrative _____
 Corner RptCS 65/72-42

**DOUGLAS COUNTY
SURVEYOR**

USDA-FOREST SERVICE

Index
File No. T-9 **PROJ. NO.** _____ **CORNER** 1/4
TOWNS. 32S **RANGE** 3W **R.D.** Tiller **COUNTY** Douglas **GCDB#** 300240
MERID. W.M. **FOREST** Umpqua **STATE** Oregon

<p>CORNER DIAGRAM</p>	<p>DESCRIBE CORNER MONUMENT FOUND Found 2.5" Brass Cap on 1.25" G. Iron Pipe Projecting 12" above Ground Marked "County Surveyors Office 1969" "T32S R3W 1/4 S28 S29"</p> <p>DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>DIA</th> <th>TYPE</th> <th>BEARS</th> <th>DIST</th> <th>FACE/MARKINGS</th> </tr> </thead> <tbody> <tr> <td>18"</td> <td>Fir Windfall</td> <td>S 77-1/4 E</td> <td>22.7 FT</td> <td>to Roothole, Cut and log lays on face</td> </tr> <tr> <td>INDT</td> <td>Pine Snag</td> <td>N 3 W</td> <td>5.8 FT</td> <td>"BT" on open lower face, good scar</td> </tr> <tr> <td>INDT</td> <td>Pine Stob</td> <td>N 85-1/4 W</td> <td>4.2 FT</td> <td>Rotten no marks visible</td> </tr> <tr> <td></td> <td>Fir</td> <td>(S 75 E)</td> <td>(12.5 FT)</td> <td>No Trace Remains</td> </tr> </tbody> </table>	DIA	TYPE	BEARS	DIST	FACE/MARKINGS	18"	Fir Windfall	S 77-1/4 E	22.7 FT	to Roothole, Cut and log lays on face	INDT	Pine Snag	N 3 W	5.8 FT	"BT" on open lower face, good scar	INDT	Pine Stob	N 85-1/4 W	4.2 FT	Rotten no marks visible		Fir	(S 75 E)	(12.5 FT)	No Trace Remains
DIA	TYPE	BEARS	DIST	FACE/MARKINGS																						
18"	Fir Windfall	S 77-1/4 E	22.7 FT	to Roothole, Cut and log lays on face																						
INDT	Pine Snag	N 3 W	5.8 FT	"BT" on open lower face, good scar																						
INDT	Pine Stob	N 85-1/4 W	4.2 FT	Rotten no marks visible																						
	Fir	(S 75 E)	(12.5 FT)	No Trace Remains																						
<p>PHOTO IDENTIFICATION DATA Photo No. <u>None</u> Filed At. <u>None</u> Obj. Ident. <u>None</u> Ident. By <u>None</u> Signature _____</p>	<p>DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER From Interstate take exit 87 East to Snow Mountain Road, Follow to Spur Road 900, 300 on quads, .75 Miles to South Bearing Spur Follow .5 Mi to intersection with closed spur, lies about 20 FT west of Main Spur about 150 Feet south of intersection</p>																									
<p>LAT/LONG POSTION DATA SYSTEM <u>NAD83 CORS 96 EP:2002</u> North <u>42° 45' 33.7280724"</u> West <u>123° 04' 06.3807276"</u> Estab. By <u>OPUS BASE -- RTK TIE</u></p>																										

Signature _____ Title _____ Division _____ Hedquarters _____ Date 7100-52 (3/68)

CORNER RECORD (PERPETUATION)

<p>MONUMENT : DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT Brushed Around Corner</p>	<p>REGISTERED PROFESSIONAL LAND SURVEYOR</p> <p><i>John Ransom</i></p> <p>OREGON JULY 21, 1992 JOHN C. RANSOM 2561</p>
<p>ACCESSORIES : DESCRIBE NEW BT's WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE Painted BT's and Brushed from corner to BT's</p> <p>NEW BT's 6" Fir Bears N 70-3/4 W 30.8 FT Marked "1/4 S29" "BT" on Double Blaze, Brass Washer nailed to lower face "LS 2561" 8" Pine Bears S 20 E 34.1 FT Marked "1/4 S28" "BT" on Double Blaze, Brass Washer nailed to lower face "LS 2561"</p>	
<p>DONE BY: <u>Jonathan Drew</u> TITLE <u>LSIT</u> DATE <u>11/16/11</u> PLS NO./AGENCY/STATE <u>SIT10002506 - Maine</u> Certified Cor. Record Prepared? <u>Yes</u> Filed At: <u>Douglas Co. Surveyor</u> DATE <u>TBD</u></p>	
<p style="text-align: center;">REMARKS</p> <p>Measurements taken with Leica 1203 Total Station Tied to GPS Bearing, Bearing Basis is OR State Plane South Zone Distances at ground</p>	

Index File No T-9 T. 32S R. 3W M. W.M. Proj No. _____ Cor. 1/4

John Ransom
 Boundary Lead
 Siuslaw, Willamette, Umpqua, and Rogue River-Siskiyou National Forests
 3106 Pierce Parkway
 Springfield, OR 97477
 Ph 541-225-6446
 Email: jransom@fs.fed.us

C.S. File No 65/72-42