


CERTIFIED LAND CORNER RECORD

History of original corner establishment: T. 29 S., R. 1 W., W. M. Donovan C. Harris, BLM Cadastral Surveyor, established the East One-Sixteenth corner of sections 31 and 6 by single proportionment in 1971. He set a 2-1/2 inch diameter iron post with a brass cap attached, marked:


GCBD No. 160100

He marked bearing trees: a 10" fir, N. 7° E., 29 lks., scribed "E 1/16 31 BT"; and a 9" fir, S. 9-1/2° W., 37 lks., scribed "E 1/16 S6 BT".



Bruce A. Shaner, LS 443, visited the corner in 1973 on Douglas County survey map M49-43. He found the brass cap marked as shown. He found the two existing bearing trees: a 10" white fir., N. 7° E., 19.7 feet, scribes vis.; and a 10" white fir, S. 9-1/2° E., 24.9 feet, scribes vis.

Description of corner evidence found: March 1, 2011
I found a 2-3/4 inch outside diameter iron pipe, firmly set, projecting 6 inches above a 3-foot diameter mound of stone, with a 3-1/2 inch diameter brass cap marked as shown:



From which the following bearing trees by Harris in 1971:

- 18" diameter red fir, bears N. 7° E., 19.7 feet, with healed single blaze.
- 16" diameter white fir, bears S. 9-1/2° E., 24.9 feet (record S. 9-1/2° W.), with healed single blaze.

Description of monument and accessories I established to perpetuate the original location of this corner:

No new measurements were taken for this corner renewal. This report is to confirm the SE quadrant for the 1971 bearing tree as reported by Shaner in 1973. The BLM bearing tree tag from 1971 states "N 09-1/2°W". Also, there is no date stamped on the brass cap.

Leonard E. Herzstein, L.S. 2150
Umpqua National Forest
2900 NW Stewart Parkway
Roseburg, OR 97471

Certificate renews June 30, 2013

DEC. 01, 2011

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 26, 1985
LEONARD E. HERZSTEIN
2150

FILED
Date: 12/5/2011 By: JC
This survey consists of:
Map: _____
Narrative: _____
Corner Rpt: 65/72-46

DOUGLAS COUNTY
SURVEYOR

C.S. File No 65/72-46

