

**FIRST RE-ESTABLISHMENT**  
GCDB 140600

Quarter corner common to Sec. 6 and 7, Twp. 31 South, Range 2 East, W.M.  $V=20\frac{1}{2}^\circ$

Fd., firmly set, the original 15x10x6 ins. (38x20x17 cm) stone; record; 10x8x7 ins. (25x20x17 cm), mkd. " $\frac{1}{4}$ " on North face.

I replace said stone with a 1x36 ins. (2.5x91 cm) G.I. pipe, set 28 ins. (71 cm) in the ground with a  $2\frac{1}{2}$  ins. (6.35 cm) bronze disc mkd:

JACKSON COUNTY 1978

T31S R2E

6

$\frac{1}{4}$ S—

7

from which, the single remaining original bearing tree recorded by P.Applegate in 1891, a dougale fir (record: red fir) now 58 ins. (147 cm) diam., with healed blazes, brs. record; S55°W, 29.70 ft. (9.05 m) to estimated lower face. Re-measured: 31.70 ft. (9.66 m) to center of tree.

I deposit original stone alongside corner and mark a new tree C.S. B.T.:

cedar, 33 ins. (83 cm) diam., brs. N28 $\frac{1}{2}$ °E, 28.5 ft. (8.68 m) to center of lower blaze.

Corner lies about 40 ft. (12.19 m) South of road, same road brs. West approximately 55 ft. (16.76 m).

June 6, 1978

B. Malotte

Approved by: Ed McGinty

Co. Surveyor

FILED

Date: 3-19-2012 By: JC

This survey consists of:

Map: \_\_\_\_\_

Narrative: \_\_\_\_\_

Corner rpt: CS 65/76-31

DOUGLAS COUNTY  
SURVEYOR

C.S. File No 65/76-31