

FIRST RE-ESTABLISHMENT
GCDB 200600

Section corner common to Sec. 5, 6, 7 and 8, Twp. 31 South, Range 2 East, W.M. $V=17\frac{1}{2}^\circ$

Found tipped over, the original 17x15x8 ins. (43x38x20 cm) stone; Record; 12x12x10 ins. (30x30x25 cm) marked (when reset up right) with 5 grooves on South and East sides.

I replace said stone with a 1x36 ins. (2.5x91 cm) G.I. pipe, set 30 ins. (76 cm) in the ground with a 2½ ins. (6.35 cm) bronze disc mkd:

JACKSON COUNTY 1978

T31S R2E

6 | 5
—+—
7 | 8

Original bearing trees recorded by P.Applegate in 1891 found as follows:

Stump remains of large fir, brs. record N23°E, 60.06 ft. (18.3 m) to estimated face.

Stump hole found at record location of original SW bT.

Stump remains of down and decayed fir, brs. record N50°W, 23.10 ft. (7.04 m).

Original SE BT now gone.

I deposit original stone alongside corner, mark new trees C.S.B.T. and take measurements to center of trees at lower blaze:

Shasta red fir, 14 ins. (35 cm) diam. brs. N43°E, 44.45 ft. (13.54 m).

Shasta red fir, 16 ins. (40 cm) diam. brs. S77°E, 48.01 ft. (14.63 m).

White fir, 13 ins. (33 cm) diam., brs. S54°W, 26.47 ft. (8.06 m).

Shasta red fir, 15 ins. (38 cm) diam. brs. N68°W, 57.77 ft. (17.6 m).

Shasta red fir, 15 ins. (38 cm) diam. brs. N68°W, 57.77 ft. (17.6 m).

Corner lies about 500 ft. (152 m) East of location marker located (on 6 ins. (15 cm) diam. fir) alongside road about 50 ft. (15.24 m) SE of cattleguard.

June 6, 1978

B. Malotte

Approved by: Ed McGinty
Co. Surveyor

FILED

Date: 2-19-2012 By: JC

This survey consists of:

Map: _____

Narrative: _____

Corner Rpt: CS 65/76-32

DOUGLAS COUNTY
SURVEYOR

C.S. File No 65/76-32